

DATASHEET

Power Cable UK BS1363A - C5 180°, black



Description

2.5 A / 250 V with fuse 3 A
Suitable for UK, Ireland, Singapur, Malaysia

General data

Connection 1	Other / BS1363A
Connection 2	Other / IEC C5 ("Mickey Mouse")
Number of cores	3
Spiralized cable	False
Protective conductor	True
With cord switch	False
Colour outer sheath	Black

Cable sheath

Material outer sheath	Polyvinyl chloride (PVC)
Temperature resistance	0 – 70 °C

Electrical characteristics

Nominal voltage	250 V
-----------------	-------

This datasheet was created automatically on 03-05-2022 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C5 180°, black

Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1) | False

Available variants

Article no.	Title	Length	Colour outer sheath	Nominal cross section conductor	Outer diameter approx.
EK499.1,8	Power Cable UK BS1363A - C5 180°, Black, 1.8 m, 3 x 0.75 mm ²	1.8 m	Black	0.75 mm ²	6.8 mm
EK499.3	Power Cable UK BS1363A - C5 180°, Black, 3.0 m, 3 x 0.75 mm ²	3.0 m	Black	0.75 mm ²	6.8 mm
EK499.5	Power Cable UK BS1363A - C5 180°, Black, 5.0 m, 3 x 0.75 mm ²	5.0 m	Black	0.75 mm ²	6.8 mm

This datasheet was created automatically on 03-05-2022 . Technical changes reserved.

