

Product datasheet

Specifications



APC Service Bypass Panel, 230V, 125A, 2x hardwire input connectors, 8x IEC 60320 C19 outlets

SBP20KRMI4U

Overview

Lead time

Main

| | |
|----------------------|---|
| Main Input Voltage | 220 V 230 V 240 V 380 V 3 phases 400 V 3 phases 415 V 3 phases |
| Main Output Voltage | 230 V |
| Other Output Voltage | 220 V 240 V |
| Number of rack unit | 4U |
| Number of cables | 1 |
| Provided equipment | Installation guide Rack mounting brackets User manual |

Physical

| | |
|---------------------|--------------|
| Colour | Black |
| Height | 17.8 cm |
| Width | 43.2 cm |
| Depth | 57.2 cm |
| Net weight | 18.78 kg |
| Mounting location | Front |
| Mounting preference | Lower |
| Mounting mode | Rack-mounted |

Input

| | |
|----------------------------|--|
| Network frequency | 50/60 Hz |
| Number of input connectors | 1 hard wire 3-wire (1P + N + E) 1 hard wire 5 wire (3P + N + E) |
| Max line current | 125 A |
| Input current limits | 125 A |
| Load capacity | 20000 VA |

| | |
|--------------|-------|
| Power factor | 0...1 |
|--------------|-------|

Output

| | |
|--------------------------------|-----------------|
| Max current draw | 125 A |
| Number of power socket outlets | 8 IEC 60320 C19 |
| Protection type | Circuit breaker |
| Efficiency | 99 % |

Conformance

| | |
|------------------------|-------------|
| Product certifications | CSA GOST |
|------------------------|-------------|

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | -20...50 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...15000 ft |
| Ambient air temperature for storage | -40...65 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0.00...15240.00 m |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 30.5 cm |
| Package 1 Width | 84.3 cm |
| Package 1 Length | 61 cm |
| Package 1 Weight | 31.36 kg |

Offer Sustainability

| | |
|-------------------|---|
| EU RoHS Directive | Under investigation |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|----------------------|
| Warranty | 2 years (parts only) |
|----------|----------------------|

Recommended replacement(s)