





## MP-B30L SERIES

## **Mobile Printer**

- Ultra Small Mobile Label Printer
- Compact & Light Weight
- Drop rating: 1.8m (6feet), IP rating: IP54
- Printing Speed: 130mm/s max
- Simple Operation & Stylish Design
- Optional Cradle for Charging

















Measuring PDA/ Instrument Smart Device

Barcode

Portable Printer

Medical Label Equipment

Model		MP-B30L
Printing	Method	Thermal line dot printing
	Number of dots/line	576
	Resolution (dots/mm)	8
	Paper width (mm)	80 <sup>+0</sup> <sub>-1</sub> / 76.2 <sup>+0</sup> <sub>-1</sub> / 58 <sup>+0</sup> <sub>-1</sub>
	Printing width (mm)	72
	Printing Speed (mm/sec) max	130
	Outside diameter of paper roll (mm) max	Ø 51
	Character matrix (H×W mm)	24 × 12, 24 × 24, 16 × 8, 16 × 16
	Character dimensions (H×W mm)	$3.0 \times 1.5$ , $3.0 \times 3.0$ , $2.0 \times 1.0$ , $2.0 \times 2.0$
Type of Paper		Roll paper, Label roll paper
Character type		Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 182 Level Kanji, Special character
Bar code		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, AZTEC
Power supply		Li-ion Battery
Communication interface		USB, Bluetooth®, W-LAN*1
Input buffer		4K bytes
Command		ESC/POS™ conformity, ZPL II™ conformity, CPCL conformity
Cutting method		Tear bar
Falling resistance		1.8m* <sup>2</sup>
IP rating		IP54* <sup>2</sup>
Operating temperature (°C)		-20 to 55
Service life: Abrasion resistance (km)		50* <sup>3</sup>
Dimensions (W×D×H mm)		105 x 126 x 58* <sup>4</sup>
Mass (g)		395*5
Standard		FCC, CE, VCCI
Bundled item		AC adapter, Battery, USB cable, Belt clip
Option		Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case
Software		Printer driver, OPOS, POS for .NET, Windows® CE(SDK), Android™(SDK),iOS SDK, Xamarin SDK, URL Print Agent

<sup>1</sup> Selected model. 12 This number is test result based on SII procedures, not guaranteed value. 13 Use recommended thermal papers. 14 Excluding protrusion 15 with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP. Windows® is the registered trademark of Microsoft Corporation(USA). Android™ is a trademark of Google Inc. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Specifications are subject to change without notice.

