

Product datasheet

Specifications



APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

SRTL2200RMXLI-NC

Overview

Presentation High density, double-conversion on-line power protection with scalable runtime.

Lead time

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated power in W 1980 W

Rated power in VA 2200 VA

Input Connection Type IEC 60320 C20
Schuko CEE 7 / EU1-16P

Output connection type 6 IEC 60320 C13
2 IEC 60320 C19

Number of rack unit 3U

Cable length 1.83 m

Number of cables 1

Battery type Li-Ion (Lithium-Ion)

Provided equipment CD with software
Communication cable
Documentation CD
Installation guide
Removable support feet
USB cable
Warranty card

General

Product web sub-family Lithium-Ion

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

Physical

Colour	Black with silver front bezel
Height	12.8 cm
Width	43.2 cm
Depth	63.9 cm
Net weight	30.5 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	40...70 Hz auto-sensing
Input voltage limits	160...275 V 40% load 80...150 V

Output

Maximum configurable power in W	1980 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Built-in bypass
Maximum configurable power in VA	2200 VA

Conformance

Product certifications	CE EAC
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA

Heat dissipation	317 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery voltage	48 V
Battery charger power	155 W rated
Battery power in VAh	605 VAh capacity 621 VAh runtime
Battery life	5...10 year(s)
Battery option	XBP48RM1U2-LI 1 1242 VAh XBP48RM1U2-LI 2 1863 VAh XBP48RM1U2-LI 3 2484 VAh XBP48RM1U2-LI 4 3105 VAh XBP48RM1U2-LI 5 3726 VAh XBP48RM1U2-LI 6 4347 VAh XBP48RM1U2-LI 7 4968 VAh XBP48RM1U2-LI 8 5589 VAh
Extended runtime	1

Communications & Management

Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.5 cm
Package 1 Width	87 cm
Package 1 Length	60 cm
Package 1 Weight	41.4 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product

Take-back Take-back program available

Contractual warranty

Warranty 5 year repair or replace

Recommended replacement(s)