



4 Port USB 3.2 Gen 2 Type C Hub with Power Delivery

No.: 43334

Connect Type A & Type C peripherals to a single USB 3.2 Gen 2 Type C port

Description

- Provides 4 USB 3.2 Gen 2 SuperSpeed ports with data rates up to 10Gbps
- Allows connection of 2 Type A and 2 Type C peripherals
- Compatible with all USB Type C equipped computers
- Features a USB Type C Female port for Power Delivery up to 100W
- 2 year warranty

The Lindy 4 Port USB 3.2 Gen 2 Type C Hub allows users to connect up to 2 USB Type A and 2 Type C peripherals to any USB Type C equipped devices. As part of the USB 3.2 Gen 2 specification, 10Gbps bandwidth provides lightning fast data transfers between host and mass storage devices.

Featuring both Power Delivery 3.0 and Battery Charging 1.2, this Hub really is an ideal companion for power users looking to expand connectivity of Ultrabooks or Macbooks whilst charging their devices. PD 3.0 is provided using an extra USB Type C Port, supporting bidirectional power of up to 100W whilst enabling higher voltage and current values to negotiate between connected devices. Battery Charging 1.2 provides a level of charging which is not possible with standard USB Type A ports by supplying up to 1.5A.

This device's tempered glass design, right angled host connection and small form factor combine to create a truly elegant hub which compliments high performance devices. Installation is simple using a reversible Type C connector and driverless installation.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- USB Standard: USB 3.2 / 3.1 Gen 2
- Supported Bandwidth: 10 Gbps
- Chipset: VL102+, GL3590

- Compatibility: USB Type C equipped computers, Thunderbolt 3 (incl. Apple M1)
- Power Delivery: PD 3.0 up to 100W (20V 5A)
- Special Features: Supports Battery Charging 1.2, 90° angled USB-C connector

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 2 x USB Type A (Female), 3 x USB Type C (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 110.5 x 34.7 x 12.1mm (4.35x1.37x12.1in)
- (Fixed) Cable Length: 200mm (7.87in)
- Housing Material: Aluminum + Tempered Glass Surface+ ABS
- Net Weight: 0.053kg (0.12lb)
- Operating Temperature: 5°C - 30°C (41°F - 86°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)
- Humidity: 20 - 80% RH (non-condensing)
- Power Requirements: -
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x20x194mm (6.85x0.79x7.64in)
- Gross Weight: 0.06kg (0.13lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH, CP65

Package Contents

- 4 Port USB 3.2 Gen 2 Hub

Purchasing information

- No.: 43334
- EAN: 4002888433341