

IFP INTERACTIVE DISPLAYS**INFORMATION****65" OS-Free Professional Touch Display for Maximum Security and Full IT Control**

The ProLite TN6505A-B1AG is a large-format professional touch display, without an operating system, designed for environments where security, reliability and control are non-negotiable. Despite its minimalist structure, the TN6505A is exceptionally easy to use: simply connect your source and it works. The responsive multi-touch panel, 4K UHD resolution and high brightness deliver a precise and professional experience for collaboration, presentations and interactive applications. Built-in annotation allows users to write directly on the screen with a pen, marking up presentations or any on-screen content in real time for clear and effective communication. The TN8605A is the ideal choice for banks, courts, defence organisations, IT departments, universities and other high-security or compliance-driven environments where simplicity, transparency and trust are essential.



Aesthetics which Elevate Any Environment

Modern, minimal, and made to elevate any environment—this design blends seamlessly into classrooms and boardrooms alike. It's not just a display; it's a statement. Clean lines, premium finish, and a presence that enhances focus and professionalism without stealing the spotlight.




DeepContrast-IR+

The state-of-the-art DeepContrast-IR+ technology ensures accurate and precise touch responses, enabling effortless interaction and annotation.



Standalone Solution & Connectivity

The OPS PC Slot offers a convenient standalone solution, allowing easy integration without the need for additional devices. The USB-C connection provides seamless connectivity, enabling quick data transfer, video output, and power through a single cable for enhanced versatility and ease of use.



Wall Mount

The included wall mount bracket ensures secure and stable installation of your display. Designed for easy setup, it supports VESA compatibility and offers a sleek, space-saving solution. Its durable construction guarantees reliability, making it ideal for classrooms, offices, and meeting rooms.

01 **DISPLAY CHARACTERISTICS**

Diagonal	64.5", 163.9cm
Panel	IPS, AG coating & Anti-Bacteria coating, haze 25%
Native resolution	3840 x 2160 (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	500 cd/m ²
Brightness	450 cd/m ² (max.)
Static contrast	1200:1
Response time (GTG)	5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Horizontal Sync	30 - 135kHz
Viewable area W x H	1428.5 x 803.5mm, 56.2 x 31.6"

02 **TOUCH**

Touch technology	DeepContrast-IR+
Touch points	40pt (HID, only with supported OS)
Touch accuracy	+/- 1mm
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

03 **INTERFACES / CONNECTORS / CONTROLS**

Analog signal input	VGA x1 (FHD)
Digital signal input	HDMI x2 (CEC/ARC) DisplayPort x1 USB-C x1 (Power Delivery 65W, DP-Alt, Data, Touch)
Audio input	Mini jack x3.5 mm
Monitor control input	RS-232c x1 RJ45 (LAN) x2 ((in/out))
Audio output	Mini jack x1 Speakers 2 x 20W (Subwoofer 1x 20W)
Monitor control output	RS-232c x1 IR loop through x1 OPS Slot x1 (Intel OPS80 standard)
USB ports	x1 2.0 (2x 3.2 (USB-B up for touch HDMI1/DP/VGA))
RS-232c	x1
RJ45 (LAN)	x2

04 **FEATURES**

Integrated software No Operating System

PiP yes

PbP yes

05 GENERAL

OSD languages EN, DE, FR, ES, IT, RU, JP, NL

User controls Color temp., image mode (including eye protection mode), sound mode, no signal standby (Off / 1 min. / 3 min. / 5 min. / 15 min. / 30 min.), meeting mode, time scheduler, key lock, PIP & PBP, brightness / contrast.

06 MECHANICAL

Orientation landscape

Fanless design yes

VESA mounting 600 x 400mm

Operation temperature range 0°C - 40°C

Storage temperature range - 20°C - 60°C

07 ACCESSORIES INCLUDED

Cables power, HDMI, RS-232c

Other 4x Stylus, Webcam bracket, Wall mount, HDMI 3m, USB 3m, Power

08 POWER MANAGEMENT

Power supply unit internal

Power usage 146W typical, 0.5W stand by, 0.3W off mode

09 SUSTAINABILITY

Regulations CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) G

REACH SVHC above 0.1%: Lead

10 DIMENSIONS / WEIGHT

Product dimensions W x H x D 1489.1 x 911.8 x 118.6mm

Weight (without box) 41.1kg

EAN code 4948570127061

11 EU ENERGY EFFICIENCY LABEL

Energy efficiency G
class (Regulation
(EU) 2017/1369)

Power in OFF Mode 0.3W off mode



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED