

i-tec USB-C Metal Nano 2x Display Docking Station + Power Delivery 100 W

i-tec USB-C Metal Nano 2x Display Docking Station + Power Delivery 100 W



PRODUCT DESCRIPTION

Small metal USB-C docking station capable of supporting up to two external monitors simultaneously*. Simply connect your laptop or tablet (no need to install drivers) and reap the benefits of quick USB data transfer and connection to the internet via a LAN port. And of course, the docking station can also power your laptop with up to 100 W, meaning you will be able to charge all laptops and tablets that support charging via USB-C (USB-C Power Delivery). Brushed aluminium body grants the docking station sufficient durability and resilience even during frequent travel. The integrated USB-C cable is sufficiently long for comfortable connection even if the USB-C port is located in the upper portion of the screen frame (typical for hybrid laptops/tablets). The docking station is also fully compatible with tablets and laptops featuring a Thunderbolt 3/4 port.

- Connect up to two external monitors.
- Power delivery: up to 100 W (USB-C charger is not included in the package)
- Fitted with two HDMI ports
- 2x USB 3.2 (5 Gbps), 2x USB 2.0 and 1x USB-C ports will allow you to easily connect your USB devices and peripherals.
- Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Supports Windows 10/11, macOS, Android, Chrome OS and Linux

1/3

PRODUCT FEATURES

- Integrated 30cm USB-C cable for connecting to devices
- Docking station technology: <u>USB-C (MST)</u>
- Power Delivery: 100W
- Video Ports:
 - 2x HDMI
- Resolution:
- Host device with DisplayPort 1.2 support:
 - 1 monitor 1x HDMI → up to 4K/30Hz
 - 1 monitor 1x HDMI → up to 1080p/120Hz
 - 2 monitors 2x HDMI → up to 2x 1080p/60Hz*
- Host device with DisplayPort 1.4 support:
 - ∘ 1 monitor $1x HDMI \rightarrow up to 4K/60Hz$
 - 2 monitors 2x HDMI → up to 2x 1440p/60Hz*

^{*} macOS does not support Multi Stream Transport (MST) technology, meaning that when connected to a device running macOS, both connected external monitors will display the same image.



- DisplayPort 1.4 host device with DSC support:
 - 1 monitor 1x HDMI → up to 4K/60Hz
 - ∘ 2 monitors $2x HDMI \rightarrow up to 2x 4K/60Hz*$
 - \circ 2 monitors 2x HDMI → up to 2x 1440p/144Hz*
- 2x USB 3.2 Gen1 port
- 2x USB 2.0 port
- 1x USB-C 3.2 Gen1
- 1x USB-C port PD (power delivery only)
- 1x Ethernet GLAN RJ-45 port (RTL8153B)
- MAC address cloning: yes (using <u>i-tec Docker Pro</u> software)
- WOL: S1. S2. S3
- Product dimensions: 152.5 x 43 x 15 mm
- Product weight: 92 g
- Package dimensions: 210 x 98 x 23 mm
- Package weight: 128 g

Hardware requirements:

Device with a free USB-C, USB4 or Thunderbolt[™] 3/4 port

Power Delivery Requirements:

• Devices with a free USB-C, USB4, or Thunderbolt™ 3/4 port with Power Delivery support

Video Output Requirements:

Device with a free USB-C or USB4 port with DisplayPort Alternate Mode support or Thunderbolt™ 3/4 port

Operating System:

• Windows 10 / 11, macOS*, iPadOS**, Android**, Chrome OS and Linux with latest updates

SPECIFICATION

Part Number	Product Description & EAN
C31NANOHDM2DOCPD	i-tec USB-C Metal Nano 2x Display Docking Station + Power Delivery 100 W EAN: 8595611706288
-	i-tec USB-C Metal Nano 2x Display Docking Station + Power Delivery 100 W EAN: -
Hardware	
Bus type	USB-C
Ports/Connectors	
System Requirements	
Operating system	Windows 7 / 8 / 8.1 /10 macOS X

^{*} macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to a macOS station will cause both monitors to display the same image. ** iPadOS, Android do not support multi-screen image transport technology or the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for Android devices with DEX and Easy Projection extensions).



	Android Linux Chrome OS R51 or laterWindows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.	
Other features		
Colour	gray	
Housing Material	aluminium	
Product Dimensions	152,5 x 43 x 15 mm	
Product Weight	92 g	
Package Weight	128 g	
Packaging Dimensions (LxWxH)	210 x 98 x 23 mm	
Support		
Warranty period	2 years	
Technical support	lifetime	
Package contents		
Product		
Manual		

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.pro</u>. Specifications are subject to change without notice.

Updated 11.7.2023