

4x4 USB 3.2 Gen 1 Matrix Switch

No.: 43406

Share 4 USB devices between 4 computers

Description

- Supports USB 3.2 Gen 1 (USB 3.0), USB 2.0/1.1 backwards compatibility
- Switching between computers with buttons, TCP/IP with web GUI or RS-232 commands
- Matrix switch with presets function
- Plug & Play, no software required
- 3 year warranty

The Lindy USB 3.2 Gen 1 Matrix Switch allows the user to share up to 4 USB devices to up to 4 hosts in many different ways: by pushing the buttons on the front panel, via web GUI and using RS-232 commands.

It's possible to save up to 8 preset configurations, change the name of hosts and devices f rom the GUI and with the commands, for smooth and easy operations.

This matrix switch is ideal for sharing printers, storage devices or webcam in office environments, for conference room presentation systems, KVM or industrial applications. It can support USB 3.2 Gen 1 with data transfer rates up to 5Gbps, USB 2.0 and USB 1.1 devices, perfect for use with multiple PCs or Macs.

Each USB Type-A port provide up to 900mA power to the connected device.

Information about USB 3.0, 3.1 & 3.2
USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.
USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.
USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- USB Standard: USB 3.2 Gen 1
- Supported Bandwidth: 5 Gbps
- Chipset: AT32F437 + VL817
- Compatibility: USB equipped computers
- Power Delivery: 900mA on each USB Type A port
- Special Features: Switching by buttons; web GUI, RS-232 commands

Connectors

- Inputs: 4 x USB 3.0 Type B (Female)
- Outputs: 4 x USB Type A (Female)

Control ports: RJ-45 (Female), RS-232 3-Pin Terminal Block
Power: 5.5/2.5mm

Physical Properties

Dimensions WxDxH: 221x105x26mm (8.7x4.13x1.02in)
(Fixed) Cable Length: -
Housing Material: Metal
Net Weight: 1.15kg (2.54lb)
Operating Temperature: 0°C - 40°C (32°F - 104°F)
Storage Temperature: -20°C - 60°C (-4°F - 140°F)
Humidity: 0 - 90% RH (non-condensing)
Power Requirements: 12V 3A
Colour: Black

Miscellaneous

Packaging Type: Carton box
Packaging Dimensions: 260x173x70mm (10.24x6.81x2.76in)
Gross Weight: 1.45kg (3.2lb)
Warranty (Years): 3
Product Compliance: CE, FCC, RoHS & REACH, California Proposition 65

Package Contents

4x4 USB 3.2 Gen 1 Matrix Switch
4x USB 3.2 Gen 1 Type A-B Cable, 1.2m
Multi-country Power Supply (UK, EU, US & AUS)
Lindy Manual

Purchasing Information

No.: 43406
EAN: 4002888434065

© LINDY 2026