



| KoiBox-100W | |
|---|---|
| CPU | Intel® Celeron® dual-core 1.8GHz |
| System Memory | 4GB DDR4 |
| Flash Memory | M.2 2242 SSD 30GB |
| Drive Bay | 1 x 2.5-inch SATA (HDD/SSD not included) |
| Gigabit Ethernet Port | 1 x 1GbE RJ45 |
| Wi-Fi / Bluetooth | Intel Wi-Fi 6 AX201, 802.11ax, Bluetooth 5.2 |
| HDMI Output | 1 x HDMI 1.4b output |
| USB Port | 4 x USB 3.2 Gen 2 Type-A |
| IR sensor | Yes, supports remote controller (RM-IR004) |
| Buttons | 1 x Power button |
| LED Indicators | Power status (On: blue, Standby: blue breathing light, Off: red) |
| Power Supply Unit | 36W, 100-240V DC, 50/60Hz |
| Security Slot | 1x Kensington security slot |
| Dimensions (H x W x D) | 232 x 152 x 45 mm |
| Net Weight | 1.09 kg (2.4lbs) |
| Operating Temperature & Relative Humidity | 0 ~ 40°C (32°F ~ 104°F) · 5 - 95% RH non-condensing |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test