

## 19" IP 54 dust and water-proof wall housing 16U



<b>SKU</b>	OW-16HE-600-IP54-V
<b>Produkt</b>	
<b>Verfügbarkeit</b>	
<b>Belastbarkeit in kg</b>	
<b>HE/U</b>	16
<b>Breite/width</b>	600
<b>Tiefe/depth</b>	600
<b>Höhe/height</b>	891
<b>kW</b>	
<b>Segmentation</b>	

19 "IP 54 wall housing for industrial use 16 U

(Mini server cabinet)

IP54 (Outdoor) wall housings for industrial applications.

Accordance with protection against water and dust. Protection class IP54.

- 1.5 mm strong sheet steel with high load capacity
- Loadcapacity: 100 kg
- 3-point locking system with lockable swing handle
- Cable entries: 2xPG21, PG481x, 2xPVCBlindcap (28 mm diameter)
- Numbered 19" mounting profiles on the front, adjustable in depth
- Integrated airfilterhousing to fresh airinlet (protection against water and dust ingress protection acc. IP54)
- Frontdoor with ground and two welded, strengthening beams in U-shape  
Incl. fastening material
- Extensive accessories available
- Size (HxWxD) 891/600/600 mm
- Color: light gray, RAL7035
- HE: 16
- Loadcapacity: 100 kg

The 16U IP54 outdoor wall housings for industrial applications based on EN 60529 compliant IP54 protection class and is thus protected from water ingress and dust ingress. The ventilation units and filter internals are based on the protection class IP54. Best Performance offer the wall housing including through the 3-point locking system with lockable Schwenkhebelgriffund insulated cable inputs. Integrated air filter housing to fresh air inlet (protection against water and dust ingress-gem. IP54).