



## 4 Port USB 3.1 Gen 2 Type C Metal Hub

No.: 43094

### Description

- Connects 2 Type A and 2 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 4 Port USB 3.1 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 4 USB ports support the Battery Charging specification 1.2 with a total charging power of 17.5 Watt for all 4 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

### Technical details

#### Specifications

- USB Standard: USB 3.1 Gen 2
- Supported Bandwidth: 10 Gbps
- Chipset: VL820
- Compatibility: USB Type C equipped computers, Thunderbolt 3
- Power Delivery: -
- Special Features: Supports Battery Charging 1.2; allows connection of USB Type C locking cables; Terminal Block

#### Connectors

- Inputs: 1 x USB Type C (Female)
- Outputs: 2 x USB Type A (Female), 2 x USB Type C (Female)
- Power: 5.5/2.1mm DC socket

#### Physical Properties

- Dimensions WxDxH: 135x60x24mm (5.31x2.36x0.94in)
- (Fixed) Cable Length: -
- Housing Material: Metal

- Net Weight: 0.229kg (0.5lb)
- Operating Temperature: 0°C - 50°C (32°F - 122°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)
- Humidity: 0 - 95% RH (non-condensing)
- Power Requirements: 5VDC 4A
- Colour: Black

**Miscellaneous**

- Packaging Type: Carton Box
- Packaging Dimensions: 230x198x63mm (9.06x7.8x2.48in)
- Gross Weight: 0.667kg (1.47lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

**Package Content**

- 4 Port USB 3.1 Metal Hub
- 0.6m USB 3.1 Gen 2 Dual Screw Type C Male to Type C Male Cable
- Multi-Country Power Supply (EU, UK, US, AUS)
- Lindy Manual

**Purchasing Information**

- No.: 43094
- EAN: 4002888430944