



NetShelter Wall-mount UPS-Depth

Easily deploy equipment without the footprint.

Ease-of-setup, durability & load capability

Whether retrofitting a space or building a new edge solution, NetShelter Wall-Mount UPS-Depth Enclosure offers reliability, durability, and ease-of-deployment for single-phase equipment mounted on the wall. Bracket-style mounting ensures quick and easy deployment.

Ideal for diverse segments such as retail, healthcare, distribution centers, and education, providing an efficient solution for deploying IT equipment for edge computing applications.



- 835 mm maximum mounting depth and 350 lb (158 kg) load capacity
- Bracket-style mounting for easy, fast, and secure deployment ensuring convenience and safety
- Pre-assembled design to minimize setup time
- Optimized to securely house sensitive data to help enable PCI compliance
- Side-mounted profile extends less than 25" from wall to maximize space efficiency
- Accommodates Zero-U PDU with vertical mounting space to power equipment without sacrificing valuable rack space
- Top and bottom cable opening to facilitate cable management and maintenance
- Compatible with APC's NetBotz security solutions for remote access, video surveillance, and environmental monitoring (sold separately)
- UL 2416 Listed

Learn more at apc.com

Life Is On





NetShelter Wall-mount UPS-Depth


Easily deploy equipment without the footprint.

Experience easy on-site setup and maximize space utilization with our UPS-Depth wall-mount enclosure, offering ample depth for UPS or server deployment all in a sleek, low-profile design.

- **Worry-free deployment.** Accommodates high-density Edge equipment, including all APC Smart-UPS and Easy UPS products and servers in a variety of sizes.
- **Simplified field setup.** Easy to mount and easy to configure, convenient for installing equipment prior to mounting on the wall.
- **Low-profile footprint.** Built with a low-profile footprint for easy access and limited interference with operations.
- **Improved cable management.** Top and bottom cutouts with rear cable channels enable more organized and efficient cabling.

Product Specifications

Rack Units	12U	18U	24U
SKU	AR112SM	AR118SM	AR124SM
Rack Units	12	18	24
Height (mm)	662	889	1156
Width (mm)	600	600	600
Depth (mm)	1037	1037	1037
Max Equipment Depth (mm)	835	835	835
Static Load (kg/lb)	158 / 350	158 / 350	158 / 350
Ventilation	Passive	Passive	Passive
Door Type*	Perforated	Perforated	Perforated
Rating	IP2X	IP2X	IP2X



Configure a full solution using the Local Edge Configurator tool. Partners can register and explore options at se.com/MySchneider.

Learn more at apc.com

Life Is On |