



10.1" fully rugged Windows 11 Pro Tablet

TOUGHBOOK G2 mk3 Standard

The TOUGHBOOK G2 is the next generation rugged device for mobile workforces. It offers all the benefits of the latest technology, while maintaining important access to legacy systems. All of this, wrapped up in a more flexible, secure and ultimately even more useable device.

Key Features

Intel[®] Core™ Ultra5 processor 135U (with Intel vPro Technology)

Windows 11 Pro

10.1" Active Matrix (TFT) colour LCD 1920 \times 1200 (WUXGA) LCD with sunlight-viewable glove-enabled capacitive touchscreen (up to 1.000cd/m²), IP55 Digitiser

IP65 Water and dust resistant****, Tested against MIL-STD 810H****

Long battery life of up to 15 hours (Mobile Mark™ 25) with extended Battery















TOUGHBOOK G2 mk3 Standard

EVOLVED TO ADAPT

An evolution of the best-selling Panasonic Toughbook G1 tablet and 20 detachable, this latest tablet is powered by the Intel Core™ Ultra5 processor 135U (with Intel vPro Technology), delivering incredible performance, and is shipping with Windows 11 Pro. It also has a rich set of business interfaces with additional customisable options to meet a worker's needs. With its long battery life and outdoor viewing, glove-enabled touchscreen, it's a versatile yet tough technology companion for mobile workers.

Panasonic Connect GmbH, Mobile Solutions Business Division, Hagenauer Straße 43, 65203 Wiesbaden, Germany

https://eu.connect.panasonic.com/g b/en/toughbook/toughbook-g2series/toughbook-g2-mk3-standard

Mobile Computing Platform	Intel [®] Core™ Ultra5 processor 135U (with Intel vPro [®] Technology)	
Operating System	Windows 11 Pro	
RAM	16GB (max. 32GB) DDR5x	
Graphic Chip	Intel [®] Graphics	
Storage	512GB OPAL NVMe SSD (up to 2TB optional)	
LCD	10.1" Active Matrix (TFT) colour LCD 1920 x 1200 (WUXGA) LCD with sunlight-viewable	
	glove-enabled capacitive touchscreen (up to 1.000cd/m²), IP55 Digitiser	
Bluetooth™	5.3 Class 1	
Wireless LAN	Intel [®] Wi-Fi6E AX211	
Mobile Broadband*	4G or 5G with SIM/eSIM support	
GPS*	U-Blox NEO-M9N Series (not compatible to 5G model)	
LAN	IEEE 802.3 10Base-T / IEEE 802.3u 100BASE-TX / IEEE 802.3ab 1000BASE-T	
Sound	Intel [®] High Definition Audio subsystem support, Stereo speaker	
Security	TPM (TCG V2.0 compliant), Integrated hardware security lock slot, Windows Hello	
	compliant Webcam	
Front Camera	2 MP with IR / privacy shutter (Windows Hello compliant)	
Rear Camera	13mpixel with autofocus and LED flash	
Top Expansion Bay Area**	Serial, 2D Barcode Reader, 2nd USB 2.0, 2nd LAN, Thermal by FLIR, Micro-SD	
Rear Expansion Bay Area***	Smart Card Reader, HF-RFID (NFC) Reader, Fingerprint Reader	
USB 3.2 Gen 1 Type A	x1	
Thunderbolt 4	x1	
LAN Port	x1	
DC In	x1	
Port Replicator	x1	
Dual Antenna Connector	x1	
AC Adaptor	Input: 100 V - 240 V AC, 50 Hz/ 60 Hz, Output: 15.6 V DC, 7.05 A	
Battery	Standard: Li-ion 11.4V, 4360mAh (50Whr), Extended: Li-ion 10.8V, 6300mAh (68Whr)	
Battery Life	Standard: Approx 11 hours (Mobile Mark™ 25)	

Extended: Appr	ox 15 hours (Mobile	Mark™ 25)
----------------	---------------------	-----------

Power Management	Standby function, ACPI BIOS, Hot swap optional
Dimensions (W x H x D)	279mm x 188mm x 23.5 mm / 11.0" x 7.4" x1.0" (without protruding parts)
Weight	Approx. 1.19kg / 2.64lb
Drop Resistance	MIL-STD 810H, 180cm ****
Dust Resistance	IEC529 (JIS C0920) IP6x ****
Water Resistance	IEC529 (JIS C0920) IPx5 ****
Operating Temperature	MIL-STD 810H, -29 °C to 60 °C ****
Standard Configuration	FZ-G2mk3 Standard, 16GB RAM, 512GB SSD, standard battery pack, IP55 digitiser pen
Included in the box	Power Supply, Power Cord, Display cleaning cloth and User Manual

^{*} Optiona

TOUGHBOOK G2 mk3 Standard: September 2024

Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances.

 $[\]ensuremath{^{**}}$ One option exlusive possible in Top Expansion Bay Area, End User replaceable

^{***} One option exlusive possible in Rear Expansion Bay Area, End User replaceable

^{****} Tested by an independent third party lab following MIL-STD-810H and IEC 60529, Sections 13.4, 13.6.2, 14.2.5 and 14.3