

VERTIV™ GEIST™ VP9559 RACK PDU

Basic, Standard



OVERVIEW

The Vertiv™ Geist™ Basic Rack PDU delivers reliable power distribution at a competitive price point. The Basic PDU is the entry-level solution in the Vertiv Geist Rack PDU family, providing basic, reliable power distribution in all IT environments.

Benefits

- Reliable power distribution at a low cost point
- Every unit is tested for reliability and functionality — no batch tests
- Fast, inexpensive customization, including non-standard cord lengths
- Standard three-year warranty, upgraded to five years with early product registration

Part Number:

VP9559 Basic, Standard

Power Configuration:

16A, 230V, 3.6kW

Physical Configuration:

17in / 432mm Horizontal/Vertical

Product Summary:

 VP9559 —

Basic, Standard, 16A, 230V, Horizontal/Vertical, (10) IEC C13, (2) IEC C19, C20, Black Powder Coat.

Specifications and Options

Quantity Of Inputs	1
Voltage	230V
Current	16A
VA per Input (Load Capacity)	3.6kW
Frequency	50/60 Hz
Over Current Protection	None
Switch	No
Plug Type	IEC60320 C20 Power Inlet (cord sold separately)
Combined Total Receptacle/Socket Quantity	12
Receptacle/Socket Type #1	IEC C13
- Quantity on Face	10
- Style	Banks of 5
- Maximum Output per Receptacle/Socket	10A per receptacle bank
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC C19
- Quantity on Face	2
- Style	Individual
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	Zero U or 1U
19in Panel Mount Brackets	Yes
SLB-4 Brackets	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years

Specifications and Options (cont'd)

Certification/Agency Approvals	CE Marked
Certification/Agency Approvals	Complies with EN 55032 and EN 55024
Certification/Agency Approvals	Complies with IEC 60950-1 (CB Certificate Available)
Certification/Agency Approvals	RoHS Compliant
Chassis Dimensions (HxWxD)	44mm x 432mm x 47mm

