

<b>INFORMATION</b>	<b>Parameter or value and precision</b>	<b>Unit</b>
1. Supplier's name or trademark.	IYAMA CORPORATION	
Supplier's address.	Wijkermeerstraat 8, 2131 HA Hoofddorp, NL	
2. Model identifier	<b>TF4339AS-B1AG</b>	
3. Energy Efficiency Class for standard Dynamic Range (SDR)	F	
4. On mode power demand for Standard Dynamic Range (SDR)	52,1	W
5. Energy Efficiency Class for standard Dynamic Range (HDR)		
6. On mode power demand in High Dynamic Range (HDR), if implemented		W
7. Off mode, power demand, if applicable	0	W
8. Standby mode power demand, if applicable	0,4	W
9. Networked standby mode power demand, if applicable	1,2	W
10. Electronic display category	Signage	
11. Size ratio	16:09	integer
12. Screen resolution	3840 x 2160	Pixels
13. Screen diagonal	108	cm
14. Screen diagonal	43	inches
15. Visible screen area	49,8	dm <sup>2</sup>
16. Panel technology used	LED LCD	
17. Automatic Brightness Control (ABC) available	No	
18. Voice recognition sensor available	No	
19. Room presence sensor available	No	
20. Image refresh frequency rate (default)	60	Hz
21. Minimum guaranteed availability of software and firmware updates (from the date of end of the placement on the market)	8	years
22. Minimum guaranteed availability of spare parts (from the date of end of the placement on the market)	7	years
23. Minimum guaranteed product support	7	years
Minimum duration of the general guarantee offered by the supplier	3	years
24. Power supply type:	Internal	
25. External power supply (non standardized and included in the product box)		
i		

ii	Input Voltage		V
iii	Output Voltage		V
26. External standardised power supply (or suitable one if not included in the product box)			
i	Supported standard name or list		
ii	Required output voltage		V
iii	Required delivered current (minimum)		A
iv	Required current frequency		Hz