

### Overview

#### Aruba 550 Series Campus Access Points

##### Extreme Wi-Fi 6 (802.11ax) Performance With Tri-Radios And Green AP Energy Efficiency

Aruba Wi-Fi 6 access points provide high-performance connectivity for any organization experiencing growing numbers of IoT and mobility requirements. With a maximum aggregate data rate of 6 Gbps (5.95 Gbps; HE80/HE40), the Aruba 550 Series deliver the speed and reliability needed for any enterprise..

---



Aruba 550 Series – Front View

---

#### Key Features

- 6 Gbps of maximum throughput and up to 1024 clients per radio
  - WPA3 and Enhanced Open security
  - Built-in technology that resolves sticky client issues for Wi-Fi 6 and Wi-Fi 5 devices
  - OFDMA and MU-MIMO for enhanced multi-user efficiency
  - IoT-ready Bluetooth 5, NFC, and Zigbee support
  - tri-radio mode with two 5GHz and one 2.4GHz radio (4x4 MIMO)
  - Unified wired and wireless policy enforcement with Dynamic Segmentation
-

---

## Standard Features

### IoT Platform Capabilities

Like all Aruba Wi-Fi 6 APs, the Aruba 550 Series includes an integrated Bluetooth 5 and 802.15.4 radio (for Zigbee support) to simplify deploying and managing IoT-based location services, asset tracking services, security solutions and IoT sensors. This allows organizations to leverage the Aruba 550 Series as an IoT platform, which eliminates the need for an overlay infrastructure and additional IT resources.

---

### Incredible Efficiency

The Aruba 550 Series APs are also designed to optimize user experience by maximizing Wi-Fi efficiency and dramatically reducing airtime contention between clients.

Features include Orthogonal frequency-division multiple access (OFDMA), bi-directional multi-user MIMO and cellular optimization. With optional tri-radios, up to 4 spatial streams (4SS) and 160MHz channel bandwidth (VHT160), the Aruba 550 Series provides groundbreaking wireless capabilities for any enterprise.

Read the [Multi-User 802.11ax white paper](#) for further information.

---

### Advantages Of OFDMA

This capability allows Aruba's APs to handle multiple Wi-Fi 6 capable clients on each channel simultaneously, regardless of device or traffic type. Channel utilization is optimized by handling each transaction via smaller sub-carriers or resource units (RUs), which means that clients are sharing a channel and not competing for airtime and bandwidth.

---

### Aruba Airslice For Extended Application Assurance

Initially, APs in controller-less mode (Instant) can provide SLA-grade performance by allocating radio resources (e.g. time, frequency, spatial streams) to specific traffic types. By combining Aruba's [Policy Enforcement Firewall](#) (PEF) and Layer 7 deep packet inspection (DPI) to identify user roles and applications, the APs will dynamically allocate the bandwidth needed. Non-Wi-Fi 6 clients can also benefit.

AirSlice for APs in controller mode will be supported in a future software release.

---

### Bi-Directional Multi-User MIMO (MU-MIMO)

Similar to downlink MU-MIMO in Wi-Fi 5 (802.11ac Wave 2), the Aruba 550 Series can simultaneously connect clients use downlink – and now – uplink spatial streams. The added benefit is the ability to multiply the number of clients that can now send traffic, thus optimizing client-to-AP spatial stream diversity.

---

### Wi-Fi 6 And MU-MIMO Aware Client Optimization

Aruba's patented AI-powered ClientMatch technology eliminates sticky client issues by placing Wi-Fi 6 capable devices on the best available AP. Session metrics are used to steer mobile devices to the best AP based on available bandwidth, types of applications being used and traffic type – even as users roam.

---

### Aruba Advanced Cellular Coexistence (ACC)

This feature uses built-in filtering to automatically minimize the impact of interference from cellular networks, distributed antenna systems (DAS), and commercial small cell or femtocell equipment.

---

### Intelligent Power Monitoring (IPM)

Aruba APs continuously monitor and report hardware energy consumption. They can also be configured to enable or disable capabilities based on available PoE power – ideal when wired switches have exhausted their power budget.

---

### Green AP Energy Efficiency

Aruba Wi-Fi 6 APs utilize analytics from NetInsight to automatically transition in and out of a sleep mode based on client density. Learn more in the [Green AP At-A-Glance](#).

---

### Target Wake Time (TWT)

Ideal for IoTs that communicate infrequently, TWT establishes a schedule for when clients need to communicate with an AP. This helps improve client power savings and reduces airtime contention with other clients.

---



---

## Standard Features

### Aruba Secure Infrastructure

The Aruba 550 Series includes components of Aruba's 360 Secure Fabric to help protect user authentication and wireless traffic. Select capabilities include:

---

### WPA3 And Enhanced Open

Support for stronger encryption and authentication is provided via the latest version of WPA for enterprise protected networks. Enhanced Open offers seamless new protection for users connecting to open networks where each session is automatically encrypted to protect user passwords and data on guest networks.

---

### WPA2-MPSK

MPSK enables simpler passkey management for WPA2 devices – should the Wi-Fi password on one device or device type change, no additional changes are needed for other devices. Requires ClearPass Policy Manager.

---

### VPN Tunnels

In Remote AP (RAP) and IAP-VPN deployments, the Aruba 550 Series can be used to establish a secure SSL/IPSec VPN tunnel to a Mobility Controller that is acting as a VPN concentrator.

---

### Trusted Platform Module (TPM)

For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials and keys, and boot code.

---

### Simple And Secure Access

To simplify policy enforcement, the Aruba 550 Series uses Aruba's policy enforcement firewall (PEF) feature to encapsulate all traffic from the AP to the Mobility Controller (or Gateway) for end-to-end encryption and inspection. Policies are applied based on user role, device type, applications, and location. This reduces the manual configuration of SSIDs, VLANs and ACLs. PEF also serves as the underlying technology for Aruba Dynamic Segmentation.

---

### High-Density Connectivity

Like the 530 Series AP, each Aruba 550 Series AP provides connectivity for a maximum of 1024 associated clients per radio (3072 in total). In real-world scenarios, the maximum recommended client density is dependent on environmental conditions.

---

### Flexible Operation And Management

A unique feature of Aruba APs is the ability to operate in either controllerless (Instant) or controller-based mode. In controllerless mode, one AP serves as a virtual controller for the entire network. Learn more about Instant mode in this technology brief.

For optimized network performance, roaming and security, APs tunnel all traffic to a mobility controller for centrally managed traffic forwarding and segmentation, data encryption, and policy enforcement. Learn more in the ArubaOS datasheet.

Available management solutions include Aruba Central (cloud-managed) or Aruba AirWave – a multi-vendor on-premises management solution.

For large installations across multiple sites, APs can be factory-shipped and can be activated with Zero Touch Provisioning through Aruba Central or AirWave. This reduces deployment time, centralizes configuration, and helps manage inventory.

---

### Mounting Details

A mounting bracket has been pre-installed on the back of the AP. This bracket is used to secure the AP to any of the Aruba mount kits (sold separately); see the ordering Information section below for details.

---

### Specifications - Hardware Variants

AP-555: Internal antenna models

---

### Warranty

**Aruba Limited lifetime warranty**

---



## Configuration Information

### BTO Model

| Remarks       | Description  | SKU    |
|---------------|--|--------|
| <b>Notes:</b> | <ul style="list-style-type: none"> <li>– Add Mount Kit</li> <li>– <a href="#">OCA Only Model Selection Form - HPE Offering &gt; Aruba &gt; Wireless &gt; Access Points &gt; Campus: Aruba 550 Series Campus Access Points</a></li> </ul> |        |
|               | <b>555 Internal Antenna Access Points</b>  |        |
|               | Aruba AP-555 (EG) Dual Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ353A |
|               | Aruba AP-555 (IL) Dual Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ354A |
|               | Aruba AP-555 (JP) Dual Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ355A |
|               | Aruba AP-555 (RW) Dual Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ356A |
|               | Aruba AP-555 (US) Dual Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ357A |
|               | <b>555 Internal Antenna Access Points - TAA Models</b>   |        |
|               | Aruba AP-555 (EG) TAA Dual-Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ363A |
|               | Aruba AP-555 (IL) TAA Dual-Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ364A |
|               | Aruba AP-555 (JP) TAA Dual-Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ365A |
|               | Aruba AP-555 (RW) TAA Dual-Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ366A |
|               | Aruba AP-555 (US) TAA Dual-Radio 8x8:8 / 4x4:4 802.11ax Internal Antennas Unified Campus AP  | JZ367A |

### Mount Accessories

| Remarks       | Description   | SKU      |
|---------------|---|----------|
|               | <b>AP Mount Kits</b>  |          |
|               | For 555, Series Std (Min 0 // max 99) User Selection (min 0 // max 99)  |          |
|               | Aruba CM AP-MNT-A Campus AP mount bracket kit (individual) type A: flat rail 9/16   | R3J15ACM |
|               | Aruba CM AP-MNT-MP10-A Campus AP mount bracket kit (10-pack) type A: flat rail 9/16   | JZ370ACM |
|               | Aruba CM AP-MNT-B Campus AP mount bracket kit (individual) type B: flat rail 15/16  | R3J16ACM |
|               | Aruba CM AP-MNT-MP10-B Campus AP mount bracket kit (10-pack) type B: flat rail 15/16  | Q9G69ACM |
|               | Aruba CM AP-MNT-C Campus AP mount bracket kit (individual) type C: profile rail 9/16  | R3J17ACM |
|               | Aruba CM AP-MNT-MP10-C Campus AP mount bracket kit (10-pack) type C: profile rail 9/16  | Q9G70ACM |
|               | Aruba CM AP-MNT-D Campus AP mount bracket kit (individual) type D: solid surface  | R3J18ACM |
|               | Aruba CM AP-MNT-MP10-D Campus AP mount bracket kit (10-pack) type D: solid surface  | Q9G71ACM |
|               | Aruba CM AP-MNT-E Campus AP mount bracket kit (individual) type E: wall-box   | R3J19ACM |
|               | Aruba CM AP-MNT-MP10-E Campus AP mount bracket kit (10-pack) type E: wall-box   | R1C72ACM |
|               | Aruba CM AP-MNT-MP10-X Campus AP mount adapter kit (10-pack)  | R3T20ACM |
| <b>Notes:</b> | <ul style="list-style-type: none"> <li>– <a href="#">Kit contains mounts for 10 access points</a></li> <li>– <a href="#">Access Points do not include a Mount. Qty 1 Mount kits should be selected</a></li> </ul> |          |

### Power Options

For 555 Series Std (Min 0 // max 1) User Selection (min 0 // max 1)

| Remarks       | Description   | SKU    |
|---------------|---|--------|
| <b>Notes:</b> | <ul style="list-style-type: none"> <li>– <a href="#">If this Power Supply is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu</a></li> <li>– <a href="#">Most devices are PoE powered from switch so these are optional</a></li> </ul> |        |
|               | <b>Compatible with 555 AP models</b>  |        |
|               | AP-POE-BTSR 1-Port Smart Rate 802.3bt 60W midspan injector  | R1C73A |
|               | AP-AC2-48C 48V/50W AC/DC desktop style power adapter with 1.35/3.5mm connector  | R3K01A |



## Configuration Information

### Accessories

| Remarks | Description  | SKU    |
|---------|--|--------|
|         | <b>Snap-on Covers</b><br>For 555 Series Std (Min 0 // max 99) User Selection (min 0 // max 99)<br>AP-555-CVR-20 20-pack for AP-555 White Non-glossy Snap-on Covers | JZ369A |

**Notes:** [Kit contains 20 optional snap-on covers](#)

#### Other Accessories (Optional)

For 555 Series Std (Min 0 // max 99) User Selection (min 0 // max 99)

| Remarks | Description   | SKU    |
|---------|---|--------|
|         | <b>Compatible with 555 AP models</b>                                  |        |
|         | AP-MOD-SERU Micro-USB TTL3.3V to RJ45 RS232 AP Console Adapter Module | R6Q99A |
|         | AP-CBL-SERU Micro-USB TTL3.3V to USB2.0 AP Console Adapter Cable      | JY728A |
|         | Aruba USB LTE Modem for use with Access Points and Gateways           | R8F34A |
|         | Aruba USB Extender Cable Kit for use with Aruba USB LTE Modem         | R8G76A |

### Software

| Remarks | Description  | SKU      |
|---------|--|----------|
|         | <b>Central</b>   |          |
|         | Aruba Central AP Foundation 1 year Subscription E-STU              | Q9Y58AAE |
|         | Aruba Central AP Foundation 3 year Subscription E-STU              | Q9Y59AAE |
|         | Aruba Central AP Foundation 5 year Subscription E-STU              | Q9Y60AAE |
|         | Aruba Central AP Foundation 7 year Subscription E-STU              | Q9Y61AAE |
|         | Aruba Central AP Foundation 10 year Subscription E-STU             | Q9Y62AAE |
|         | Aruba Central AP Advanced 1yr Subscription E-STU                   | Q9Y63AAE |
|         | Aruba Central AP Advanced 3yr Subscription E-STU                   | Q9Y64AAE |
|         | Aruba Central AP Advanced 5yr Subscription E-STU                   | Q9Y65AAE |
|         | Aruba Central AP Advanced 7yr Subscription E-STU                   | Q9Y66AAE |
|         | Aruba Central AP Advanced 10yr Subscription E-STU                  | Q9Y67AAE |
|         | Aruba Central On-Premises AP Foundation 1 year Subscription E-STU  | R6U63AAE |
|         | Aruba Central On-Premises AP Foundation 3 year Subscription E-STU  | R6U64AAE |
|         | Aruba Central On-Premises AP Foundation 5 year Subscription E-STU  | R6U65AAE |
|         | Aruba Central On-Premises AP Foundation 7 year Subscription E-STU  | R6U66AAE |
|         | Aruba Central On-Premises AP Foundation 10 year Subscription E-STU | R6U67AAE |

**Notes:** [Add the Central On-Prem Skus to the Aruba Catalog as Standalone:](#)  
[Aruba > Network Management > Central > On-Prem Services](#)



## Technical Specifications

| RF Performance Table         |  |   |
|------------------------------|--|---|
| Band, rate                   | Maximum transmit power (dBm) per transmit chain <sup>6</sup> | Receiver sensitivity (dBm) per receive chain <sup>6</sup> |
| <b>2.4GHz, 802.11b</b>       |  |   |
| 1Mbps                        | 18   | -98   |
| 11Mbps                       | 18   | -89   |
| <b>2.4GHz, 802.11g</b>       |  |   |
| 6Mbps                        | 18   | -92   |
| 54Mbps                       | 16   | -75   |
| <b>2.4GHz, 802.11n HT20</b>  |  |   |
| MCS0                         | 18   | -92   |
| MCS7                         | 14   | -73   |
| <b>2.4GHz, 802.11ax HE20</b> |  |   |
| MCS0                         | 18   | -92   |
| MCS11                        | 10   | -64   |
| <b>5GHz, 802.11a</b>         |  |   |
| 6Mbps                        | 18   | -91   |
| 54Mbps                       | 16   | -74   |
| <b>5GHz, 802.11n HT20</b>    |  |   |
| MCS0                         | 18   | -91   |
| MCS7                         | 14   | -72   |
| <b>5GHz, 802.11n HT40</b>    |  |   |
| MCS0                         | 18   | -88   |
| MCS7                         | 14   | -69   |
| <b>5GHz, 802.11ac VHT20</b>  |  |   |
| MCS0                         | 18   | -91   |
| MCS9                         | 12   | -68   |
| <b>5GHz, 802.11ac VHT40</b>  |  |   |
| MCS0                         | 18   | -88   |
| MCS9                         | 12   | -65   |
| <b>5GHz, 802.11ac VHT80</b>  |  |   |
| MCS0                         | 18   | -85   |
| MCS9                         | 12   | -62   |
| <b>5GHz, 802.11ac VHT160</b> |  |   |
| MCS0                         | 18   | -82   |
| MCS9                         | 12   | -59   |
| <b>5GHz, 802.11ax HE20</b>   |  |   |
| MCS0                         | 18   | -91   |
| MCS11                        | 10   | -62   |
| <b>5GHz, 802.11ax HE40</b>   |  |   |
| MCS0                         | 18   | -88   |
| MCS11                        | 10   | -58   |
| <b>5GHz, 802.11ax HE80</b>   |  |   |
| MCS0                         | 18   | -85   |
| MCS11                        | 10   | -56   |
| <b>5GHz, 802.11ax HE160</b>  |  |   |
| MCS0                         | 18   | -82   |
| MCS11                        | 10   | -53   |



## Technical Specifications

### Wi-Fi Antennas

- Integrated downtilt omni-directional antennas for 4x4 MIMO in 2.4GHz with peak antenna gain of 4.3dBi, and 8x8 MIMO in 5GHz with peak antenna gain of 5.8dBi in 5GHz. In tri-radio mode, the peak gain of the antennas for each of the 4x4 5GHz radios is 5.5dBi (radio 0L, lower half of 5GHz) and 5.6dBi (radio 0U, upper half of 5GHz). Built-in antennas are optimized for horizontal ceiling mounted orientation of the AP. The downtilt angle for maximum gain is roughly 30 degrees.
  - A mix of horizontally and vertically polarized antenna elements is used
  - 
  - Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 2.4dBi in 2.4GHz and 0.7dBi in 5GHz (dual-radio mode).
  - In tri-radio mode, the peak gain of the combined, average pattern is 1.1dBi (radio 0L, lower half of 5GHz) and 3.6dBi (radio 0U, upper half of 5GHz)

### Reliability

Mean Time Between Failure (MTBF): 962,134hrs (110yrs) at +25C operating temperature.

### Wi-Fi Radio Specifications

- AP type: Indoor, dual/tri-radio, 5GHz and 2.4GHz 802.11ax 4x4 MIMO
- 5GHz radio (dual-radio operation): Eight spatial stream Single User (SU) MIMO for up to 4.8Gbps wireless data rate with individual 8SS HE80 (or 4SS HE160) 802.11ax client devices, or with eight 1SS or four 2SS HE80 802.11ax MU-MIMO capable client devices simultaneously
- 5GHz radio (tri-radio operation): Four spatial stream Single User (SU) MIMO for up to 2.4Gbps wireless data rate with individual 4SS HE80 (or 2SS HE160) 802.11ax client devices, or with four 1SS or two 2SS HE80 802.11ax MU-MIMO capable client devices simultaneously
- 2.4-GHz radio: Four spatial stream Single User (SU) MIMO for up to 1,150Mbps wireless data rate with individual 4SS HE40 802.11ax client devices or with two 2SS HE40 802.11ax MU-MIMO capable client devices simultaneously
- Support for up to 1,024 *associated* client devices per radio (typical recommended limit for *active* clients is 200), and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
  - 2.400 to 2.4835GHz (radio 1)
  - 5.150 to 5.250GHz (radio 0 and 0L)
  - 5.250 to 5.350GHz (radio 0 and 0L)
  - 5.470 to 5.725GHz (radio 0 and 0U)
  - 5.725 to 5.850GHz (radio 0 and 0U)
- Available channels: Dependent on configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
  - 802.11b: Direct-sequence spread-spectrum (DSSS)
  - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
  - 802.11ax: Orthogonal frequency-division multiple access (OFDMA) with up to 37 resource units (for an 80MHz channel)
- Supported modulation types:
  - 802.11b: BPSK, QPSK, CCK
  - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM (proprietary extension)
  - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM (proprietary extension)
  - 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
- 802.11n high-throughput (HT) support: HT20/40
- 802.11ac very high throughput (VHT) support: VHT20/40/80/160
- 802.11ax high efficiency (HE) support: HE20/40/80/160

## Technical Specifications

### Wi-Fi Radio Specifications

- Supported data rates (Mbps):
  - 802.11b: 1, 2, 5.5, 11
  - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
  - 802.11n: 6.5 to 600 (MCS0 to MCS31, HT20 to HT40), 800 with 256-QAM
  - 802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4, VHT20 to VHT160), 2,166 with 1024-QAM
  - 802.11ax (2.4GHz): 3.6 to 1,147 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE40)
  - 802.11ax (5GHz): 3.6 to 4,804 (MCS0 to MCS11, NSS = 1 to 8, HE20 to HE160)
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU
- Transmit power: Configurable in increments of 0.5dBm
- Maximum (aggregate, conducted total) transmit power (limited by local regulatory requirements):
  - 2.4GHz band: +24dBm (18dBm per chain)
  - 5GHz band: +27dBm in dual-radio mode, +24dBm in tri-radio mode (18dBm per chain)

**Notes:** Conducted transmit power levels exclude antenna gain. For total (EIRP) transmit power, add antenna gain.
- Advanced Cellular Coexistence (ACC) minimizes the impact of interference from cellular networks
- Maximum ratio combining (MRC) for improved receiver performance
- Cyclic delay/shift diversity (CDD/CSD) for improved downlink RF performance
- Space-time block coding (STBC) for increased range and improved reception
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
- Transmit beam-forming (TxBF) for increased signal reliability and range
- 802.11ax Target Wait Time (TWT) to support low-power client devices

### Additional Wi-Fi Features

Each AP also includes the following standards-based technologies:

- Transmit beamforming (TxBF) increases signal reliability and range
- Passpoint Wi-Fi (Release 2) (Hotspot 2.0) offers seamless cellular-to-Wi-Fi carryover for guests
- Dynamic Frequency Selection (DFS) optimizes use of available RF spectrum
- Maximum Ratio Combining (MRC) improves receiver performance
- Cyclic Delay/Shift Diversity (CDD/CSD) provides greater downlink RF performance
- Space-Time Block Coding increases range and improved reception
- Low-Density Parity Check (LDPC) provides a high-efficiency error correction for increased throughput

### Environmental Specifications

- Operating conditions
  - Temperature: 0C to +50C / +32F to +122F
  - Humidity: 5% to 93% non-condensing
  - AP is plenum rated for use in air-handling spaces
  - ETS 300 019 class 3.2 environments
- Storage and transportation conditions
  - Temperature: -40C to +70C / -40F to +158F
  - Humidity: 5% to 93% non-condensing
  - ETS 300 019 classes 1.2 and 2.3 environments

### Regulatory Model Numbers

- AP-555: APIN0555

### Minimum Operating System Software Versions

- ArubaOS
- Aruba InstantOS 8.5.0.0



## Technical Specifications

### Certifications

- UL2043 plenum rating
- Wi-Fi Alliance:
  - Wi-Fi CERTIFIED a, b, g, n, ac
  - Wi-Fi CERTIFIED ax<sup>1</sup>
  - WPA, WPA2 and WPA3 – Enterprise with CNSA option, Personal (SAE), Enhanced Open (OWE)
  - WMM, WMM-PS, Wi-Fi Vantage, W-Fi Agile Multiband
  - Wi-Fi Location<sup>2</sup>
  - Passpoint (release 2)
- Bluetooth SIG
- Ethernet Alliance (POE, PD device, class 4)

### Notes:

- <sup>1</sup>Will require software update. Certification effort will be kicked off as soon as the Wi-Fi Alliance starts the program
- <sup>2</sup>Not available initially; will require a software upgrade

---

### Other Interfaces

- E0, E1: HPE SmartRate port (RJ-45, maximum negotiated speed 5Gbps)
  - Auto-sensing link speed (100/1000/2500/5000BASE-T) and MDI/MDX
  - 2.5Gbps and 5Gbps speeds comply with NBase-T and 802.3bz specifications
  - POE-PD: 48Vdc (nominal) 802.3af/at/bt POE (class 3 or higher)
  - 802.3az Energy Efficient Ethernet (EEE)
- Link aggregation (LACP) support between both network ports for redundancy and increased capacity
- POE power can be drawn from either port (single source, or set to prioritize) or both ports simultaneously (set to combine)
- DC power interface: 48Vdc (nominal, +/- 5%), accepts 1.35mm/3.5mm center-positive circular plug with 9.5mm length
- USB 2.0 host interface (Type A connector)
  - Capable of sourcing up to 1A / 5W to an attached device
- Bluetooth Low Energy (BLE5.0) and Zigbee (802.15.4) radio
  - BLE: up to 8dBm transmit power (class 1) and -99dBm receive sensitivity (125kbps)
  - Zigbee: up to 8dBm transmit power and -97dBm receive sensitivity
  - A pair of integrated omnidirectional antennas (polarization diversity) with roughly 30 degrees downtilt and peak gain of 4.5dBi
- Visual indicators (two multi-color LEDs): for System and Radio status
- Reset button: factory reset, LED mode control (normal/off)
- Serial console interface (proprietary, micro-B USB physical jack)
- Kensington security slot

---

### Regulatory Compliance

- FCC/ISED
- CE Marked
- RED Directive 2014/53/EU
- EMC Directive 2014/30/EU
- Low Voltage Directive 2014/35/EU
- UL/IEC/EN 60950
- EN 60601-1-1, EN60601-1-2

For more country-specific regulatory information and approvals, please see your Aruba representative.

---



## Technical Specifications

### Power Sources And Power Consumption

- The AP supports direct DC power and Power over Ethernet (POE; on port E0 and/or E1)
- When POE power is supplied to both Ethernet ports, the AP can be configured to combine or prioritize power sources
- When both DC and POE power sources are available, DC power takes priority over POE
- Power sources are sold separately; see the ordering Information section below for details
- When powered by DC, 802.3bt (class 5) POE or 2x 802.3at (class 4) POE, the AP will operate without restrictions.
- When powered by 1x 802.3at (class 4) POE and with the IPM feature disabled, the AP will disable the USB port, disable the other Ethernet port, operate the 5GHz radio in 4x4 mode, and disable tri-radio operation  
In the same configuration but with IPM enabled, the AP will start up in unrestricted mode, but may dynamically apply restrictions depending on the POE budget and actual power. The feature restrictions and order can be programmed.
- Operating the AP with an 802.3af (class 3 or lower) POE source is not supported.
- Maximum (worst-case) power consumption:
  - DC powered: 38.5W
  - POE powered (802.3bt or dual 802.3at): 38.2W
  - POE powered (802.3at, IPM enabled): 25.1W
  - All numbers above are without an external USB device connected. When sourcing the full 5W power budget to such a device, the incremental (worst-case) power consumption for the AP is up to 5.7W (POE powered) or 6W (DC powered).
- Maximum (worst-case) power consumption in idle mode (dual-radio operation): 18W (POE) or 18W (DC). In tri-radio mode, this increases to 18W (POE) or 18W (DC).
- Maximum (worst-case) power consumption in deep-sleep mode: 3W (POE) or 3W (DC)

### Mechanical Specifications

- Dimensions/weight (AP-555; unit, excluding mount bracket):
  - 260mm (W) x 260mm (D) x 61mm (H) / 10.2" (W) x 10.2" (D) x 2.3" (H)
  - 1,570g / 55.4oz
- Dimensions/weight (AP-555; shipping):
  - 320mm (W) x 303mm (D) x 108mm (H) / 12.6" (W) x 11.9" (D) x 4.3" (H)
  - 2,230g / 78.7oz




## Technical Specifications


### Antenna Patterns

#### Horizontal Planes (Top View)

Showing azimuth (0 degrees) and 30 degrees downtilt patterns (averaged patterns for all applicable antennas)




— 2.45GHz WiFi (R1) Average Azimuth — 2.45GHz WiFi (R1) Average Downtilt




— 5.5GHz WiFi (R0) Average Azimuth — 5.5GHz WiFi (R0) Average Downtilt

#### 2.45GHz Wi-Fi (Radio 1)



— 5.18GHz WiFi (R1) Average Azimuth — 5.18GHz WiFi (R1) Average Downtilt

#### 5.5GHz Wi-Fi (Dual-Radio Mode, Radio 0)



— 5.875GHz WiFi (R0) Average Azimuth — 5.875GHz WiFi (R0) Average Downtilt

#### 5.18GHz Wi-Fi (Radio 0L, Tri-Radio Mode)


#### 5.875GHz Wi-Fi (Radio 0U, Tri-Radio Mode)




## Technical Specifications

### Vertical Elevation Planes (Side View, AP Facing Down)

Showing side view with AP rotated 0 and 90 degrees (averaged patterns for all applicable antennas)




— 2.45GHz WiFi (R1) Average Elevation 0 — 2.45GHz WiFi (R1) Average Elevation 90




— 5.5GHz WiFi (R0) Average Elevation 0 — 5.5GHz WiFi (R0) Average Elevation 90

### 2.45GHz Wi-Fi (Radio 1)



— 2.45GHz WiFi (R1) Average Elevation 0 — 2.45GHz WiFi (R1) Average Elevation 90

### 5.5GHz Wi-Fi (Dual-Radio Mode, Radio 0)



— 5.5GHz WiFi (R0) Average Elevation 0 — 5.5GHz WiFi (R0) Average Elevation 90

### 5.18GHz Wi-Fi (Radio 0L, Tri-Radio Mode)

### 5.875GHz Wi-Fi (Radio 0U, Tri-Radio Mode)





## Summary of Changes

| Date        | Version History | Action  | Description of Change  |
|-------------|-----------------|---------|--|
| 05-Jul-2022 | Version 9       | Changed | Configuration Information section was updated, new SKUS were added.                                    |
| 06-Dec-2021 | Version 8       | Changed | SKUs were added in Configuration Information section was updated.                                      |
| 15-Mar-2021 | Version 7       | Changed | SKUs were added in Configuration Information section was updated.                                      |
| 08-Sep-2020 | Version 6       | Changed | Configuration Information section was updated<br>New SKUS were added<br>Obsolete SKUs were removed     |
| 09-Dec-2019 | Version 5       | Changed | Standard Features section was updated  |
| 04-Nov-2019 | Version 4       | Changed | Configuration Information section was updated<br>New SKUS were added                                   |
| 07-Oct-2019 | Version 3       | Changed | Overview, Standard Features and Configuration Information sections were updated<br>New SKUS were added |
| 03-Jun-2019 | Version 2       | Changed | Configuration Information Section was updated.<br>New SKUs were added.                                 |
| 02-Apr-2019 | Version 1       | New     | New QuickSpecs   |



## Copyright

Make the right purchase decision.  
Contact our presales specialists.



---

© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00060236enw - 16365 - Worldwide - V9 - 05-July-2022