



The bridge to possible

[Data sheet](#)  
Cisco public

# Cisco UCS B200 M5 Blade Server

---

# Contents

|                                    |   |
|------------------------------------|---|
| Product overview                   | 3 |
| Main features                      | 4 |
| Product specifications             | 5 |
| System requirements                | 6 |
| Ordering information               | 6 |
| UCS B200 Ready2Ship Program        | 7 |
| Warranty information               | 7 |
| Cisco environmental sustainability | 8 |
| Product environmental information  | 8 |
| Takeback and Recycle Program       | 8 |
| Cisco and Partner Services         | 8 |
| Cisco Capital                      | 9 |



For remote sites or data centers, the enterprise-class Cisco UCS® B200 M5 Blade Server delivers market-leading performance, versatility, and density without compromise for workloads ranging from web infrastructure to distributed databases.

## Product overview

The Cisco UCS B200 M5 Blade Server delivers performance, flexibility, and optimization for deployments in data centers, in the cloud, and at remote sites. This enterprise-class server offers market-leading performance, versatility, and density without compromise for workloads, including Virtual Desktop Infrastructure (VDI), web infrastructure, distributed databases, converged infrastructure, and enterprise applications such as Oracle and SAP HANA. The B200 M5 server can quickly deploy stateless physical and virtual workloads through programmable, easy-to-use [Cisco UCS Manager](#) and Cisco Intersight™ and simplified server access through Cisco SingleConnect technology. It includes:

- 2<sup>nd</sup> Gen Intel® Xeon® Scalable and Intel Xeon Scalable processors with up to 28 cores per socket
- Up to 24 DDR4 DIMMs for improved performance with up to 12 DIMM slots ready for Intel Optane™ DC Persistent Memory
- Up to 2 GPUs
- Up to 2 Small Form-Factor (SFF) drives
- Up to 2 SD cards or M.2 SATA drives
- Up to 80 Gbps of I/O throughput

---

## Main features

The Cisco UCS B200 M5 server is a half-width blade. Up to eight servers can reside in the 6-Rack-Unit (6RU) Cisco UCS 5108 Blade Server Chassis, offering one of the highest densities of servers per rack unit of blade chassis in the industry. You can configure the B200 M5 to meet your local storage requirements without having to buy, power, and cool components that you do not need.

The Cisco UCS B200 M5 provides these main features:

- Up to two 2<sup>nd</sup> Gen Intel Xeon Scalable and Intel Xeon Scalable processors with up to 28 cores per CPU
- 24 DIMM slots for industry-standard DDR4 memory at speeds up to 2933 MHz, with up to 3 TB of total memory when using 128-GB DIMMs. Up to 12 DIMM slots ready for Intel Optane DC Persistent Memory to accommodate up to 6 TB of Intel Optane DC Persistent Memory
- Modular LAN on Motherboard (mLOM) card with Cisco UCS Virtual Interface Card (VIC) 1440 or 1340, a 2-port, 40-gigabit Ethernet (GE), Fibre Channel over Ethernet (FCoE)-capable mLOM mezzanine adapter
- Optional rear mezzanine VIC with two 40-Gbps unified I/O ports or two sets of 4 x 10-Gbps unified I/O ports, delivering 80 Gbps to the server; adapts to either 10- or 40-Gbps fabric connections
- Two optional, hot-pluggable, Hard Disk Drives (HDDs), Solid-State Drives (SSDs), or Nonvolatile Memory Express (NVMe) 2.5-inch drives with a choice of enterprise-class Redundant Array of Independent Disks (RAID) or pass-through controllers
- Support for Optional SD Card or M.2 SATA drives for flexible boot and local storage capabilities
- Support for up to 2 optional GPUs
- Support for one rear storage mezzanine card
- Support for one 16-GB internal flash USB drive

## Product specifications

Table 1 lists the specifications for the Cisco UCS B200 M5 Blade Server.

**Table 1.** Specifications

| Item                                     | Specifications  |
|--|---|
| <b>Processors</b>                        | Up to 2 Intel Xeon Scalable processors (1 or 2)   |
| <b>Memory</b>                            | 24 DDR4 DIMM slots: 16, 32, 64, and 128 GB at up to 2933 MHz  |
| <b>Intel Optane DC Persistent Memory</b> | 12 DIMM slots: 128, 256, and 512 GB at up to 2666 MHz   |
| <b>mLOM</b>                              | mLOM slot for Cisco UCS VIC 1440 or 1340  |
| <b>Mezzanine adapter (rear)</b>          | 1 rear mezzanine adapter for: <ul style="list-style-type: none"><li>• Cisco UCS VIC 1480 or 1380 mezzanine card</li><li>• Cisco® port expander mezzanine card</li><li>• Cisco nVIDIA P6 GPU rear mezzanine card</li><li>• Cisco blade NVMe storage card</li></ul>   |
| <b>Mezzanine adapter (front)</b>         | 1 front mezzanine adapter for: <ul style="list-style-type: none"><li>• Cisco FlexStorage 12-Gbps SAS RAID Controller</li><li>• Cisco FlexStorage 12-Gbps SAS RAID Controller with 2-GB cache</li><li>• Cisco FlexStorage NVMe or pass-through module</li><li>• Cisco nVIDIA P6 GPU front mezzanine card</li></ul>   |
| <b>Internal storage</b>                  | 2 hot-pluggable front-access 2.5-inch drives: <ul style="list-style-type: none"><li>• <b>HDD:</b> 10,000 or 15,000 RPM with up to 1.8 TB per drive</li><li>• <b>SSD:</b> Enterprise Performance and Value SSDs with up to 7.6 TB per drive</li><li>• <b>NVMe:</b> Up to 7.7 TB per drive</li></ul> <p><b>Note:</b> Drives require a RAID or pass-through controller in the front mezzanine adapter slot.</p> <p>Choice of either:</p> <ul style="list-style-type: none"><li>• 2 internal SD cards (32-, 64-, or 128-GB with boot-mirroring or</li><li>• Up to 2 M.2 SATA drives (240 or 960 GB) supported via LSI software RAID</li></ul> |
| <b>Management</b>                        | <a href="#">Cisco Intersight software</a><br><a href="#">Cisco UCS Manager Release 4.0(4)</a><br><a href="#">Cisco UCS Central Software</a> <a href="#">Cisco UCS Director</a> <a href="#">Cisco UCS Performance Manager</a>  |
| <b>Temperature: operating</b>            | 50° to 95° F (10° to 35° C)   |
| <b>Temperature: nonoperating:</b>        | -40° to 149° F (-40° to 65° C)  |
| <b>Humidity: operating</b>               | 5% to 93% noncondensing   |

| Item                          | Specifications   |
|-------------------------------|--|
| <b>Humidity: nonoperating</b> | 5% to 93% noncondensing  |
| <b>Altitude: operating</b>    | 0 to 10,000 ft (0 to 3000m); maximum ambient temperature decreases by 1°C per 300m |
| <b>Altitude: nonoperating</b> | 40,000 ft (12,000m)  |

## System requirements

Table 2 lists system requirements for the server.

**Table 2.** System requirements

| Item                              | Requirements  |
|-----------------------------------|---|
| <b>Blade chassis</b>              | Cisco UCS 5108 Blade Server Chassis   |
| <b>Fabric interconnect</b>        | Cisco UCS 6248 UP, 6296UP, 6332- 16UP, 6332, 6324, and 6454 Fabric Interconnects                            |
| <b>Fabric extender</b>            | Cisco UCS 2204, 2208, 2304 Fabric Extenders   |
| <b>Cisco UCS Manager software</b> | Current: Release 4.0(4) or later; refer to the UCSM Release Notes for supported releases for this platform. |

## Ordering information

Table 3 provides ordering information for the Cisco UCS B200 M5.

**Table 3.** Ordering information

| Part number            | Description  |
|------------------------|--|
| <b>UCSB-B200-M5</b>    | Cisco UCS B200 M5 Blade w/o CPU, memory, HDD, mezzanine              |
| <b>UCSB-B200-M5-U</b>  | Cisco UCS B200 M5 Blade w/o CPU, memory, HDD, mezzanine (UPG)        |
| <b>UCSB-B200-M5-CH</b> | DIST1: Cisco UCS B200 M5 w/o CPU, memory, drive bays, HDD, mezzanine |

For information about installing or upgrading your server, see the [Cisco UCS B200 M5 hardware installation guide](#).

For ordering information, see the [Cisco UCS B200 M5 Blade Server specification sheet](#).

## UCS B200 Ready2Ship Program

### 5 Ready2Ship Blade Configurations

- Most popular
- Shipped within 5 days
- Standard Pricing

**Table 4.** Available Configuration PIDs

| Part number              | Description  |
|--------------------------|--|
| <b>UCSB-B200M5-RSV1A</b> | Qty 1 B200 M5 Blade Server with Qty 2 Intel 6252, Qty 12 64GB Memory, Qty 1 1340 MLOM, Qty 1 M2 240GB HW RAID  |
| <b>UCSB-B200M5-RSV1B</b> | Qty 1 B200 M5 Blade Server with Qty 2 Intel 6226R, Qty 12 64GB Memory, Qty 1 1440 MLOM, Qty 1 M2 240GB HW RAID |
| <b>UCSB-B200M5-RSV1C</b> | Qty 1 B200 M5 Blade Server with Qty 2 Intel 6248, Qty 12 32GB Memory, Qty 1 1340 MLOM, Qty 1 M2 240GB HW RAID  |
| <b>UCSB-B200M5-RSV1D</b> | Qty 1 B200 M5 Blade Server with Qty 2 Intel 6254, Qty 12 64GB Memory, Qty 1 1340 MLOM, Qty 1 M2 240GB HW RAID  |
| <b>UCSB-B200M5-RSV1E</b> | Qty 1 B200 M5 Blade Server with Qty 2 Intel 5218R, Qty 12 64GB Memory, Qty 1 1440 MLOM, Qty 1 M2 240GB HW RAID |

#### Note:

- 3-5 days is Business days, does not include delivery time and is based on receipt of final Partner PO; Subject to parts in stock at time of final PO
- Only orderable through Authorized Build To Order (BTO) Distributors – Tech Data US.

## Warranty information

Cisco UCS B200 M5 Blade Servers have a 3-year Next-Business-Day (NBD) hardware warranty and 90-day software warranty.

Augmenting the Cisco Unified Computing System™ (Cisco UCS) warranty, Cisco Smart Net Total Care® and Cisco Solution Support services are part of Cisco's technical services portfolio. Cisco Smart Net Total Care combines Cisco's industry-leading and award-winning foundational technical services with an extra level of actionable business intelligence that is delivered to you through the smart capabilities in the Cisco Smart Net Total Care portal. For more information, please refer to:

<https://www.cisco.com/c/en/us/support/services/smart-net-total-care/index.html>.

Cisco Solution Support includes both Cisco product support and solution-level support, resolving complex issues in multivendor environments on average 43 percent more quickly than with product support alone. Cisco Solution Support is a critical element in data center administration, helping rapidly resolve any issue encountered while maintaining performance, reliability, and return on investment.

This service centralizes support across your multivendor Cisco environment for both our products and solution partner products that you have deployed in your ecosystem. Whether there is an issue with a Cisco product or with a solution partner product, just call us. Our experts are the primary point of contact and own the case from first call to resolution. For more information, please refer to:

<https://www.cisco.com/c/en/us/services/technical/solution-support.html>.

## Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

| Sustainability topic   | Reference                       |
|--|---------------------------------|
| Information on product material content laws and regulations                                       | <a href="#">Materials</a>       |
| Information on electronic waste laws and regulations, including products, batteries, and packaging | <a href="#">WEEE compliance</a> |

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

## Product environmental information

Product environmental information for users per Commission Regulation (EU) 2019/424

<https://www.cisco.com/web/dofc/18799424.pdf>

## Takeback and Recycle Program

For more information, please refer to <https://www.cisco.com/c/en/us/about/product-innovation-stewardship/product-recycling/takeback-recycle-program.html>.

## Cisco and Partner Services

Cisco and our industry-leading partners deliver services that accelerate your transition to a Cisco UCS B-Series Blade Servers solution. Cisco Unified Computing Services can help you create an agile infrastructure, accelerate time to value, reduce costs and risks, and maintain availability during deployment and migration. After deployment, our services can help you improve performance, availability, and resiliency as your business needs evolve and help you further mitigate risk. For more information, visit

<https://www.cisco.com/go/unifiedcomputingservices>.



---

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)