

USB-C 10Gbps to M.2 NVMe or M.2 SATA SSD Enclosure - Portable External M.2 PCIe/SATA NGFF SSD Aluminum Case - USB Type-C & USB-A Host Cables - Supports 2230/2242/2260/2280

Productcode: SM2E1BMU31C



Turn your PCIe M.2 NVMe or SATA AHCI M.2 SSD into a highly portable, USB-based external storage solution. This enclosure features USB 3.2 Gen 2x1 (10Gbps) with UASP support & PCIe 3.0 delivering real read/write data transfer speeds up to 1GB per second. Working with both PCIe and SATA based drives, this enclosure ensures compatibility with virtually any M.2 drive, supporting both M-Key (PCIe) and B+M-Key (SATA) drives sized 2230/2242/2260/2280.

USB 3.2 Gen 2x1 10Gbps (also known as USB 3.1 Gen 2) is backward compatible with USB 3.1 Gen 1 5Gbps (also known as USB 3.0), USB 2.0, and USB 1.1.

With compatibility for both PCIe NVMe and SATA based M.2 drives, this enclosure solves the common challenge of identifying which enclosure is compatible with your M.2 drive. Regardless of whether your M.2 drive is SATA or PCIe NVMe based, you can rest assured that this enclosure will provide a high-performance solution for turning your M.2 drive into a portable external enclosure. For further compatibility the enclosure works with multiple drive heights supporting 2230, 2242, 2260 and 2280mm drives including Samsung (850, 860, 870, 950, 960, 970) Kingston, Seagate, Western Digital (WD), HP, and Intel SSD drives.

For multiplatform support this enclosure, that features a USB-C host connection, includes two different host cables, a USB-C to USB-C cable (20 in. / 50 cm) and a USB-C to USB-A cable (10" / 25 cm). This combined with the backward compatibility of the USB protocol, ensures that this M.2 enclosure will work with virtually any computer, whether it's USB-A, USB-C or Thunderbolt 3.

Leverage the high speeds of your M.2 NVMe or SATA drive, with this external SSD enclosure. It delivers USB 3.2 Gen 2x1 maximum theoretical throughput of 10Gbps, which is twice the throughput of USB 3.2 Gen 1x1 at 5Gbps. The enclosure also supports PCIe 3.0 which when combined with an M.2 NVMe drive takes full advantage of the throughput available to USB 3.2 Gen 2x1.

This fan-less aluminum enclosure features ventilation holes for maximum heat dissipation, ensuring your drive operates noiselessly at an optimal temperature to preserve performance and protect your drive from overheating damage.

This slim, pocket-sized enclosure for PCIe NVMe or SATA based M.2 drives is specially designed for mobility, with a small form-factor design that fits easily into your laptop bag. Its lightweight, yet durable aluminum housing helps to ensure your drive won't be damaged while you're on the move.

The external M2 SATA or M.2 NVMe SSD enclosure case supports driverless plug-and-play installation and hassle free drive installation. A screwdriver is included ensuring no additional tools are required.

SM2E1BMU31C is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certificaties, rapporten en compatibiliteit

Toepassingen

- Creëer een mobiele, krachtige opslagoplossing
- Access your NVMe or SATA drive externally with ultra-fast transfer speeds
- Superieure snelheden zijn ideaal voor taken waarbij gegevens moeten worden overgedragen

Eigenschappen

- **HIGH PERFORMANCE:** External USB-C or USB-A storage solution for your PCIe M.2 NVMe or SATA M.2 AHCI SSD; This enclosure features USB 3.2/3.1 Gen 2 (10Gbps) with UASP support & PCI Express 3.0
 - **M.2 COMPATIBILITY:** Works with M.2 PCIe NVMe (M-Key) & M.2 SATA (B+M-Key) based drives; Works with 2230/2242/2260/2280 SSDs including Samsung 850/860/870/950/960/970, Kingston, Seagate, Western Digital, HP, and Intel SSD drives; NOT COMPATIBLE W/22110mm
 - **WORKS WITH USB HOST:** M.2 SATA or M.2 NVMe SSD enclosure comes with two separate USB host cables to provide support for both USB Type-A and USB Type-C/Thunderbolt 3 host computers; Backward compatible with USB 3.0/2.0
 - **DURABILITY & RELIABILITY:** Enclosure with aluminum housing protects the SSD; The NGFF case features ventilation holes for heat dissipation to ensure consistency at peak performance levels, making it a reliable solution for high-speed data backup & recovery
 - **EASY INSTALLATION:** The M2 SATA or M.2 NVMe SSD (solid state drive) adapter enclosure supports driverless plug-and-play installation & hassle free drive installation (screwdriver incl.); 20in (50cm) USB-C cable and 10in (25cm) USB-A cable incl.
-

Hardware

Garantiebeleid	2 Years
Interface	USB 3.1 Gen 2
Bus type	USB 3.2 Gen 2 10Gbps
Aantal stations	1
Schijfgrootte	22 mm - M.2 NVMe
Schijftype	M.2 (PCIe, NVMe, M-Key, NGFF) M.2 SATA (NGFF, B+M-Key)
Schijfinstallatie	Vast
Ondersteunde schijfhoogte(n)	2230 2242 2260 2280
Chipsetcode	Realtek - RTL9210B

Prestaties

Maximale overdrachtsnelheid	10 Gbps
Type en snelheid	USB 3.2 Gen 2 - 10 Gbit/s
UASP ondersteuning	Ja
TRIM Support	Ja
4Kn Support	Ja
Type en snelheid	NVMe (PCIe Gen 3)
Aantal plaatsingen	USB-C: 10,000 cycles M.2: 60 Cycles
Algemene specificaties	Fully compatible with M.2 SATA, AHCI and PCIe NVMe based drives



	MTBF	112,000 Hours
<hr/>		
Connector(en)	Schijfaansluitingen	M.2 (PCIe, SATA, M-Key, NGFF)
	Hostaansluitingen	USB 3.1 USB Type C (10 pin, Gen 2, 10 Gbps)
<hr/>		
Software	Besturingssystemen	Onafhankelijk van besturingssysteem; Geen software of drivers nodig
<hr/>		
Speciale opmerkingen / vereisten	Notitie	Windows 7 en vroegere Windows-versies ondersteunen TRIM niet bij USB-opslagapparaten.
<hr/>		
Indicatoren	LED-indicatoren	Voeding & activiteit
<hr/>		
Voeding	Inclusief voedingsadapter	Gevoed via USB
<hr/>		
Gebruiksomgeving	Bedrijfstemperatuur	0°C to 40°C (32°F to 104°F)
	Opslagtemperatuur	-10°C to 65°C (14°F to 149°F)
	Vochtigheid	Vochtigheid tijdens gebruik: 10% ~ 90% RV Vochtigheid tijdens opslag: 5% ~ 95% RV
<hr/>		
Fysieke eigenschappen	Kleur	Zwart
	Type behuizing	Aluminium en kunststof
	Lengte product	1.6 in [40.0 mm]
	Breedte product	5.1 in [12.8 cm]
	Hoogte product	0.6 in [14.0 mm]
	Gewicht product	2.9 oz [81.6 g]



Verpakkingsinformatie

Package Length	4.2 in [10.6 cm]
Package Width	6.1 in [15.4 cm]
Package Height	1.4 in [35.0 mm]
Verzendgewicht (verpakt)	6.8 oz [193.4 g]

Wat wordt er meegeleverd

Meegeleverd	M.2 SSD-behuizing
	USB-C naar USB-C kabel
	USB-A naar USB-C kabel
	Schijfinstallatieschroevenset
	Microschroevendraaier
	Quick-start handleiding

* Uitvoering en specificaties van het product zijn zonder aankondiging vatbaar voor wijzigingen.

