## **Key Features**

- Instant, secure access to your digital workspace using Windows Hello
- Crystal-clear video with a built-in Zoom®
   Certified 5MP pop-up camera with LED fill lights, microphone, and 5W speakers
- Integrated docking station with Ethernet,
   Daisy Chain capability, and dual USB-C ports
   for seamless connectivity
- 15W quick charging for mobile devices via
   USB-C connection
- Flicker-free, low blue light screen with Eye
   ProTech+ for always-on eye protection



## Product **Description**

The VG2757V-2K is a 27" QHD videoconferencing monitor featuring Windows Hello compatibility. It boasts a Zoom® Certified QHD pop-up webcam that delivers exceptional audiovisuals and discreetly hides away for privacy when not in use. With Windows Hello, it ensures secure facial recognition for swift and convenient logins, eliminating the dependency on passwords. Equipped with 90W and 15W USB-C ports, ethernet, and daisy-chain support, the VG2757V-2K serves as a complete integrated docking station for charging, data transfer, and network connectivity, effectively reducing cable clutter. Its extensive ergonomic flexibility allows tilt, swivel, pivot, and height adjustments for various workflows. Enhanced by vDisplay Manager software for efficient multitasking and on-screen display controls, it offers a comprehensive videoconferencing solution.

Visit Us

www.viewsonic.com



DISPLAY		ADDITIONAL HARDWARE	
Display Size (in.):	27	Kensington Lock Slot:	1
Viewable Area (in.):	27	Webcam:	5.0M pixel
Panel Type:	IPS Technology	Cable Organization:	Yes
Resolution:	2560 x 1440	Microphone:	Yes
Resolution Type:	QHD (Quad HD)	CONTROLS	
Static Contrast Ratio:	1,300:1 (typ)	Physical Controls:	Key 1 (eye), Key 2, Key 3, Key 4, Key
Dynamic Contrast Ratio:	80M:1	i nysicai Controls.	5, Key 6 (power)
Light Source:	LED	On Screen Display:	Input Select, Conference Mode, ViewMode, Color Adjust, Manual
Brightness:	350 cd/m² (typ)		Image Adjust, Setup Menu
Colors:	16.7M	OPERATING CONDITIONS	
Color Space Support:	8 bit true	Temperature:	32°F to 104°F (0°C to 40°C)
Aspect Ratio:	16:9	Humidity (non-condensing):	20% to 90%
Response Time (Typical GTG):	5ms	WALL MOUNT	
Response Time (GTG w/OD):	5ms	VESA Compatible:	100 x 100 mm
Viewing Angles:	178° horizontal, 178° vertical	INPUT SIGNAL	45 45001
Backlight Life (Hours):	30000 Hrs (Min)	Frequency Horizontal:	15 ~ 150KHz
Curvature:	Flat	Frequency Vertical:	50 ~ 100Hz
Refresh Rate (Hz):	100	VIDEO INPUT	TMDS HDMI (v2.0) BOLE
Low Blue Light:	Software solution	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4), Micro-Packet -
Flicker-Free:	Yes	EDCONOMICS	Type C
	NTSC: 76% size (Typ) sRGB: 108%	ERGONOMICS	110
Color Gamut:	size / 100% coverage (Typ)	Height Adjust (mm):	120°
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Swivel:	
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Tilt (Forward/Back):	-5° / 40°
COMPATIBILITY		Pivot (Right/Left):	90° / 90°
PC Resolution (max):	2560x1440	WEIGHT (IMPERIAL)	47.7
Mac® Resolution (max):	2560x1440	Net (lbs):	17.7
PC Operating System:	Windows 10/11 certified; macOS	Net Without Stand (lbs):	12
	tested	Gross (lbs):	25.3
Mac® Resolution (min):	2560x1440	WEIGHT (METRIC)	8
CONNECTOR	1	Net (kg):	5.5
USB 3.1 Type C - Downstream:		Net Without Stand (kg):	11.5
USB 3.2 Type A Down Stream:	3	Gross (kg):	
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1 (90W power charger)	DIMENSIONS (IMPERIAL) (WX	27.1 x 17.8 x 8.9
3.5mm Audio Out:	1	Packaging (in.):	
HDMI 2.0:	1	Physical (in.):	24.12 x 16.67~21 x 8.55
DisplayPort:	1	Physical Without Stand (in.): 24.12 x 15.36 x 2.24	
Power in:	3-pin Socket (IEC C14 / CEE22)	DIMENSIONS (METRIC) (WXH Packaging (mm):	689 x 452 x 225
Ethernet LAN (RJ45):	1	Physical (mm):	612.7 x 423.38~533.38 x 217.24
AUDIO		Physical Without Stand (mm):	612.7 x 390.15 x 56.9
Internal Speakers:	5Watts x2	GENERAL	012.7 X 390.13 X 30.9
POWER		GENERAL	cTUVus, FCC-B, ICES003, Energy
Eco Mode (Conserve):	24.36W	Regulations:	Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS,
Eco Mode (optimized):	26.75W		ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
Consumption (typical):	29.77W		
Consumption (max):	34.29W	PACKAGE CONTENTS:	VG2757V-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Gen2 Cable (Male-Male) x1, USB Type-C to
Voltage:	AC 100-240V		
Stand-by:	0.5W		Type-A 3.2 Gen1 Cable (Male-Male) x1, Quick Start Guide x1
Power Supply:	Internal Power Supply	Pagyala/Dianagal	Please dispose of in accordance with
		Recycle/Disposal:	local, state or federal laws.  *Warranty offered may differ from
		Warranty:	market to market
		Power Management:	Energy Star standards, EPEAT