

MultiSync® E221N NEC LCD 22" Commercial Display

## **Datasheet**



# NEC MultiSync® E221N Ultra-Thin Bezel - The Office Workhorse, combining sleek and elegant design with health-conscious performance

The 22" ultra-thin bezel display targeting reliable office productivity, performance and quality, fulfils demand for future-ready design. Enduring productivity requires high attention to healthcare. Thanks to the built-in Low Blue Light Plus technology your eyes are protected and ensure overall well-being. It filters out only the hazardous blue light emissions and eliminates flickering, keeping the eye safe while ensuring a true-to-life display colour performance from all viewing angles. The LED backlight panel with AH-IPS technology supports a high display brightness of 250 cd/m² and in parallel lowers power consumption.

The ultra-narrow bezel display reduces the display footprint without compromising on screen size and gives an office a fresh professional interior with its sleek and elegant design.

#### **Benefits**

Future-Ready Design – best in form and function design with 3-sided 1 mm ultra-thin bezel gives an office a fresh professional interior. Protecting your eyes from strain and damage – built-in Low Blue Light Plus technology filters out hazardous blue light emissions and eliminates flickering protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Ergonomic Office – full height adjustability (110 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Business Class Image Quality – IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour production.

Your environmental and social responsibility – NEC's TCO 7 and ENERGY STAR 7 certified display is environmentally designed with minimal hazardous materila meeting the growing demand for more sustainable technologies.

| Product Information           |   |  |  |
|-------------------------------|---|--|--|
| Product Name                  | MultiSync® E221N  |  |  |
| Product Group                 | NEC LCD 22" Commercial Display                              |  |  |
| Order Code                    | 60004223 (WH) , 60004224 (BK)                               |  |  |
| Display                       |   |  |  |
| Panel Technology              | IPS TFT with W-LED backlight                                |  |  |
| Screen Size [inch/cm]         | 21.5 / 54.62  |  |  |
| Screen Aspect Ratio           | 16:9  |  |  |
| Pixel Pitch [mm]              | 0.248   |  |  |
| Brightness (typ.) [cd/m²]     | 250   |  |  |
| Contrast Ratio (typ.)         | 1000:1  |  |  |
| Viewing Angle [°]             | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |  |  |
| Response Time (typ.) [ms]     | 6   |  |  |
| Colours [Mio.]                | 16.77   |  |  |
| Synchronisation Rate          |   |  |  |
| Horizontal Frequency [kHz]    | 31.5 - 81.1   |  |  |
| Vertical Frequency [Hz]       | 56 - 76   |  |  |
| Resolution                    |   |  |  |
| Optimum Resolution            | 1920 x 1080 at 60 Hz  |  |  |
| Connectivity                  |   |  |  |
| Digital                       | 1 x DisplayPort; 1 x HDMI                                   |  |  |
| Analog                        | 1 x D-sub 15 pin  |  |  |
| Electrical                    |   |  |  |
| Power Consumption on Mode [W] | 15 (Eco Mode 1); 17 (typ.); 25 (max.)                       |  |  |
| Power Savings Mode [W]        | 0.29  |  |  |
| Environmental Conditions      |   |  |  |
| Operating Temperature [°C]    | +5 to +25   |  |  |
| Operating Humidity [%]        | 20 to 80  |  |  |
| Ergonomics                    |   |  |  |
| Height adjustable stand [mm]  | 110   |  |  |
| Screen Tilt [°]               | 5 to 20   |  |  |
|                               | 0.020   |  |  |

| RA. | ecl |     | -:- | _  |
|-----|-----|-----|-----|----|
| IVI | eci | nar | uc  | aı |
|     |     |     |     |    |

Screen Swivel [°]

45 to 45

| Bezel Width [mm]            | 1 (left and right); 1 (top) |
|-----------------------------|-----------------------------|
| Dimensions (W x H x D) [mm] | 488.1 x 359.8 x 213.9       |
| Weight [kg]                 | With stand: 5               |
| VESA Mounting [mm]          | 100 x 100                   |

#### **Additional Features**

| Special Characteristics | DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2                  |  |
|-------------------------|---|--|
| Colour Versions         | Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet              |  |
| Cable Management        | yes   |  |
| Plug and Play           | VESA DDC2Bi   |  |
| Audio                   | 1W + 1W (De-activateable); Headphone Jack   |  |
| Shipping Content        | Power Cable; Setup Guide  |  |
|                         | Signal Cable: DisplayPort; VGA - VGA  |  |
| Safety and Ergonomics   | EnergyStar 7.0; Flicker-free; Low Blue Light; RoHS; TCO 7.0; TÜV Ergonomics; TÜV GS; WEEE |  |

### **Green Features**

| Energy Efficiency    | Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy efficiency class: A |
|----------------------|--|
| Ecological Standards | Energy Star 7.0; RoHS compliant; TCO 7.0; WEEE                                     |







This document is © 2017 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 10.01.2017