



Delock External USB 3.1 Hub 4 Port with 10 Gbps

Description

This USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by **four USB Type-A** connectors.

Hub with power supply

The included power supply provides power to the connected devices on the front. The hub can also be used without a power supply.



Specification

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
 - 4 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
 - 1 x DC 12 V power connector
- Chipset: VIA VL820
- Data transfer rate up to:
 - SuperSpeed USB 10 Gbps,
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- 1 x LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 92 x 54 x 19 mm
- Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.5 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Chrome OS
- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- Hub USB
- 1 x Cable USB A male to USB-C™ male, length ca. 1 m
- Power supply
- User manual

Item no. 64053

EAN: 4043619640539

Country of origin: China

Package: • Retail Box



Images





General	
Function:	Plug & Play
Specification:	SuperSpeed USB 10 Gbps (USB 3.1 Gen 2)
Supported operating system:	Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.6 or above Mac OS 10.13.3 or above
LED indicator:	1 x
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Connector 2:	4 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
connector 3:	1 x DC jack
Technical characteristics	
Chipset:	VIA VL820
Data transfer rate:	10 Gbps
Physical characteristics	
Length:	92 mm
Width:	54 mm
Height:	19 mm
Colour:	black
Power supply	
Input:	AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
Output:	12 V / 2 A
Connector:	DC plug 5.5 mm x 2.5 mm