



USB 3.1 Type C to HDMI Converter with USB Type A port and Power Delivery

No.: 43340

Connect an HDMI display, a USB device and a Type C power supply to a single USB Type C port

Description

- Adds an HDMI port, a USB Type A port and a Type C power supply port to your computer
- Supports HDMI resolutions up to 4K 3840x2160@30Hz
- Supports USB 3.2 / 3.1 Gen 1 / USB 3.0 standard (5Gbps)
- Supports Power Delivery 3.0 up to 100W
- 2 year warranty

The Lindy USB 3.1 Type C to HDMI, USB & Power Delivery Converter allows users to maximise the functionality of a single USB 3.1 Type C port by connecting and simultaneously using an HDMI display and USB SuperSpeed peripheral as well as a USB Type C power supply to your MacBook, ultrabook or notebook. The only requirement is that the computer supports the DisplayPort Alternate Mode.

USB Power Delivery of up to 100W provides power to a notebook or ultrabook, simply connect a compatible USB power supply to the USB Type C socket of the converter.

With support for resolutions up to 3840x2160p 30Hz, the converter is ideal for use by designers and video editors.

Installation is simple as no drivers are required, while Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- AV Interface: USB Type C to HDMI
- Interface Standard: HDMI 1.4
- Supported Bandwidth: -
- Maximum Input Resolution: 3840x2160@30Hz

- Maximum Output Resolution: 3840x2160@30Hz
- Chipset: VL815, AG6311
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support (incl. Apple M1)
- Power Delivery: PD 2.0 up to 60W (20V 3A)
- HDCP Support: HDCP 1.4
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x HDMI (Female), 1 x USB Type A (Female)
- Power: Bus-powered

Physical Properties

- Dimensions (approx.) WxDxH: 75.5x38.4x15.3mm (2.97x1.51x0.6in)
- (Fixed) Cable Length: 180mm (7.09in)
- Housing Material: Plastic
- Net Weight: 0.042kg (0.09lb)
- Operating Temperature: -20°C - 40°C (-4°F - 104°F)
- Storage Temperature: -40°C - 80°C (-40°F - 176°F)
- Humidity: 5 - 90% RH (non-condensing)
- Power Requirements: -
- Colour: White

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x194mm (6.85x7.64in)
- Gross Weight: 0.06kg (0.13lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

Package Contents

- USB 3.1 Type C to HDMI Converter
- Lindy Manual

Purchasing information

- No.: 43340
- EAN: 4002888433402