



2 Port Dual Head HDMI 4K60, USB 3.0 KVM Switch

No.: 39314

Fast switching via buttons, hotkeys, IR remote control and RS232

Description

- Controls two HDMI® equipped PCs from a single console with keyboard, mouse and two monitors
- Dual Head support with 2 modes, single and dual PC mode
- Supports HDMI® 18G resolutions up to 4K@60Hz 4:4:4 with HDR
- USB 3.0 and 3.5mm stereo audio port to connect additional USB devices, speakers or headphones
- 2 year warranty

This KVM Switch can share 2 displays and USB devices between 2 computers in different modes: Single PC mode with both video showing the dual head input from one source; Dual PC mode with the first display fixed on the first PC1 input and the second display fixed on the first PC2 input.

Switching methods are:

- Front panel buttons
- Hotkeys [with on/off button]
- IR remote control
- RS-232 commands

Support for resolutions up to 4K Ultra HD 60Hz ensures the highest image quality, perfect for demanding graphical content in gaming setups, video editing or dual system control workstations. The additional support for (HDR) High-Dynamic Range ensures video content can be seen with enhanced brightness, greater contrasts and a much wider colour gamut. The audio output port also allow users to connect headphones or speakers to add immersive 2CH audio.

USB ports allow the connection of mouse, keyboard and additional USB 3.2 Gen 1 devices such as web cam, flash drive, printer, etc. Auto-switch function enables automatic switching between connected PCs and DDM function ensures that all connected USB devices retain their settings and functionality when switching between PCs ensuring the maximum compatibility.

With advanced features and different switching methods, this switch is the perfect solution for professional KVM installations, plug and play presentations and home offices.

Technical details

Specifications

- AV Interface: HDMI®
- Console Interfaces: USB
- Interface Standard: HDMI® 2.0, USB 3.0
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8Bit

HDCP Support: 2.3
Supported Audio: HDMI® Pass Through, Analogue Stereo
Separate Audio Ports: 3.5mm [Female]
Serial Interface: 3-pin Terminal Block
Console Number: 1
Max Number PC/Server: 2
Cascadable: -
Switching Method: Push Button, Mouse & Keyboard Hotkeys, IR Remote control, RS-232 commands
19" Rack Mountable: -
Special Features: USB 3.0 device ports, dual head, active LED indicators

Connectors

Console Interfaces: 2 x HDMI® Type A [Female], 4 x USB Type A [Female], 3.5mm [Female]
PC/Server Interfaces: 4 x HDMI® Type A [Female], 2 x USB 3.0 Type B [Female]
Other Interfaces: 3-Pin Terminal Block, 3.5mm IR [Female]
Power: 5.5/2.1mm screw type DC socket

Physical Properties

Dimensions (approx.) WxDxH: 220x100x30mm [8.66x3.94x1.18in]
Housing Material: Metal
Net Weight: 0.609kg [1.34lb]
Operating Temperature: 0°C - 40°C [32°F - 104°F]
Storage Temperature: -20°C - 60°C [-4°F - 140°F]
Humidity: 20 - 90% RH [non-condensing]
Power Requirements: 12V 1A
Colour: Black

Miscellaneous

Packaging Type: Carton Box
Packaging Dimensions: 300x185x115mm [11.81x7.28x4.53in]
Gross Weight: 1.611kg [3.55lb]
Warranty [Years]: 2
Certificated: CE, UKCA, FCC, RoHS, REACH & California Proposition 65

Package Content

HDMI® Dual Head KVM Switch
IR Remote Control
IR Receiver Cable, 1.5m
2 x USB 3.0 Cable Type A to Type B, 1.8m
4 x HDMI® Cable, 1.5m
3-Pin Terminal Block
2 x Mounting Ears & 4 x Screws
Multi-country PSU [UK, EU, US & AUS]
Lindy Manual

Purchasing Information

No.: 39314
EAN: 4002888393140