

TAROX ParX µServer G8v2

WITH INTEL® XEON® E-2324G



SPECIFICATIONS

P/N	2315768
Manufacturer	TAROX

CHASSIS

Chassis	TAROX Micro Tower Server Chassi
Formfactor	Mini Tower
Width	210 mm
Heights	230 mm
Depth	276,1 mm
Colour	black
Backplane	4x SAS/SATA 12 Gb/s
HDD / SSD	max. 4x 3,5" / 2x 2,5" fix

FRONT INTERFACES

USB 2.0	-
USB 3.0	2
Line in	-
Line Out	-

PSU

Power	265 W
Efficiency	80+ Bronze

OPERATION SYSTEM

Operation System	optional
Languages	-

MAINBOARD

Mainboard	Intel® C252, 2x DDR4ECC, Mini-ITX
-----------	-----------------------------------

SYSTEM

CPU Socket	1200
Chipset	Intel® C252
Audio Chipset	-
GPU	ASPEED AST2600 BMC
LAN Chipset	2x Intel® i210AT Gigabit LAN
PXE	
Wake on Lan (WoL)	
Trustes Plattform Module (TPM)	1x optional
Formfactor	Mini-ITX
Memory Support	DDR4 ECC UDIMM
max. Memory	64 GB
max. Memory-Modules	2

REAR INTERFACES

USB 3.0	4
USB 2.0	-
RS232	-
LPT	
Displayport	-
HDMI	-
DVI	-
D-Sub	-
RJ-45	2x Intel® i210AT Gigabit LAN
Management	IPMI 2.0, KVM mit dediziertem LAN

INTERNAL INTERFACES

PCI Express x16	1
PCI Express x8	-
PCI Express x4	-
USB 2.0	-
USB 3.0	-
Serielle Ports	1x COM-Port Header
Trusted Plattform Module (TPM)	1x optional
S-ATA Controller	6

PROCESSOR(S)

Processor(s)	Intel® Xeon® E-2324G 3.10 GHz (4 cores)
Base Clock	3.10Ghz
Turbo Clock	4.60Ghz
Cores	4
Cache	8 MB
Virtualization	yes
TDP	65
Socket	1200

MEMORY

Capacity	16 GB
----------	-------

Memory Type	UDIMM ECC
Memory-Modules (installed)	1
HDD / SSD	
Capacity	2x 960GB SATA SSD RAID1
Solid State Disk (SSD)	ja
ODD	
DVD+-R/RW	-
CERTIFICATES	
Decleration of Conformity	yes
Production in Germany according to ISO9001	yes
WEEE-Reg.-Nr. DE 99267951	yes
SERVICE	
Warranty	36 months
Service	36 months NBD