

APC Easy UPS Line-interactive SMV 750VA 230V with Network Slot

SMV750CAI

O	1	Δ	r	/1	Δ	۱۸	
$\mathbf{\mathcal{C}}$	v	C		"	C	V١	v

Presentation	Easy UPS provides power protection for unstable power conditions, ensuring consistent and reliable connectivity at the most critical moments.
Lead time	
Main	
Input voltage	230 V
Input voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	525 W
Rated power in VA	750 VA
Input Connection Type	IEC 60320 C14
Nb of power socket outlets	6 IEC 60320 C13
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Documentation CD User manual USB cable

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Colour	Black	
Height	22 cm	
Width	16 cm	
Depth	41 cm	
Net weight	13.6 kg	

Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Input	
Network frequency	4565 Hz +/- 1 Hz auto-sensing
Input voltage limits	165290 V
Output	
Maximum configurable power in W	525 W
Output frequency	50/60 Hz +/- 1 Hz unsynchronised
Crest factor	3:1
UPS type	Line interactive
Wave type	Sine wave
Graph display	1
Maximum configurable power in VA	750 VA
Transfer time	2-6 ms typical : 12 ms maximum
Conformance	
Product certifications	CE
Standards	EN/IEC 62040-1 EN/IEC 62040-2
Environmental	
Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m
Ambient air temperature for storage	-1040 °C
Storage Relative Humidity	095 % Non-condensing
Storage altitude	015000 m
Acoustic level	45 dBA
IP degree of protection	IP20
Batteries & Runtime	
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Battery voltage	24 V
Battery charger power	33 W rated

3...5 year(s)

0

Battery life

Extended runtime

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

|--|

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	16.6 kg
Package 1 Height	33.9 cm
Package 1 width	27.2 cm
Package 1 Length	50.8 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Under investigation

Contractual warranty

|--|