



by Schneider Electric

# Easy PDU Basic Rack Power Distribution Unit

## Overview

### EPDU1116B, EPDU1132B

The APC by Schneider Electric Easy PDU, Basic Rack Power Distribution Unit distributes power to devices in the rack.

**Outlets.**

EPDU1116B - The Rack PDU has twenty (20) IEC-320-C13, 10A outlets and four (4) IEC-320-C19, 16A outlets.


EPDU1132B - The Rack PDU has two banks of ten (10) IEC-320-C13, 10A outlets and two (2) IEC-320-C19, 16A outlets.

**Power cord.** The power cord is 3 m (9.8 ft) in length.

EPDU1116B - The input connection is an IEC-309 16A 2P+E

EPDU1132B - The input connection is an IEC-309 32A 2P+E

**Mounting.** Two brackets and mounting hardware are provided with the Rack PDU. The Rack PDU also has two (2) toolless mounting pegs installed for 0U mounting capability in a rack or enclosure.



# Specifications

	EPDU1116B	EPDU1132B
<b>Electrical</b>		
Nominal Input Voltage	200 - 240 VAC 1 PHASE	
Maximum Input Current (Phase)	16A	32A
Input Frequency	50/60Hz	
Input Connection	IEC-309 16A 2P+E	IEC-309 32A 2P+E
Output Voltage	200 - 240 VAC 1 PHASE	
Output Connections	IEC-320-C13 (20) Max. output current 10A  IEC-320-C19 (4) Max. output current 16A	Bank1: IEC-320-C13 (10) Max. output current 10A  IEC-320-C19 (2) Max. output current 16A  Bank2: IEC-320-C13 (10) Max. output current 10A  IEC-320-C19 (2) Max. output current 16A
Circuit Breakers	None	Two (2) 16A 1-pole hydraulic-magnetic circuit breakers
<b>Physical</b>		
Dimensions (H x W x D)	902 x 62 x 44.4 mm (35.5 x 2.44 x 1.74 in)	1175 x 62 x 44.4 mm (46.25 x 2.44 x 1.74 in)
Input power cord length	3 m (9.8 ft)	3 m (9.8 ft)
Shipping dimensions (H x W x D)	1320 x 160 x 110 mm (52.0 x 6.30 x 4.33 in)	1320 x 160 x 110 mm (52.0 x 6.30 x 4.33 in)
Weight/Shipping weight	2.2 kg (4.85 lb)/ 2.98 kg (6.56 lb)	3.58kg (7.89 lb)/ 4.36 kg (9.61 lb)
<b>Environmental</b>		
Maximum elevation (above MSL) Operating/Storage	0–3000 m (0–10,000 ft) / 0–15000 m (0–50,000 ft)	
Temperature: Operating/Storage	–5 to 45°C (23 to 113°F) / –25 to 65°C (–13 to 149°F)	
Humidity: Operating/Storage	5–95% RH, non-condensing	
<b>Compliance</b>		
EMC verification	CE EN55035, EN55032, EN55024	
Safety verification	CE, TUV, EN/IEC62368-1	
CE EU Contact Address	Schneider Electric, 35 rue Joseph Monier 92500 Rueil Malmaison France	
Environmental	RoHS & Reach	

Customer support and warranty information are available on the APC by Schneider Electric website, [www.apc.com](http://www.apc.com).

© 2019 APC by Schneider Electric. APC and the APC logo are owned by Schneider Electric S.E. All other trademarks are property of their respective owners.

**990-91339**  
**11/2019**



