

19" Server Cabinet 42 U with top air A&C unit 2130 W, 800x1000x2000 +415



Artikelnummer/SKU 20633-DK-2.1

Produkt delivery time 1-2 weeks

Verfügbarkeit

HE/U 42 Breite/width 800 Tiefe/depth 1000 Höhe/height 2000+415

kW 2.1 Segmentation No

19" Server Climate Cabinet with air conditioning unit with 2130W

- Glazed front door
- Full rear door
- Rotary lever handles
- Lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 42 U
- Max. 19" mounting depth 710 mm
- Cable entry in base module
- Earthing kit Levelling feet
- Air Ducts for increased airflow control
- Roof air conditioner 2130 W
- Operating voltage Volt 230 Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

Note to the site:

- The location and thus the arrangement of the heat must be selected so that good ventilation. is ensured.
- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.
- The refrigerator must be installed and operated in horizontal position (max. deviation: 2°).
- The site must be free from excessive dirt and moisture.
- The ambient temperature must not be higher than 55 ° C.
- A condensate drain must be enabled.
- The network connection specifications on the nameplate of the unit must be ensured.