

Product datasheet

Specifications



Power Cord, Locking C19 to IEC309-16A, 3.0m

AP8758

Overview

Presentation

Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

Lead time

Main

Input Connection Type IEC 60309 16 A 2P + E

Cable length 3.00 m

Physical

Height 43.2 cm

Width 15.2 cm

Depth 10.2 cm

Net weight 0.49 kg

Mounting preference No preference

Mounting mode Not rack-mountable

Input

Max line current 16 A

Input current limits 16 A

Output

Max current draw 16 A

Number of power socket outlets 1 IEC 60320 C19

Power cable length 3.05 m

Conformance

Product certifications VDE

Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...70 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Height	43.2 cm
Package 1 Width	15.2 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.49 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Height	43.2 cm
Package 2 Width	10.2 cm
Package 2 Length	15.2 cm
Package 2 Weight	490 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------