

USB C Multiport Video Adapter w/ HDMI, VGA, Mini DisplayPort or DVI - USB Type C Monitor Adapter to HDMI 2.0 or mDP 1.2 (4K 60Hz) - VGA or DVI (1080p) - Space Gray Aluminum

Product ID: CDPVDHMDMP2G



This USB-C™ multiport video adapter offers a portable solution for connecting your USB Type-C laptop to a VGA, DVI, HDMI® or Mini DisplayPort (mDP) display.

All-in-One Video Connectivity with Travel in Mind

Avoid the hassle of carrying different adapters, with a 4-in-1 USB-C monitor adapter. With VGA, DVI, HDMI and mDP output, you can connect your laptop to any display using this multiport adapter.

The adapter features a magnetic retainer that guides the breakout cable into place for quick, secure portability. With a durable aluminum enclosure, the adapter can withstand being carried in your travel bag.



Ultra HD 4K 60Hz Resolution

The HDMI and mDP outputs on this USB-C video adapter support UHD resolutions up to 4K 60Hz, while the VGA and DVI outputs support HD resolutions up to 1920 x 1200.

Stylish Connectivity for Your MacBook, MacBook Pro, or Any Laptop

The USB-C adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook, or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

The adapter is also available with 4K 30Hz HDMI resolution support, in three colors: Space Gray (CDPVDHDMDP2G), Rose Gold (CDPVDHDMDP2RG) and Silver (CDPVGDVHDMDP2G), so you can choose an adapter that matches your laptop or your color preference.

CDPVDHDMDP2G is backed by a StarTech.com 3-year warranty and free lifetime technical support.



Certifications, Reports and Compatibility



Applications

- Connect to virtually any display while traveling
- Connect your MacBook to a provided VGA, DVI, HDMI or mDP display at work or school
- Connect a secondary VGA, DVI, HDMI or mDP monitor to your Space Gray MacBook

Features

- 4-IN-1 MULTIPOINT USB-C VIDEO ADAPTER: USB-C DP Alt Mode to any one of HDMI 2.0 (4K 60Hz & 7.1ch audio), mDP 1.2 (4K 60Hz & 2ch audio), VGA or DVI (1080p), HDCP 2.2/1.4, Thunderbolt 3 compatible
- TOUGH & PORTABLE: Durable aluminum space gray enclosure with a magnetically-secured hideaway cable wrap for on-the-go users in the office, at home, boardrooms, and classrooms
- COMPATIBILITY: USB-C display adapter for Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface Laptop 3/Surface Book 3, TB3 MacBook Pro/Air, HP EliteBook/Spectre/ZBook, Chromebooks
- TESTED & VERIFIED: USB Type-C adapter tested @ 4K 60Hz mini DisplayPort/HDMI or 1080p VGA/DVI for compatibility w/ TV, monitor & projector brands like Dell, Asus, Acer, LG, Samsung, Sharp, Sony, Epson
- EASY TO USE: Supporting a driverless plug-and-play setup, this adapter is fully compatible with multiple OS platforms: Windows / macOS / Linux / Chrome OS

Hardware	Warranty	3 Years
	Active or Passive Adapter	Active
	Adapter Style	Adapters
	AV Input	USB-C
	AV Output	HDMI - 1.4
		Mini DisplayPort - 1.2
		DVI-I (Digital Only) - Single-Link
		VGA
	Chipset ID	Cypress - CYPD3120 Parade - PS8348 Parade - PS8617 Parade - PS8338 Parade - PS171 Parade - PS176
Performance	Audio Specifications	HDMI - 7.1 Channel Audio DVI - No Audio Support VGA - No Audio Support Mini DisplayPort - 5.1 Channel Audio
	Maximum Analog Resolutions	1920 x 1200 @ 60Hz
	Maximum Cable Distance To Display	15.2 m [49.9 ft]
	Maximum Digital Resolutions	4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz (HDMI) 4096 X 2160 @ 60Hz (mDP)
	MTBF	800,703 hours
	Supported Resolutions	Maximum HDMI output: 4096 X 2160 @ 24Hz or 3840 X 2160 @ 60Hz Maximum mDP output: 4096 X 2160 @ 60Hz Maximum DVI and VGA output: 1920 x 1200 @ 60Hz <i>Lower resolutions and refresh rates may also be supported</i>
	Video Revision	HDMI 2.0 DisplayPort 1.2
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - Mini-DisplayPort (20 pin) Female Output

		1 - VGA (15 pin, High Density D-Sub) Female Output 1 - DVI-I (29 pin) Female Output 1 - HDMI (19 pin) Female Output
Special Notes / Requirements	Note	Only one video output is supported on the video adapter at a time, if multiple connections are made, only one of the outputs will function Maximum Cable Distance to Display refers to digital video. VGA distance capabilities are dependent upon the quality of your cabling
Environmental	Humidity	Storage: 5% ~ 90 % RH (no condensation) Operating: 10% ~ 85 % RH (no condensation)
	Operating Temperature	0°C to 45°C (32°F to 113°F)
	Storage Temperature	-10°C to 70°C (14°F to 158°F)
Physical Characteristics	Cable Length	115 mm [4.5 in]
	Color	Space Gray
	Material	Aluminum
	Product Height	3 cm [1.2 in]
	Product Length	17.5 cm [6.9 in]
	Product Width	14.2 cm [5.6 in]
	Weight of Product	185 g [6.5 oz]
Packaging Information	Package Height	16 mm [0.6 in]
	Package Length	55 mm [2.2 in]
	Package Width	10.5 cm [4.1 in]
	Shipping (Package) Weight	0.1 kg [0.3 lb]
What's in the Box	Included in Package	1 - travel A/V adapter

Product appearance and specifications are subject to change without notice.