

USB 3.2 Gen 2 Type C Hub & Gigabit Ethernet Converter

Part No.: 43385



Description

- Connects a USB 3.2 Type C computer to a Gigabit Ethernet network
- Provides two USB 3.2/3.1 Gen 2 Type A and one Type C port
- USB 3.2/3.1 Gen 2 SuperSpeed data transfer rates up to 10Gbps
- Supports 10/100/1000BASE-T, full and half duplex mode
- 2 year warranty

The Lindy USB 3.2 Gen 2 Hub & Gigabit Ethernet Converter allows users to conveniently connect a laptop, ultrabook or tablet to a Gigabit Ethernet network via a Type C USB port and also provides two additional USB Type A and one USB Type C device ports. As part of the USB 3.2 Gen 2 specification, 10Gbps bandwidth provides lightning fast data transfers between host and mass storage devices. This hub is also backwards compatible with USB 3.2 / 3.1 Gen 1 / USB 3.0 and USB 2.0.

This converter is ideal for ultrabooks or tablets which do not feature wired network connectivity and may only offer a limited number of USB ports. It features USB Type A and Type C interfaces for connecting a wide range of devices.

With its small size and lightweight design this USB 3.2 Hub & Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- Interface: USB Type C to RJ45 & 2x USB Type A & 1x USB Type C
- Interface Standard: USB 3.2 / 3.1 Gen 2, Gigabit LAN
- Supported Bandwidth: 10Gbps (USB), 10/100/1000Mbps (LAN)
- Chipset: RTL8153 (LAN), VL822 (Hub)
- Compatibility: USB Type C equipped computers, Thunderbolt 3/4
- Power Delivery: -
- Special Features: Supports Wake on LAN (WoL)

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x RJ45 (Female), 2 x USB Type A (Female), 1x USB Type C (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 121x23.5x16.5mm (4.76x0.92x0.64in)
- (Fixed) Cable Length: 250mm (9.84in)
- Housing Material: Aluminium, Plastic (side parts)
- Net Weight: 0.052kg (0.11lb)
- Operating Temperature: -25°C - 40°C (77°F -104°F)
- Storage Temperature: -25°C - 85°C (-13°F - 185°F)
- Humidity: 60 - 95% RH (non-condensing)
- Power Requirements: -
- Colour: Dark Grey

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x20x194mm (6.85x0.79x7.64in)
- Gross Weight: 0.06kg (0.13lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, CP65

Package Contents

- USB 3.2 Gen 2 Hub & Gigabit Ethernet Converter
- LINDY Manual

Purchasing information

- No.: 43385
- EAN: 4002888433853

© LINDY 2023