

INFORMATION

32" 4K VA panel with USB-C connection (95W), KVM Switch and PiP/PbP

The ProLite XB3294UHSCP-B1 is a 32 inch 4K monitor designed to give you more space, sharper detail, and smoother workflows.




Its VA panel with Ultra HD resolution and a 3000:1 contrast ratio delivers crisp, vibrant visuals. A brightness of 350cd/m², 2ms response time, and Adaptive Sync ensure everything stays smooth and clear, whether you're creating content or working with data.

USB-C (95W Power Delivery), HDMI, DisplayPort, and a built-in KVM switch make it easy to manage multiple devices while powering your laptop. PiP (Picture-in-Picture) and PbP (Picture-by-Picture) modes let you view content from two sources at the same time for more efficient multitasking.

The three side borderless design helps you stay focused and supports seamless multi-monitor setups. The height adjustable stand, built-in speakers, and headphone jack provide comfort and convenience throughout your day.

Certified with TCO, TÜV-GS and EPEAT Silver, it's a smart, sustainable choice for any modern workspace.




Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.



Mini HDMI, your gateway to versatile media

Pair your monitor to laptop, camera, console, or mini PC. Enjoy high-quality video and audio, expand your creative workflow and take your entertainment anywhere.



Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.



Reduced eye strain & fatigue

Work, study or play longer without eye fatigue, thanks to flicker-free technology and reduced blue light emissions. These features help minimize eye strain and improve visual comfort, allowing you to stay focused and productive throughout the day.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	3-side borderless
Diagonal	31.5", 80cm
Panel	VA
Native resolution	3840 x 2160 @60Hz (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	400 cd/m ²
Static contrast	3000:1
Advanced contrast	80M:1
Response time (GTG)	2ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 8bit+FRC (sRGB: 99%; NTSC: 93%)
Horizontal Sync	30 - 160kHz
Viewable area W x H	708.9 x 405.7mm, 27.9 x 15.9"
Pixel pitch	0.182mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.1) DisplayPort x1 (v.1.2) USB-C x1 (PD 95W)
USB HUB	x4 (2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type-C (5Gbps, 7.5W))
HDCP	yes
Headphone connector	yes

03 FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	i-Style colour
HDR	HDR10
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick: Center: Power/ Menu, Up/ Input Select, Down, Left: i-Style Colour/ ECO/ Blue Light Reducer, Right/ Volume

User controls	picture adjust (brightness, contrast, Eco, ACR, OD, HDR, AdaptiveSync, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.), PiP/PiB (PiP/PiB, sub source, PiP position, PiP size, swap), OSD (position H, position V, OSD time, background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB-C speed), KVM, input select, audio settings (volume, mute, audio input), recall (recall all)
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B

04 MECHANICAL

Display position adjustments	height, swivel, tilt, pivot (rotation both sides)
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.85m), USB (1.5m), HDMI, DP (1.85m), USB-C (1.0m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	55W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY


Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	G
REACH SVHC	above 0.1%: Lead


08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	713.9 x 448.5 (598.5) x 245.5mm
Box dimensions W x H x D	790 x 510 x 143mm
Weight (without box)	8.5kg

Weight (with box) 11.8kg

EAN code 4948570126279





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED