

# USB C Multiport Video Adapter - 4K 60Hz USB-C to HDMI 2.0 or DisplayPort 1.2 Monitor Adapter - USB Type-C 2-in-1 Display Converter HDMI/DP HBR2 HDR - Thunderbolt 3 Compatible

Product ID: CDP2DPHD



This USB-C multiport video adapter offers a portable solution for connecting your USB Type-C laptop to an HDMI or DisplayPort display. The adapter supports High Dynamic Range (HDR) and provides sharper images with enhanced video.

## Two-in-One Video Connectivity with Travel in Mind

Avoid the hassle of carrying different adapters, with a 2-in-1 USB-C monitor adapter. The multiport adapter features both HDMI and DisplayPort outputs, so you can conveniently connect your laptop to any HDMI or DP-equipped display, using this multiport adapter.

The adapter features a durable aluminum enclosure and can withstand being carried in your travel bag.

## **Astonishing 4K Picture Quality and HDR**

The HDMI and DisplayPort outputs on this USB-C video adapter lets you harness the audio and video capabilities that are built into your computer's USB-C connection, delivering the astonishing quality of UHD to your 4K 60Hz display. This makes it easier for you to multitask while working on the most resource-demanding applications imaginable.

With HDR support, you can enjoy lifelike images with increased contrast, brightness and colors and greater luminosity than standard digital imaging.

## **Stylish Connectivity for Your MacBook, MacBook Pro, or Any Laptop**

The USB C display adapter has a Space Gray housing and built-in USB-C cable designed to match your Space Gray MacBook or MacBook Pro. The adapter is compatible with USB-C DP Alt Mode devices.

CDP2DPHD is backed by a 3-year StarTech.com warranty and free lifetime technical support.

*Note: This adapter only supports a single display - you are not able to output DisplayPort and HDMI video simultaneously.*

### Certifications, Reports and Compatibility



### Applications

- Connect to virtually any HDMI and DisplayPort display while traveling or in the office
- Output video to a secondary HDMI or DP monitor
- Stream, view and edit 4K video on your HDMI or DisplayPort display

### Features

- **HIGH PERFORMANCE:** USB C (DP Alt Mode) to HDMI 2.0 4K 60Hz (UHD) w/HDR or DisplayPort 1.2 4K 60Hz HBR2 display adapter on a single monitor w/ 7.1ch audio, compatible w/ HDCP 2.2/1.4 & Thunderbolt 3
- **FLEXIBLE VIDEO OUTPUT:** 2-in-1 portable USB-C multiport video adapter w/ DisplayPort 1.2 or HDMI 2.0, is the perfect video hub for working from a home or office workstations, boardrooms or on the road
- **COMPATIBILITY:** USB C display adapter for devices like Dell XPS/Precision/Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Surface Pro 7/Surface Laptop 3, MacBook Pro/Air, HP Elite/EliteBook/Spectre/ZBook
- **TESTED & VERIFIED:** USB-C adapter tested for peak performance @ 4K 60Hz to ensure compatibility w/ a range of projectors/displays from brands like Samsung, Dell, HP, Lenovo, Asus, Acer, LG, Sharp, Sony
- **EASY TO USE:** USB C (DisplayPort over USB-C) display adapter for any TB3/USB Type-C laptop/tablet & supports driverless plug & play in Windows, macOS, iPadOS, Chrome OS | Works w/ 1080p, HDMI 1.4

<b>Hardware</b>	Warranty	3 Years
	Active or Passive Adapter	Active
	Audio	Yes
	AV Input	USB-C
	AV Output	HDMI - 2.0 DisplayPort - 1.2
	Chipset ID	ITE - IT6563 Parade - PS8338
<b>Performance</b>	Audio Specifications	HDMI - 7.1 Channel Audio DisplayPort - 7.1 Channel Audio
	Maximum Cable Distance To Display	2 m [6.6 ft]
	Supported Resolutions	HDMI: 3840x2160 (4K) / 60Hz DisplayPort: 3840x2160 (4K) / 60Hz Lower resolutions and refresh rates may also be supported
	Video Revision	HDMI 2.0 DisplayPort 1.2
	Wide Screen Supported	Yes
<b>Connector(s)</b>	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - DisplayPort Female Output 1 - HDMI Female Output
	<b>Special Notes / Requirements</b>	<b>Note</b> Your USB-C device must support DP Alt Mode to work with this adapter  This adapter only supports a single display - you are not able to output DisplayPort and HDMI video simultaneously
<b>Environmental</b>	Humidity	5~90% RH (no condensation)
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-10°C to 55°C (14°F to 131°F)
<b>Physical Characteristics</b>	Cable Length	15.2 cm [6 in]
	Color	Space Gray
	Material	Aluminum
	Product Height	15.000
	Product Length	20.5 cm [8.1 in]

	Product Width	62.000
	Weight of Product	48.000
<b>Packaging Information</b>	Package Height	20.000
	Package Length	80.000
	Package Width	173.000
	Shipping (Package) Weight	70.000
<b>What's in the Box</b>	Included in Package	1 - USB-C to DisplayPort and HDMI Adapter

Product appearance and specifications are subject to change without notice.