

3.3 ft. (1 m) HDMI to Mini DisplayPort Cable - 4K 30Hz

Product ID: HD2MDPMM1M



This 3.3 ft. HDMI® to Mini DisplayPortTM cable (male to male) lets you connect an HDMI video source, such as your laptop, desktop, Blu-rayTM player or camera, to a Mini DP monitor or display without the need for additional video cables and adapters.

Astonishing Picture Quality

With support for 4K at 30Hz, you get a sharp, crisp picture that's richer and more true-to-life than traditional HD, with far greater detail. The HDMI to Mini DisplayPort adapter cable delivers UHD content to your mDP display and supports 7.1 channel surround audio.

The video converter is also backward compatible with 1440p and 1080p displays, which makes it a great accessory to for your existing setup at home or in the office.





Clutter-Free Installation

At 3.3 ft. (1 m) in length, this HDMI to mDP cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 6.6 ft. (2 m) adapter cable, enabling you to choose the right cable length for your custom installation needs.

Convenient Connectivity

This active HDMI to Mini DP converter offers plug-and-play installation, providing a hassle-free setup with no software or drivers to install. The adapter cable is powered via a USB port, avoiding the need for external power adapters.

HD2MDPMM1M is backed by a StarTech.com 3-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect your HDMI computer to a Mini DisplayPort monitor
- Ideal for boardroom or office workstations
- View 4K video from your HDMI source on an mDP display

Features

- Reduce clutter with a cable and adapter in-one
- Active HDMI to Mini DisplayPort conversion transmits high-definition audio and video from your computer to a Mini DP monitor
- Delivers astonishing picture quality with support for video resolutions up to Ultra HD 4K
- Provides a convenient plug-and-play solution with no additional adapters required



Data Sheet

Audio Yes AV Input HDMI - 1.4 AV Output Mini-DisplayPort Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications Mini DisplayPort - 7.1 Channel Audio Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature - 10°C to 55°C (14°F to 131°F) Physical Color Black Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 20.000 Package Width 218.000 Shipping (Package) Weight 75.400		Warranty	3 Years
AV Input AV Output Mini-DisplayPort Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications Mini DisplayPort - 7.1 Channel Audio Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature 10°C to 55°C (14°F to 131°F) Physical Characteristics Material Product Height 12.500 Product Length Product Length Veight of Product 67.500 Packaging Information Package Length Package Width Shipping (Package) Weight 75.400	Hardware	Active or Passive Adapter	Active
AV Output Mini-DisplayPort Chipset ID MegaChips Technology - STDP2600 Performance Audio Specifications Mini DisplayPort - 7.1 Channel Audio Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector (s) Connector A 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Height 12.500 Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Height 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Audio	Yes
Performance Audio Specifications Mini DisplayPort - 7.1 Channel Audio Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector(s) Connector A 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature 10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Height 12.500 Product Width 1000.000 Weight of Product 7.500 Packaging Information Package Height 20.000 Package Width 218.000 Package Width 218.000 Shipping (Package) Weight 75.400		AV Input	HDMI - 1.4
Performance Audio Specifications Mini DisplayPort - 7.1 Channel Audio Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector A Connector B 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Product Height 12.500 Product Length Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Height 20.000 Package Width 218.000 Shipping (Package) Weight 75.400		AV Output	Mini-DisplayPort
Supported Resolutions Mini DisplayPort: 3840x2160 (4K) / 30Hz Additional resolutions and refresh rates may be supported Video Revision HDMI 1.4 Wide Screen Supported Yes Connector A Connector B 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Package Height 20.000 Package Length Package Length Package Width 5hipping (Package) Weight 75.400		Chipset ID	MegaChips Technology - STDP2600
Additional resolutions and refresh rates may be supported Video Revision Wide Screen Supported Connector(s) Connector A Connector B 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity S%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Product Height 12.500 Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Height 20.000 Package Width Package Width 5hipping (Package) Weight 75.400	Performance	Audio Specifications	Mini DisplayPort - 7.1 Channel Audio
Connector(s) Connector A Connector B 1 - HDMI Male Input Connector B 1 - Mini DisplayPort Male Output Environmental Humidity Operating Temperature Storage Temperature O°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product Weight of Product Fackage Height 20.000 Package Height 20.000 Package Width Shipping (Package) Weight 75.400		Supported Resolutions	
Connector(s) Connector A Connector B 1 - HDMI Male Input 1 - Mini DisplayPort Male Output Environmental Humidity S%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length Product Width 1000.000 Weight of Product Weight of Product Packaging Information Package Height 20.000 Package Undth Shipping (Package) Weight 75.400		Video Revision	HDMI 1.4
Environmental Humidity Operating Temperature Storage Temperature Physical Characteristics Material Product Height Product Length Product Width Weight of Product Packaging Information Package Length Package Width Shipping (Package) Weight Piow C to 70°C (32°F to 158°F) Storage Temperature 0°C to 70°C (32°F to 158°F) Pow C to 75°C (14°F to 131°F) Black Plastic Plastic Plastic Plastic Plastic Product Length 12.500 Product Length 12.500 Product Width 1000.000 Packaging Information Package Height 20.000 Package Width 218.000 Shipping (Package) Weight 75.400		Wide Screen Supported	Yes
Humidity 5%-90% RH (no condensation) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400	Connector(s)	Connector A	1 - HDMI Male Input
Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 20.000 Package Width 218.000 Shipping (Package) Weight 75.400		Connector B	1 - Mini DisplayPort Male Output
Storage Temperature -10°C to 55°C (14°F to 131°F) Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 20.000 Package Width 218.000 Shipping (Package) Weight 75.400	Environmental	Humidity	5%-90% RH (no condensation)
Physical Characteristics Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Operating Temperature	0°C to 70°C (32°F to 158°F)
Material Plastic Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 20.000 Package Width 218.000 Shipping (Package) Weight 75.400		Storage Temperature	-10°C to 55°C (14°F to 131°F)
Product Height 12.500 Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400	Physical Characteristics	Color	Black
Product Length 2.2 in [5.5 cm] Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Material	Plastic
Product Width 1000.000 Weight of Product 67.500 Packaging Information Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Product Height	12.500
Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Product Length	2.2 in [5.5 cm]
Packaging Information Package Height 20.000 Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Product Width	1000.000
Package Length 200.000 Package Width 218.000 Shipping (Package) Weight 75.400		Weight of Product	67.500
Package Width 218.000 Shipping (Package) Weight 75.400	Packaging Information	Package Height	20.000
Shipping (Package) Weight 75.400		Package Length	200.000
		Package Width	218.000
What's in the Box Included in Package 1 - HDMI to Mini DisplayPort Adapter Cable		Shipping (Package) Weight	75.400
	What's in the Box	Included in Package	1 - HDMI to Mini DisplayPort Adapter Cable

Product appearance and specifications are subject to change without notice.