EB-770F



Drive engagement and communication with an affordable display, up to 150", that will improve productivity in any environment.

Whatever the size of class or meeting room, unrestricted and immersive presentations are possible with this bright, clear, compact and affordable display solution.

The EB-770F's bright, 1080p image, scalable up to 150", is clearly visible from every angle and at a distance, and content can easily be shared or streamed directly from multiple devices for the ultimate collaborative experience.

The EB-770F's ultra short throw lens allows safe, discreet positioning close to the display, enabling presenters free access to perform without casting shadows.

With 4,100 lumens CLO and 3LCD technology, the display is bright and vibrant up to 150", clearly visible from all angles and at a distance. The experience is immersive and user-friendly.

Scalable from 49-150", display sizes can be optimised for each room with one product and a fixed cost, and the EB-770F supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image.

Versatile wired and wireless connectivity options, including Miracast[™] screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room.

Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots at certain angles, and teachers are not subjected to LCD panel direct blue light radiation, believed to damage eyes. Paired with a hygenic, antibacterial whiteboard, teachers can annotate presentations with dry-wipe pens, or to save energy, simply use the whiteboard with the display turned off.

DATASHEET / BROCHURE



























KEY FEATURES

- Scalable FHD display for any room 49-150" UST display for unrestricted viewing (no shadows/reflections)
- Bright and energy efficient laser
 4,100lm CLO with 3LCD technology for brighter colours at only 205W
- Effortless connectivity options
 Auto-on, wired / wireless display with
 USB 2A output for smart sticks
- Simple to use and built to last Virtually maintenance free with 5-year, 12,000hr warranty
- Document camera compatibility
 Create and record a live, totally immersive lesson or presentation





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0,62 inch with C2 Fine

IMAGE

Color Light Output 4.100 Lumen - 2.800 Lumen (economy) In accordance with IDMS15.4

White Light Output 4.100 Lumen - 2.800 Lumen (economy) In accordance with ISO 21118:2020

Resolution 1080p High Definition Full HD Aspect Ratio 16:9

Contrast Ratio Over 2.500.000 : 1

Light source Laser

Laser Light source 20.000 hours Durability High, 30.000 hours Durability Eco

Keystone Correction Manual vertical: ± 3 °, Manual horizontal ± 3 °

Colour Video Processing 10 Bits
2D Vertical Refresh Rate 192 Hz - 240 Hz
Colour Reproduction Upto 1.07 billion colours

OPTICAL

Throw Ratio 0,25 - 0,35:1

Zoom Digital, Factor: 1 - 1,35

Lens Optical

Screen Size 60 inches - 150 inches

Projection Lens F Number 1,6
Projection Lens Focal Length 3,7 mm
Projection Lens Focus Manual
Offset 5:1

CONNECTIVITY

Interfaces USB 2.0-A (2x), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE

802.11a/b/g/n/ac, VGA in (2x), VGA out, HDMI in (3x), Composite in, Miracast, Jack plug out,

Jack plug in (3x), USB 2.0 Type B (Service Only), Wi-Fi Direct, Microphone input

Epson iProjection App Ad-Hoc / Infrastructure

Network Protocol HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock,

Wireless LAN security, Password protection

Other features 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built-

in speaker, CEC compatible, Customizable user logo, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, JPEG Viewer, Long light source life, Network projection, OSD copy function, PC Free, Point correction, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Ultra-wide display (16:6), Web

Control, Web Remote, Wireless LAN capable, iProjection App

Video Color Modes Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection

Projector control via: Crestron Integrated Partner, Crestron RoomView, Extron IP Link, AMX Device Discovery,

Control4 Simple Device Discovery Protocol

EB-770F

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries





PRODUCT SPECIFICATIONS

EB-770F

GENERAL

Heat Dissipation 895 BTU/hour (max)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 356 x 395 x 133 mm (Width x Depth x Height)

Product weight 5,9 kg

Noise Level Normal: 37 dB (A) - Economy: 27 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance

Included Software Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager,

Epson Projector Management

Options Air filter, Ceiling mount, Connection and control box, External Speaker, Safety wire set,

Visualiser camera, WP System - ELPWP10, Wall mount, Wireless LAN unit, Wireless

transmitter - ELPWT01

Loudspeaker 16 Watt

Room Type / Application Boardroom, Home Office, Meeting room / Classroom, Signage / Retail, Visitor Attraction

Positioning Ceiling Mounted, Desktop, Table Mounted, Wall Mounted

Colour White

OTHER

Warranty 60 months Carry in or 12.000 h

Optional warranty extension available



OPTIONAL ACCESSORIES

- Active Speakers (2 x 15W) ELPSP02 V12H467040
- Wall Mount ELPMB62 EB-7xx / EB-8xx V12HA06A06
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Air Filter ELPAF60 EB-7XX / EB-L2xx Series V13H134A60
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Control and Connection Box ELPCB03 V12H927040
- Safety Wire ELPWR01 V12H003W01

LOGISTICS INFORMATION

SKU	V11HA79080
EAN code	8715946715841
Country of Origin	Philippines
Layer	2 Units



Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch



EB-770F