

DATASHEET

Power Cable CEE7/7 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm²



General data

10 A / 250 V VDE tested
Suitable for Germany, Belgium, France and further

Allgemeine Daten

Number of cores	3
Colour outer sheath	black
With cord switch	True
Material outer sheath	Polyvinyl chloride (PVC)
Spiralized cable	True
Halogen free	False

Mechanische Eigenschaften

Connection 1	Socket outlet with protective contact, straight
Connection 2	Cold device plug straight, female

Kabelmantel

Temperature resistance	0 - 70 °C
Oil resistant (according to EN 60811-404)	False

Elektrische Eigenschaften

Protective conductor	True
Nominal voltage	250 V

This datasheet was created automatically on 31-08-2023 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm²

Normen, Zulassungen, Zertifizierungen

Oil resistant (acc. EN 60811-2-1)	True
-----------------------------------	------

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length Leiternennquerschnitt Außendurchmesser ca.		
EK508SW.0,5	Power Cable CEE7/7 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	0.5 m	0,75 mm ²	6,8 mm
EK508SW.2	Power Cable CEE7/7 180° - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	2.0 m	0,75 mm ²	6,8 mm
EK508SW.3	Power Cable CEE7/7 180° - C13 180°, Black, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	1,00 mm ²	7,1 mm
EK508SW.5	Power Cable CEE7/7 180° - C13 180°, Black, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	1,00 mm ²	7,1 mm

This datasheet was created automatically on 31-08-2023 . Technical changes reserved.

