

240W 6 Port USB Type C & A GaN Charger with Display

No.: 73450

High-performance charging station with 6 USB ports

Description

- Charge up to 6 devices simultaneously, including laptops, tablets, smartphones and gaming consoles
- Featuring Power Delivery 3.2 with Extended Power Range (EPR), a single USB-C port can deliver up to 140W, making it ideal for high-performance laptops
- Utilising cutting-edge GaN (Gallium Nitride) technology, this charger provides maximum power in a compact, energy-efficient design, with reduced heat
- Stay in control with the integrated LCD display, offering real-time insights into charging status, power distribution, and performance across each port
- 2 year warranty

Experience next-generation charging with the Lindy 240W GaN Charger - engineered to deliver exceptional power, efficiency, and convenience in a compact design. Ideal for home and office, this high-performance charger keeps all your essential devices powered from a single solution.

The Lindy 240W GaN Charger is your all-in-one power solution, designed to keep every device charged. Built with cutting-edge GaN technology, this compact powerhouse delivers exceptional performance without the bulk. Whether you're powering a high-performance laptop, topping up your smartphone, or charging multiple devices at once, the Lindy 240W charger does it all-efficiently, intelligently, and reliably.

With 4 USB-C ports and 2 USB-A ports, you can charge up to 6 devices simultaneously. From laptops and tablets to phones, cameras, and gaming gear - everything stays powered from a single, streamlined solution. A single USB-C port delivers up to 140W (PD 3.2 EPR) - perfect for demanding laptops and high-performance devices. No waiting, no slowing down-just fast, consistent charging.

Intelligent Power That Adapts to You
The charger automatically adjusts power output in real time, ensuring each connected device receives exactly what it needs.

The integrated LCD display gives you live insights into charging speed and power distribution across each port, so you are always in control.

Smarter Charging with PPS
With advanced PPS technology, the charger fine-tunes voltage and current continuously to:
- Maximise efficiency
- Reduce heat

- Protect battery health
- Extend device lifespan

With integrated protection against overvoltage, overcurrent, and short circuits, your devices are always in safe hands.

The Smart Choice for Modern Power Needs
If you want fewer chargers, faster performance, and smarter energy management, the Lindy 240W GaN Charger is the upgrade your setup deserves.

Power more. Carry less. Charge without limits.

Technical details

Connectors
- Input: IEC C7
- Output: 4 x USB Type C (Female), 2 x USB Type A (Female)

Specifications
- Power Input: 110-240V~50/60Hz 2.5A (max.)
- Power Output: max. 240W in total

Single Port Output Mode:
- USB-C1/USB-C2: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A (max. 140W)
- USB-C3/USB-C4: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (max. 100W)
- USB-A1/USB-A2: 4.5V/5A, 5V/4.5A, 9V/3A, 12V/2.5A, 20V/1.5A (max. 30W)
- PPS: 5V-20V, 5A

Combined Output Mode
- 2 ports in use: up to max. 240W
- 3 ports in use: up to max. 235W
- 4 ports in use: up to max. 240W
- 5 ports in use: up to max. 238W
- 6 ports in use: up to max. 229W

Supported Output Protocols:
- Type C1: UFCS33W, QC 3+, FCP, SCP, AFC, TFCP, PD3.2 140W (PPS, AVS, QC5), DCP, Apple 2.4A
- Type C2: UFCS33W, QC 3+, FCP, SCP, AFC, TFCP, PD3.2 140W (PPS, AVS, QC5), DCP, Apple 2.4A
- Type C3: QC3+, FCP, SCP, AFC, SFCP, PD3.0 100W (PPS, QC5), DCP/BC 1.2, SAM2A, Apple 2.4A
- Type C4: QC3+, FCP, SCP, AFC, SFCP, PD3.0 100W (PPS, QC5), DCP/BC 1.2, SAM2A, Apple 2.4A
- USB-A1: QC 2.0/3.0, SAM2A, AFC, FCP, SCP, DCP/BC 1.2, Apple 2.4A
- USB-A2: QC 2.0/3.0, SAM2A, AFC, FCP, SCP, DCP/BC 1.2, Apple 2.4A

Max. Total Power: 240W
Output Voltage Accuracy: ±5%
Average Active Efficiency: 88.23%
Efficiency at Low Load (10%): 74.24%
No-load Power Consumption: 287mW
Additional Features: Overcurrent, overvoltage and short-circuit protection

Physical Properties
- Dimensions (approx.) WxDxH: 95x95x94.88mm (3.74x3.74x3.74in)
- Housing Material: Plastic
- Net Weight: 0.45kg (0.99lb)
- Operating Temperature: -10°C - 35°C (14°F - 95°F)
- Operating Humidity: 60% RH (non-condensing)
- Storage Temperature: -20°C - 80°C (-4°F - 176°F)
- Storage Humidity: 5-90% RH (non-condensing)
- Colour: Anthracite

Miscellaneous
- Packaging Type: Carton Box
- Packaging Dimension: 13.8x17.1x5.2mm (0.54x0.67x0.2in)
- Gross Weight: 0.7kg (1.54lb)
- Warranty (Years): 2
- Product Compliance: UKCA, CE, RoHS, REACH, ErP

Package Contents
- 240W 6 Port USB Type C & A GaN Charger
- Country specific power cables (EU & UK to IEC C7)
- Lindy Manual

Purchasing Information

No.: 73450

EAN: 4002888734509

© LINDY 2026