

Product datasheet

Specifications



APC Smart-UPS Ultra, 2200VA 230V 1U, with Lithium-Ion Battery, with Network Management Card Embedded

SRTL2K2RM1UINC

Overview

Lead time

Main

Main Input Voltage 230 V AC

Other Input Voltage 230 V

Main Output Voltage 230 V AC

Other Output Voltage 230 V

Rated power in W 2200 W

Rated power in VA 2200 VA

Input Connection Type BS1363A British

Output connection type 3 IEC 320 C13

Number of rack unit 1U

Number of cables 1

Battery type Li-Ion (Lithium-Ion)

Provided equipment RJ45 cable

Batteries & Runtime

Battery recharge time 1.5 h

Number of battery replacement quantity 1

Battery voltage 50 V

Battery charger power 448 W rated

Battery design life 8...10 year(s)

Battery power in VAh 336 VAh runtime

Battery option SRTL50RMBP1U-LI 1 1240 VAh

Extended runtime 1

General

Product web sub-family High density

Redundant No

Physical

Colour	Silver grey
Height	43 mm
Width	432 mm
Depth	560 mm
Net weight	15.9 kg
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	1
USB compatible	Yes
Mounting position	Horizontal Vertical

Input

Network frequency	50/60 Hz auto-sensing
Input voltage limits	160...275 V adjustable 220...240 V AC

Output

Maximum configurable power in W	2200 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	On-Line
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	2200 VA

Conformance

Product certifications	CE
Marking	CE Mark
Standards	EN/IEC 62040-1

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

Communications & Management

Preinstalled device	Network management card with environmental monitoring
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.82 cm
Package 1 Width	56.4 cm
Package 1 Length	76.4 cm
Package 1 Weight	24.18 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)