

Overview

We've got you covered

Keep the conversation going whenever, wherever in the office. Built for on-site employees the Poly Rove 20 wireless DECT $^{\text{TM}}$ IP phone solution delivers the freedom to move and the flexibility to scale as you grow.

Clarity meets function

Designed for busy professionals, Poly Rove 20 handsets emphasize usability, functionality, and style. Enjoy HD voice for lifelike conversations, customizable line keys, and effortless call parking.

You grow, we scale

You shouldn't have to worry about outgrowing your communication solution or feel held back by its options. Poly Rove 20 wireless DECT ™ IP phone solution has the flexibility to scale with handsets, bases, and repeaters as you grow.

Features

Privacy is ensured

Conversations are safe and secure with DECT ™ wireless security. And it doesn't stop there - maintain DECT ™ encryption even when you add a base or repeater to your solution.

Extended battery life

Enable employees on the move to communicate more effectively, respond faster to requests and alerts, and be more productive with up to 35 hours of talk time (Eco-mode) and up to 300 hours of standby time.

Grab a Poly headset and go

Communicate hands-free with a Poly wired headset using the dedicated 3.5 mm connection. Perfect for users who feel more comfortable wearing a headset. [1]

Easy-to-clean handsets

Ideal for healthcare environments, these handsets are specifically designed for easy cleaning with smooth surfaces and no gaps between buttons.

Pro-grade features

Single-cell DECT ™ handset with 4-line keys and easy call park functionality. Push-to-talk for inter-handset communication. And with the 2" TFT color LCD with backlight users will see productivity soar.

HD audio quality

HD voice enables more natural conversations to enhance productivity. Voices stay in the forefront – background noise suppression lets people on both sides of the call focus on the person speaking, not their surroundings.

[1] Poly wired headset sold separately.

Specifications

Display size (diagonal)	5.1 cm (2")
Display size (diagonal)	2"
Panel technology	Color TFT LCD
Audio	Full-duplex handsfree speakerphone with acoustic echo cancellation and background noise suppression
Dimensions (W x D x H)	55.2 x 127 x 26.3 mm
Dimensions (W x D x H)	2.2 x 5 x 1 in
Weight	162 g
Weight	0.36 lb
Package dimensions (W x D x H)	180 x 92.2 x 61 mm
Package weight	300 g
Battery life	Up to 35 hours (talk time) using Eco mode; Up to 300 hours (standby time)
Energy star certified	ENERGY STAR® certified
Security management	DECT™ security certified
UPC number	(ABA) 197497473193; (ABB) 197497473186; (ABG) 197497473179; (ABJ) 197497776973; (ABU) 197497473162; (UUF) 197497473155
Manufacturer Warranty	Poly standard one-year limited warranty
What's in the box	Safety information sheet; Handset; Quick start guide; AC power adapter; Charging cradle; Belt clip; Battery

Additional specifications

Audio codecs	G.165, 168 echo cancellation	
Battery type	Rechargeable Li-ion	
Cartons per layer	8	
Cartons per pallet	64	
Certifications and compliances	UL 62368-1	
Certified collaboration software	Zoom; Microsoft (OpenSIP gateway)	
Color	Black	
DECT frequency	1920 to 1930 MHz (US) Auto configures frequencies to base station	
Datasheet photo 1	AHID/343b45863a7b93e5285195eabdc2cecceb8e5719	
Display features	Adjustable font size selection (regular, medium, large)	
ECCN	EAR99	
HTS code	8517140080	
Headset and handset compatibility	Compliant with ADA Section 508 Subpart B 1194.23 (all); 3.5 mm headset port	
Headset ports	3.5 mm headset jack	
Management Software	Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management	
Master carton dimension (imperial)	9.64 x 17.32 x 11.61 in	
Master carton dimension (metric)	24.5 x 44 x 29.5 cm	
Master carton weight (imperial)	12.84 lb	
Master carton weight (metric)	5.82 kg	
Multiple order quantity	20	
Native resolution	128 x 160	
Network protocols, supported	Manual or dynamic host configuration protocol (DHCP) network setup; Time and date synchronization using SNTP	
Operating humidity range	5 to 95%	
Operating temperature range	-10 to 55℃	
Operating temperature range	14 to 131°F	
Package dimensions (W \times D \times H)	7.48 x 8.26 x 2.16 in	
Package weight	0.66 lb	
Pallet (layers)	8	
Pallet dimensions	40 x 48 x 58.66 in	
Pallet dimensions (W \times D \times H)	101.6 x 121.9 x 149 cm	
Pallet weight	787.05 lb	

Pallet weight	357 kg	
Power	External universal AC adapter: 5V 1A DC (model-specific plugs)	
Products per pallet	1280	
Products per pallet layer	160	
Storage temperature range	-40 to 70°C	
Storage temperature range	-40 to 158°F	
Telephony and call handling features	Up to 2 call appearances	
UNSPSC code	43191606	
VoIP features	Up to Twenty (10) lines per Handset service subscription profile assignments (SP 1 $-$ 20)	
Wireless range	Up to 50 m indoor	
Wireless range (imperial)	Up to 165 ft indoor	

Services

Communication & Collaboration

Poly Support Services

3 Year Poly+ Rove 20 Dect IP Phone Handset	P88090312 ★
1 Year Partner Poly+ Rove 20 Dect IP Phone Handset	P88090160
1 Year Poly+ Rove 20 Dect IP Phone Handset	P88090112
3 Year Partner Poly+ Rove 20 Dect IP Phone Handset	P88090362
5 Year Next Business Day HW Replacement Rove 20 Dect IP Phone Handset HSP Only	D88090DS5

★: Recommended

Disclaimer — Copyright

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Nov 14, 2025 7:36 AM UTC+0000