Brodit
DEVICE MOUNTING SOLUTIONS



Holder with key-lock

Active holder with cig-plug and tilt swivel. Fits for devices with original skin. 2 keys included. With Easy-switching system. With AMPS, VESA 75 holes.

Item no: 735386
EAN Number: 7320287353860

Use an active holder for your Galaxy Tab Active and you will always have a freshly charged battery! The holder provides a neat and comfortable installation - safe and convenient. The holder is equipped with a cig-plug for connection to the vehicle's 12/24 Volt socket. 2,7A charging. Charging via pogo plug.

The holder with lock is to be used when you want to have your tablet safely locked in place and still easy accessible, for example in shops, exhibitions, events, trucks, boats etc. The holder has a built-in lock, in order to take the device out from the holder you need a key (2 keys included).

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden.

Easy-switching system:
The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time! When upgrading to a new device, you do not longer need to make a full installation. Same goes for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

Choose installation placement with care, devices must not be placed in positions where they may block the view or important controls. The cradle should only be attached onto a suitable place. Installations always take place at the customer's own discretion and responsibility.

Fits the following models:
Samsung Galaxy Tab Active 3 SM-T570/SM-T575
Samsung Galaxy Tab Active 5 SM-X300/SM-X306B

For a complete list, see
www.brodit.com/en/product/735386

Measurements:
Height 187 mm
Width 247 mm
Depth 62 mm
Volume 2864 cm³
Weight 456 g

Charging specifications:
- Input voltage: 10V-30V
- Charging voltage: 5.4V
- Output current (Typ): 2.7A
- Rated power: 15W
- Input & output protection: Input Reverse Voltage Protection , OVP , OCP
- LED charging indicator: Red
- DC-DC Conversion Efficiency:
- Operating temperature: 0°C~50 °C
- Storage temperature: -20°C~ +60 °C
- Made of material: ABS
- Approvals: CE, E-mark, FCC, RoHS