

1m (3 ft.) USB-C to HDMI Cable - 4K at 60Hz - Black

Product ID: CDP2HD1MBNL



This USB- C^{TM} to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type- C^{TM} device to your HDMI monitor, television, or projector. The adapter offers a connection distance of up to 1 m (3 ft.) and works with USB-C devices that support DP Alt Mode, such as the MacBook, Chromebook PixelTM and DellTM XPSTM models 15 and 13. It's also compatible with ThunderboltTM 3 ports.

Clutter-free installation

At 1 m (3 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation.

For longer installations, StarTech.com also offers a 2 m (6 ft.) USB-C to HDMI cable (CDP2HD2MBNL) and a 3 m (10 ft.) USB-C to HDMI cable (CDP2HD3MBNL), enabling you to choose the right cable length for your custom installation needs.





Astonishing picture quality

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K 60Hz monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection, to deliver the astonishing quality of Ultra HD to your 4K display.

Plus, the adapter is still compatible with lower display resolutions, such as 1080p, which makes it a great accessory for your current home, office or other HD work environment, while future-proofing for 4K 60Hz implementation.

The CDP2HD1MBNL is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

Features

- Reduce clutter with a 1 m (3 ft.) all-in-one solution with a combined cable and adapter
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for resolutions up to 4K at 60Hz



Data Sheet

	Warranty	3 Years
Hardware	Adapter Style	Cable Adapters
	AV Input	USB Type-C
	AV Output	HDMI
	Chipset ID	VIA/VLI - VL100 Parade - PS176
	Ports	1
Performance	Audio Specifications	7.1 surround sound
	Maximum Digital Resolutions	3840x2160 @ 60 Hz
	Supported Resolutions	1024x768 1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p) 1920x1200 2560x1440 2560x1600 3840x2160 (Ultra HD 4K)
	Wide Screen Supported	Yes
Connector(s)	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode Male Input
	Connector B	1 - HDMI (19 pin) Male Output
		Value IICD Carata and Disala Data and IICD CAD
Special Notes / Requirements	Note	Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.
	Note Humidity	
Requirements		Alt mode) in order to work with this adapter.
Requirements	Humidity	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation)
Requirements	Humidity Operating Temperature	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F)
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m] Black
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m] Black 0.6 in [14 mm]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m] Black 0.6 in [14 mm] 39.4 in [1000 mm]
Requirements Environmental Physical	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Weight	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m] Black 0.6 in [14 mm] 39.4 in [1000 mm] 1.3 oz [36 g]
Requirements Environmental Physical Characteristics Packaging	Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Weight Product Width	Alt mode) in order to work with this adapter. 5%-90% RH (no condensation) 0°C to 45°C (32°F to 113°F) -10°C to 70°C (14°F to 158°F) 3.3 ft [1 m] Black 0.6 in [14 mm] 39.4 in [1000 mm] 1.3 oz [36 g] 0.9 in [22 mm]

Product appearance and specifications are subject to change without notice.