

Product datasheet

Specifications



Rack PDU, Switched, Zero U, 10A, 230V, (16) C13

AP7950B

Overview

Lead time

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit User manual

Physical

Colour	Black
Height	124.5 cm
Width	5.6 cm
Depth	4.4 cm
Net weight	4.32 kg
Mounting location	Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Permissible voltage	200...240 V
Max line current	10 A
Input current limits	10 A
Load capacity	2300 VA
Network frequency	47...63 Hz

Output

Number of power socket outlets 16 IEC 60320 C13

Conformance

Product certifications	CE GOST IRAM VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	5.23 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)