

Rittal – The System.

Faster – better – everywhere.

Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.735

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.735

created: 07.12.2020 on www.rittal.com/com-en



Product description

| | |
|--|---|
| Design: | Pre-configured |
| Description: | Wall-mounted enclosure with optimum accessibility due to hinged part. |
| Material: | Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm |
| Surface finish: | Powder-coated |
| Colour: | Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey) |
| Protection category IP to IEC 60 529: | IP 54 in conjunction with solid gland plate, top and bottom |
| IK Code: | IK08 |
| Supply includes: | Wall section with solid gland plate at the top and brush strip at the bottom, two vertical mounting rails and C rail, horizontal, for cable clamping Hinged part with 25 mm pitch pattern of holes in the front and rear frame, two 482.6 mm (19") mounting angles at the front, infinitely depth-variable, and side outlet filters on the left and right Earth rail with star earthing Designer glazed door 1 double-kit key no. 5 Wall mounting bracket, 10 mm Mini-comfort handle for lock inserts Security lock 3524 E |
| Basic material: | Sheet steel |

Product features

Dimensions: Width: 600 mm
Height: 478 mm
Units: 9 U
Depth: 573 mm

Depth hinged part: 416 mm

Installation depth: 520 mm

Clearances: Clearance width: 502 mm
Clearance height: 415 mm

Wall section: Depth: 135 mm

Load capacity: Hinged part, static (max.): 450 N

Packs of: 1 pc(s).

Weight/pack: 35 kg

EAN: 4028177324237

Customs tariff number: 94032080

ETIM 7.0: EC000261

ETIM 6.0: EC000261

eCl@ss 8.0/8.1: 27142408

eCl@ss 6.0/6.1: 27180208

Product description: DK Wall-mounted enclosures, 3-part, WHD: 600x478x573 mm, 9 U, Pre-configured, with mounting angles, depth-variable

Approvals

Approvals: UL + C-UL

Certificates: EAC
IK-Code
Protection category

Declarations: Declaration of conformity