

Product datasheet

Specifications



Rack PDU, Basic, Zero U, 22kW, 400V, (6) C19 & (3) C13

AP7555A

Overview

Lead time Usually in Stock

Main

Main Input Voltage 400 V 3 phases

Main Output Voltage 230 V

Input Connection Type IEC 60309 32 A 3P + N + PE

Number of rack unit 0U

Cable length 1.83 m

Number of cables 1

Provided equipment Installation guide
Toolless mounting kit

Physical

Colour Black

Height 92.7 cm

Width 5.5 cm

Depth 8.8 cm

Net weight 4.76 kg

Mounting location Side

Mounting preference No preference

Mounting mode Rack-mounted

Input

Permissible voltage 200...250 V

Max line current 32 A

Load capacity 22000 VA

Network frequency 47...63 Hz

Output

Number of power socket outlets 3 IEC 60320 C13
6 IEC 60320 C19

Conformance

Product certifications	CE GOST VDE
------------------------	-------------------

Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	106.7 cm
Package 1 Width	29.8 cm
Package 1 Length	8.3 cm
Package 1 Weight	6.247 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------