

# Product data sheet

Specifications



## APC Performance SurgeArrest 8 (1 PLC Compatible) outlets with Phone and Coax Protection 230V Germany

PL8VT3-DE

### Overview

Lead time

### Main

|                       |   |
|-----------------------|---|
| Main Input Voltage    | 230 V   |
| Input Connection Type | Schuko CEE 7/7P                                 |
| Cable length          | 2.44 m  |
| Number of cables      | 1   |
| Provided equipment    | Coaxial cable<br>Telephone cable<br>User manual |

### Physical

|                     |                    |
|---------------------|--------------------|
| Colour              | Black              |
| Height              | 37.2 cm            |
| Width               | 12.2 cm            |
| Depth               | 4.2 cm             |
| Net weight          | 1.23 kg            |
| Mounting preference | No preference      |
| Mounting mode       | Not rack-mountable |

### Input

|                            |          |
|----------------------------|----------|
| Network frequency          | 50/60 Hz |
| Maximum input current      | 10 A     |
| Switching current capacity | 10 A     |

### Output

|                                |              |
|--------------------------------|--------------|
| Number of power socket outlets | 8            |
| Outlet standard                | Schuko CEE 7 |

### Conformance

|                        |    |
|------------------------|----|
| Product certifications | CE |
|------------------------|----|

Equipment protection policy Lifetime : 100000 euros

## Environmental

|                                       |                   |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...40 °C         |
| Relative humidity                     | 0...95 %          |
| Operating altitude                    | 0...10000 ft      |
| Ambient air temperature for storage   | -40...85 °C       |
| Storage Relative Humidity             | 0...95 %          |
| Storage altitude                      | 0.00...15240.00 m |

## Surge Protection and Filtering

|                       |  |
|-----------------------|--|
| Response time         | 1 ns common mode                           |
| Common mode rejection | 70 dB                                      |
| Peak current          | 37.5 kA common mode<br>37.5 kA normal mode |
| Surge energy rate     | 2500 J                                     |

## Packing Units

|                              |                |
|------------------------------|----------------|
| Unit Type of Package 1       | PCE            |
| Number of Units in Package 1 | 1              |
| Package 1 Height             | 38.1 cm        |
| Package 1 Width              | 5.1 cm         |
| Package 1 Length             | 21.6 cm        |
| Package 1 Weight             | 1.32 kg        |
| Number of Units in Package 2 | 12             |
| Package 2 Height             | 381.00 mm      |
| Package 2 Width              | 228.60 mm      |
| Package 2 Length             | 685.80 mm      |
| SCC14                        | 10731304281396 |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |  |
|----------|--|
| Warranty | Limited Lifetime (European Union countries only) |
|----------|--|

**Recommended replacement(s)**