



LANCOM 1926VAG-5G

High-end router for powerful SD-WAN with 5G and two VDSL Super Vectoring modems and/or a G.fast modem

This high-end router supports the high-performance 5G cellular standard. It guarantees the highest availability and the best bandwidths on every line: Be it with 5G as the primary access, in active/active mode with VDSL Super Vectoring, or via G.fast. State-of-the-art SD-WAN technology for secure, automated VPN site connectivity and the advantage of 5G technology, the LANCOM 1926VAG-5G is the top-class solution for mission-critical applications in medium-sized and large branch infrastructures.

- Two integrated VDSL Super Vectoring modems (operable in parallel), alternative use of a modem at a G.fast connection, 1x SFP/TP, 1x WAN Ethernet and 5G offering high performance
- Low latencies and high bandwidth for real-time applications thanks to integrated 5G modem(4K/8K video streaming, telephony or AR)
- Mobile primary operation or in parallel with other access technologies
- Load balancing for the active/active operation of several Internet access connections and maximization of the available bandwidth.
- 25 simultaneous IPsec VPN connections (100 optional)
- Network virtualization with up to 64 networks on one device (ARF)
- SD-WAN – automatic VPN and VLAN configuration via the LANCOM Management Cloud
- 2x ISDN S0, 4x analog (internal) / fax
- Professional telephony features thanks to integrated LANCOM VCM (Voice Call Manager) / SBC (session border controller)
- Full-metal housing for mounting in a 19" rack and integrated 230V power supply

LANCOM 1926VAG-5G

Full future viability with 5G

As the primary connection when on the move, or in active/active mode with other access technologies, the LANCOM 1926VAG-5G provides all of the advantages of 5G technology, such as the low-latency and high-performance use of real-time applications such as telephony, video chat, video streaming in 4K or 8K, or augmented reality—especially where there is a high density of users. The backwards compatible 5G module works seamlessly with the 4G LTE network and thus guarantees maximum future viability.

Multi-WAN & backup

The LANCOM 1926 series are the first routers on the market with two integrated VDSL Super Vectoring modems for a total of 2x 300 Mbps. Alternatively, one of the two modems can be used to connect via G.fast at up to 1,000 Mbps. Also, their SFP port allows them to operate directly at high-speed fiber-optic connections. They can also operate with any external DSL or cable modem via WAN Ethernet. The 5G modem integrated into the LANCOM 1926VAG-5G ensures high-performance cellular access. It is ideally suited for intelligent backup scenarios in 4G and at the same time offers future viability for 5G.

Active/active (load balancing)

The LANCOM 1926VAG-5G allows multiple Internet access connections to be operated in parallel, with load balancing to ensure that the available bandwidth is used to maximum effect. With the combined operation of 5G, 2x VDSL Super Vectoring, and fiber optic, it provides unsurpassed availability and bandwidth. The LANCOM 1926VAG-5G thus offers the ultimate in future proofing for performance-hungry SD-WAN scenarios in mission-critical environments.

Awarding-winning LANCOM VPN

The LANCOM 1926VAG-5G offers high levels of security. The standard equipment of 25 IPsec VPN channels guarantees strong encryption, secure connections for mobile employees, and protection of corporate data. The LANCOM VPN option upgrades the router to support up to 100 VPN channels.

Radically simplified configuration with LANCOM SD-WAN

In combination with the LANCOM Management Cloud, the LANCOM 1926VAG-5G opens the way for automated management. The software-defined WAN (SD-WAN) enables the automatic setup of secure VPN connections between sites, including network virtualization and backup across the wide-area network: A few mouse clicks is all it takes to enable the VPN function and select the required VLANs for each site. The laborious configuration of individual tunnel endpoints is no longer necessary.

Professional telephony with the LANCOM VCM (Voice Call Manager)

The LANCOM Voice Call Manager is already integrated into the LANCOM 1926VAG-5G and provides a wide range of telephony functions. It manages all aspects of the telephony and controls all of the router-based PBX functions for SIP, ISDN and analog components. Furthermore, it enables the easy integration of DECT telephones by auto provisioning with the LANCOM DECT 510 IP base station.

LANCOM 1926VAG-5G

LCOS 10.50

Layer 2 features	
VLAN	4.096 IDs based on IEEE 802.1q, dynamic assignment, Q-in-Q tagging
Multicast	IGMP-Snooping, MLD-Snooping
Protocols	Ethernet over GRE-Tunnel (EoGRE), L2TPv3, ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP, LACP
Layer 3 features	
Firewall	Stateful inspection firewall including paket filtering, extended port forwarding, N:N IP address mapping, paket tagging, support for DNS targets, user-defined rules and notifications
Quality of Service	Traffic shaping, bandwidth reservation, DiffServ/TOS, packetsize control, layer-2-in-layer-3 tagging
Security	Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button
PPP authentication mechanisms	PAP, CHAP, MS-CHAP, and MS-CHAPv2
High availability / redundancy	VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup
Router	IPv4-, IPv6-, NetBIOS/IP multiprotokoll router, IPv4/IPv6 dual stack
SD-WAN Application Routing	SD-WAN Application Routing in connection with the LANCOM Management Cloud
SD-WAN dynamic path selection	SD-WAN dynamic path selection in connection with the LANCOM Management Cloud
Router virtualization	ARF (Advanced Routing and Forwarding) up to separate processing of 64 contexts
IPv4 services	HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NetBIOS/IP proxy, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS
IPv6 services	HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS
Dynamic routing protocols	RIPv2, BGPv4, OSPFv2, LISP (Locator/ID Separation Protocol)
IPv4 protocols	DNS, HTTP, HTTPS, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3
IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, BGP, LISP, Syslog, SNMPv1,v2c,v3, MLDv2, PIM, NPTv6 (NAT66)
Multicast Routing	PIM (Protocol Independent Multicast), IGMP proxy, MLD proxy
WAN operating mode	VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port
WAN protocols	PPPoE, Multi-PPPoE, ML-PPP, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire and IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static)
Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd (static and over DHCP), Dual Stack Lite (IPv4-in-IPv6-Tunnel), 464XLAT
Security	
Intrusion Prevention	Monitoring and blocking of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
URL blocker	Filtering of unwanted URLs based on DNS hitlists and wildcard filters. Extended functionality with Content Filter Option
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP traps and SYSLOG
Authentication mechanisms	PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanism
Adjustable reset button	Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot'

LANCOM 1926VAG-5G

LCOS 10.50

High availability / redundancy	
VRRP	VRRP (Virtual Router Redundancy Protocol) for backup in case of failure of a device or remote station.
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
Load balancing	Static and dynamic load balancing over up to 4 WAN connections (incl. client binding). Channel bundling with Multilink PPP (if supported by network operator)
VPN redundancy	Backup of VPN connections across different hierarchy levels, e.g. in case of failure of a central VPN concentrator and re-routing to multiple distributed remote sites. Any number of VPN remote sites can be defined (the tunnel limit applies only to active connections). Up to 32 alternative remote stations, each with its own routing tag, can be defined per VPN connection. Automatic selection may be sequential, or dependant on the last connection, or random (VPN load balancing)
Line monitoring	Line monitoring with LCP echo monitoring, dead-peer detection and up to 4 addresses for end-to-end monitoring with ICMP polling
VPN	
IPSec over HTTPS	Enables IPSec VPN based on TCP (at port 443 like HTTPS) which can go through firewalls in networks where e. g. port 500 for IKE is blocked. Suitable for client-to-site connections and site-to-site connections. IPSec over HTTPS is based on the NCP VPN Path Finder technology
Number of VPN tunnels	25 tunnels active simultaneously (50 / 100 with VPN-50 / VPN-100 Option) when combining IPSec with PPTP (MPPE) and L2TPv2 tunnels, unlimited configurable connections. Configuration of all remote sites via one configuration entry when using the RAS user template or Proadaptive VPN.
Hardware accelerator	Integrated hardware accelerator for 3DES/AES encryption and decryption
Realtime clock	Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case
Random number generator	Generates real random numbers in hardware, e. g. for improved key generation for certificates immediately after switching-on
1-Click-VPN Client assistant	One click function in LANconfig to create VPN client connections, incl. automatic profile creation for the LANCOM Advanced VPN Client
1-Click-VPN Site-to-Site	Creation of VPN connections between LANCOM routers via drag and drop in LANconfig
IKE, IKEv2	IPSec key exchange with Preshared Key or certificate (RSA signature, ECDSA-Signature, digital signature)
Smart Certificate	Convenient generation of digital X.509 certificates via an own certification authority (SCEP-CA) on the webpage or via SCEP.
Certificates	X.509 digital multi-level certificate support, compatible with Microsoft Server / Enterprise Server and OpenSSL. Secure Key Storage protects a private key (PKCS#12) from theft.
Certificate rollout	Automatic creation, rollout and renewal of certificates via SCEP (Simple Certificate Enrollment Protocol) per certificate hierarchy
Certificate revocation lists (CRL)	CRL retrieval via HTTP per certificate hierarchy
OCSF Client	Check X.509 certifications by using OCSF (Online Certificate Status Protocol) in real time as an alternative to CRLs
XAUTH	XAUTH client for registering LANCOM routers and access points at XAUTH servers incl. IKE-config mode. XAUTH server enables clients to register via XAUTH at LANCOM routers. Connection of the XAUTH server to RADIUS servers provides the central authentication of VPN-access with user name and password. Authentication of VPN-client access via XAUTH and RADIUS connection additionally by OTP token
RAS user template	Configuration of all VPN client connections in IKE ConfigMode via a single configuration entry
Proadaptive VPN	Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections. Propagation of dynamically learned routes via RIPv2 if required
Algorithms	3DES (168 bit), AES-CBC and -GCM (128, 192 or 256 bit), Blowfish (128 bit), RSA (1024-4096 bit), ECDSA (P-256-, P-384-, P-521-curves), Chacha20-Poly 1305 and CAST (128 bit). OpenSSL implementation with FIPS-140 certified algorithms. MD-5, SHA-1, SHA-256, SHA-384 or SHA-512 hashes
NAT-Traversal	NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough
LANCOM Dynamic VPN	Enables VPN connections from or to dynamic IP addresses. The IP address is communicated via the ICMP or UDP protocol in encrypted form. Dynamic dial-in for remote sites via connection template
Dynamic DNS	Enables the registration of IP addresses with a Dynamic DNS provider in the case that fixed IP addresses are not used for the VPN connection
Specific DNS forwarding	DNS forwarding according to DNS domain, e.g. internal names are translated by proprietary DNS servers in the VPN. External names are translated by Internet DNS servers
Split DNS	Allows the selective forwarding of traffic for IKEv2 depending on the addressed DNS domain.
IPv4 VPN	Connecting private IPv4 networks

LANCOM 1926VAG-5G

LCOS 10.50

VPN	
IPv4 VPN over IPv6 WAN	Use of IPv4 VPN over IPv6 WAN connections
IPv6 VPN	Connecting private IPv6 networks
IPv6 VPN over IPv4 WAN	Use of IPv6 VPN over IPv4 WAN connections
Radius	RADIUS authorization and accounting, outsourcing of VPN configurations in external RADIUS server in IKEv2, RADIUS CoA (Change of Authorization)
High Scalability VPN (HSVPN)	Transmission of multiple, securely separated networks within a VPN tunnel
IKEv2-EAP	VPN clients can be authenticated with IKEv2-EAP against a central database like Microsoft Windows Server or RADIUS Server
Performance	
Routing-Performance	Data regarding the overall routing performance can be found inside the LANCOM tech paper "Routing-Performance" on www.lancom-systems.com
VoIP	
Number of local subscribers	10 (up to 40 with VoIP +10 Option)
Number of local ISDN subscribers	Up to 2 internal ISDN buses each with 2 parallel channels and each up to 10 telephone numbers
Number of simultaneous VoIP connections	Up to 100 external VoIP connections depending on code conversion, echo canceling and load
Functionality	Hold/Request, Swap, Transfer, Call Forwarding (CFU, CFB, CFNR), number display/suppression (CLIP, CLIR), suppression of second call (Busy on Busy), immediate outgoing line, hunt groups, call diversion, overlap dialing
Hunt groups	Hunt group cascades, Call diversion, simultaneously or sequentially. Automatic forwarding after timeout or when busy/unreachable
Multi login	Registration of several local VoIP terminal devices with the same number/ID.
Call router	Central switching of all incoming and outgoing calls. Number translation by mapping, numeral replacement and number supplementation. Configuration of line and route selection incl. line backup. Routing based on calling and called number, SIP domain and line. Blocking of telephone numbers or blocks of telephone numbers. Inclusion of local subscribers into the number range of an upstream PBX. Supplement/remove line-related prefixes or switchboard numbers.
SIP registrar	Management of local VoIP users/VoIP PBXs, registration at VoIP providers/upstream VoIP PBXs. Service location (SRV) support. Line monitoring for SIP trunk, link, remote gateway and SIP PBX line
SIP proxy	Up to 25 SIP-provider accounts (up to 55 with VoIP +10 Option), up to 4 SIP PBXs incl. line backup. SIP connections from/to internal subscribers, SIP providers and SIP PBXs. Automatic bandwidth management and automatic configuration of the firewall for SIP connections.
SIP gateway	Conversion of analog or ISDN telephone calls to SIP calls, and vice versa. Local ISDN and analog subscribers register as local SIP users, and local ISDN/analog subscribers automatically register as SIP users at upstream SIP PBXs or SIP providers. Number translation between internal numbers and MSN/DDI
SIP trunk	Call switching based on extension numbers to/from VoIP PBXs/VoIP providers (support of the VoIP-DDI functions compliant with ITU-T Q.1912.5). Mapping of entire VoIP telephone number blocks
SIP link	Call switching of any numbers to/from SIP PBXs/SIP providers. Mapping of entire SIP telephone number blocks
Media proxy	Termination and interconnection of multiple media streams. Control of media sessions. IP address and port translation for media stream packets. Connection of parties at media stream level where a call transfer in SIP (REFER) is not possible
Session Border Controller (SBC)	Separation of insecure and secure networks, QoS, management of signaling and voice data, transcoding
Media protocols	RTP, SIPs and SRTP
Supported providers	German Telekom, QSC, Ecotel and Sipgate
ISDN features	Provision of extension lines.
Analog features	Internal FXS ports for one analog terminal device each, or as an analog PBX exchange line.
Audio properties	Echo canceling (G.168) with automatic deactivation during fax transmission, automatic adaptive jitter buffer. Inband tone signaling compliant with EU standards and country-specific. Voice encoding with G.711 -law/A-law (64 kbps)
SIP-Codec support	SIP only: G.711 -law/A-law (64 kbps), G.722, G.723, G.726, G.729, iLBC, PCM (16, 20 and 24 Bit, Mono und Stereo), OPUS, AAC (LC, HE HEv2), MPEG Layer II, ADPCM 4SB. DTMF support (Inband, RFC2833, SIP-INFO)

LANCOM 1926VAG-5G

LCOS 10.50

VoIP	
Fax transmission	Transmission of fax via SIP on the LAN/WAN side with T.38 or G.711. Conversion of SIP fax with T.38 and break-in/break-out at the outside line to ISDN G.711 with service signalisation. Connection and conversion to SIP T.38 or G.711 for SIP, analog or ISDN fax machines. Compatible to SwyxFax on true G.711 SIP lines.
Auto QoS	Automatic dynamic bandwidth reservation per SIP connection. Voice packet prioritization, DiffServ marking, traffic shaping (incoming/outgoing) and packet-size management of non-prioritized connections compared to VoIP. Independent settings for DiffServ marking of signaling (SIP) and media streams (RTP)
VoIP monitoring	Reporting of Call Data Records (CDR) via SYSLOG or e-mail. Status display of subscribers, lines, and connections. Logging of VoIP Call Manager events in LANmonitor. SYSLOG and TRACE for voice connections. Active monitoring even with SNMP
Autoprovisioning	Automatic network and VoIP integration of LANCOM DECT 510 IP base station
SIP ALG	The SIP ALG (Application Layer Gateway) acts as a proxy for SIP communication. For SIP calls the ALG opens the necessary ports for the corresponding media packets. Automatic address translation (STUN is no longer needed).
Cellular radio	
Supported standards	5G, LTE, UMTS and HSPA support (mode of transmission automatically or manually adjustable), 2G/GSM is not supported
Supported 5G modes	5G standalone (SA), 5G non-standalone (NSA)
Supported mobile bands (5G)	n1 (2100 MHz), n2 (1900 MHz), n3 (1800 MHz), n5 (850 MHz), n28 (700 MHz), n41 (2500 MHz), n66 (2100 MHz), n71 (600 MHz), n77 (3700 MHz), n78 (3500 MHz), n79 (4700 MHz)
Supported mobile bands (4G)	B1 (2100 MHz), B2 (1900 MHz), B3 (1800 MHz), B4 (1700 MHz), B5 (850 MHz), B7 (2600 MHz), B8 (900 MHz), B12 (700 MHz), B13 (700 MHz), B14 (700 MHz), B17 (700 MHz), B18 (850 MHz), B19 (850 MHz), B20 (800 MHz), B25 (1900 MHz), B26 (850 MHz), B28 (700 MHz), B29 (700 MHz), B30 (2300 MHz), B32 (1500 MHz), B34 (2000 MHz), B38 (2600 MHz), B39 (1900 MHz), B40 (2300 MHz), B41 (2500 MHz), B42 (3500 MHz), B43 (3700 MHz), B46 (5200 MHz), B48 (3500 MHz), B66 (1700 MHz), B71 (600 MHz)
Supported mobile bands (3G)	Band 1 (2100 MHz), Band 2 (1900 MHz), Band 3 (1800 MHz), Band 4 (1700 MHz), Band 5 (850 MHz), Band 6 (800 MHz), Band 7 (2600 MHz), Band 8 (900 MHz), Band 9 (1700 MHz), Band 19 (800 MHz)
Maximum transmission power	+23 dBm
Diversity support	Receive diversity on the aux antenna (3G); MIMO (2x2) for LTE (4G); MIMO (4x4) for 5G
Supported SIM card formats*	Mini-SIM (2FF), Micro-SIM (3FF) via adaptor, Nano-SIM (4FF) via adaptor
Multi-SIM support	Supported
*) Note	LANCOM Systems recommends the use of a standard SIM (2FF / Mini-SIM)
Interfaces	
WAN: G.FAST / VDSL / ADSL2+	<ul style="list-style-type: none"> > G.FAST compliant with ITU G.9700 and G.9701, profiles 106a, 212a > VDSL2 compliant with ITU G.993.2, profiles 8a, 8b, 8c, 8d, 12a, 12b, 17a, 35b > VDSL Supervectoring as per ITU G.993.2 (Annex Q) > VDSL2 Vectoring: as per ITU G.993.5 (G.Vector) > ADSL2+ over ISDN as per ITU G.992.5 Annex B/J with DPBO, ITU G.992.3/5 and ITU G.992.1 > ADSL2+ over POTS as per ITU G.992.5 Annex A/M with DPBO, ITU G.992.3 and ITU.G.992.1 > Supports one virtual ATM circuit (VPI, VCI pair) at a time
G.FAST / VDSL / ADSL2+	1 G.FAST/VDSL/ADSL2+- and 1 VDSL / ADSL2+ modem integrated
WAN: Ethernet	10/100/1000 Mbps Gigabit Ethernet
Ethernet ports	6 individual 10/100/1000 Mbps Ethernet ports, 2 of them are set to WAN; up to 3 ports can be operated as additional WAN ports. Ethernet ports can be electrically disabled within LCOS configuration. The ports support energy saving according to IEEE 802.3az
SFP slot	Slot for Small Form-factor Pluggable Gigabit Ethernet transceivers ('mini-GBIC'). Compatible to optional LANCOM SFP modules for fiber connections over short distances (SX) or long distances (LX). By default a WAN port that can be configured as a LAN port
Port configuration	Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). LAN ports can be operated as a switch or separately. Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing. DMZ ports can be operated with their own IP address range without NAT
USB 2.0 host port	USB 2.0 hi-speed host port for connecting USB printers (USB print server), serial devices (COM port server), USB data storage (FAT file system); bi-directional data exchange is possible
ISDN	2x internal ISDN BRI port (NT)

LANCOM 1926VAG-5G

LCOS 10.50

Interfaces	
Analog	4x internal FXS ports (Analog1, Analog2, Analog3, Analog4) each for one analog device
Serial interface	Serial configuration interface / COM port (RJ45): 9,600 - 115,000 baud
Management and monitoring	
Management	LANCOM Management Cloud, LANconfig, WEBconfig, LANCOM Layer 2 management (emergency management)
Management functions	Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job
Monitoring	LANCOM Management Cloud, LANmonitor, WLANmonitor
Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events
Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG, Layer 7 Application Detection including application-centric tracking of traffic volume
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
Netflow	Export of information about incoming and outgoing IP traffic
SD-LAN	SD-LAN – automatic LAN configuration via the LANCOM Management Cloud
SD-WAN	SD-WAN – automatic WAN configuration via the LANCOM Management Cloud
Hardware	
Weight	5,50 lbs (2,50 kg)
Power supply	Internal power supply unit (110–230 V, 50-60 Hz)
Environment	Temperature range 0–40° C; humidity 0–95%; non-condensing
Housing	Robust metal housing, network connectors on the front, 1U (345 x 44 x 253 mm > W x H x D) with removable mounting brackets
Fans	1 silent fan
Power consumption (max)	38 watt
Declarations of conformity*	
Europe/EFTA	CE
IPv6	IPv6 Ready Gold
Country of Origin	Made in Germany
*) Note	You will find all declarations of conformity on our website at www.lancom-systems.com/doc
Scope of delivery	
Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
Cable	1 Ethernet cable, 3 m
Cable	EU version: IEC power cord, WW version: country-specific IEC power cords are separately available
Cable	2x DSL cable for IP based communications incl. galvanic signature, 4,25m
Adapter	4x TAE adapter (RJ11 to TAE)
Antennas	Four 2 dBi 5G/LTE/UMTS-antennas
Support	
Warranty	<ul style="list-style-type: none"> > 3 years > For details, please refer to the General Warranty Conditions at: www.lancom-systems.com/warranty-conditions.
Software updates	Regular free updates as part of the LANCOM Software Lifecycle Managements (www.lancom-systems.com/lifecycle).
Manufacturer support	Free technical manufacturer support as part of the LANCOM Software Lifecycle Management (www.lancom-systems.com/lifecycle).

LANCOM 1926VAG-5G

LCOS 10.50

Software	
Software Lifecycle Management	After discontinuation, the device is subject to the LANCOM Software Lifecycle Management. Details can be found at: www.lancom-systems.com/lifecycle .
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security.
Options	
VPN	LANCOM VPN-50 Option (50 channels), item no. 61405
VPN	LANCOM VPN-100 Option (100 channels), item no. 61407
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 500), 1 year subscription, item no. 61590
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 500), 1 year subscription, item no. 61591
LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 500), 1 year subscription, item no. 61592
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 500), 3 year subscription, item no. 61593
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 500), 3 year subscription, item no. 61594
LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 500), 3 year subscription, item no. 61595
LANCOM Warranty Basic Option M	Option to extend the manufacturer's warranty from 3 to 5 years, item no. 10711
LANCOM Warranty Advanced Option M	Option to extend the manufacturer's warranty from 3 to 5 years and replacement of a defective device, item no. 10716
LANCOM Public Spot	Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network, item no. 60642
LANCOM Public Spot PMS Accounting Plus	Extension of the LANCOM Public Spot (XL) Option for the connection to hotel billing systems with FIAS interface (such as Micros Fidelio) for authentication and billing of guest accesses for 178x/19xx routers, WLCs, and current central-site gateways, item no. 61638
LANCOM WLC Basic Option for Routers	LANCOM WLC Basic Option for Routers for up to 6 managed LANCOM access points or WLAN routers, item no. 61639
LANCOM WLC AP Upgrade +6	LANCOM WLC AP Upgrade +6 Option, enables your WLC to manage 6 Access Points/WLAN router (additive up to 30) in addition, item no. 61629
LANCOM VoIP +10 Option	Upgrade for LANCOM VoIP router with 10 additional internal VoIP numbers (additionally up to 40) and 10 external SIP lines (additionally up to 55) item no. 61423
LANCOM Management Cloud	
LANCOM LMC-C-1Y LMC License	LANCOM LMC-C-1Y License (1 Year), enables the management of one category C device for one year via the LANCOM Management Cloud, item no. 50106
LANCOM LMC-C-3Y LMC License	LANCOM LMC-C-3Y License (3 Years), enables the management of one category C device for three years via the LANCOM Management Cloud, item no. 50107
LANCOM LMC-C-5Y LMC License	LANCOM LMC-C-5Y License (5 Years), enables the management of one category C device for five years via the LANCOM Management Cloud, item no. 50108
Accessories	
LANCOM DECT 510 IP (EU)	Professional DECT base station for up to 6 DECT phones, network integration and configuration via LANCOM VoIP router, 4 simultaneous calls possible, highest voice quality, power supply via PoE or power supply unit, item no. 61901
1000Base-BX20-U SFP module	LANCOM SFP-AON-1, item no. 60200
GPON ONT SFP module	LANCOM SFP-GPON-1, item no. 60199
1000Base-SX SFP module	LANCOM SFP-SX-LC1, item no. 61556
1000Base-LX SFP module	LANCOM SFP-LX-LC1, item no. 61557
SFP copper module	LANCOM SFP-CO1, item no. 61494
VPN Client Software	LANCOM Advanced VPN Client for Windows 7, Windows 8, Windows 8.1, Windows 10, single license, item no. 61600
VPN Client Software	LANCOM Advanced VPN Client for Windows 7, Windows 8, Windows 8.1, Windows 10, 10 licenses, item no. 61601
VPN Client Software	LANCOM Advanced VPN Client for Windows 7, Windows 8, Windows 8.1, Windows 10, 25 licenses, item no. 61602
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), single license, item no. 61606

LANCOM 1926VAG-5G

LCOS 10.50

Accessories	
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), 10 licenses, item no. 61607
LANCOM Power Cord (UK)	IEC power cord, UK plug, item no. 61650
LANCOM Power Cord (CH)	IEC power cord, CH plug, item no. 61652
LANCOM Power Cord (AU)	IEC power cord, AU plug, item no. 61653
*) Note	Support for third-party accessories (SFP and DAC) is excluded and cannot be granted
Item number(s)	
LANCOM 1926VAG-5G (EU)	62124

LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and/or omissions. 12/21