

Rittal – The System.

Faster – better – everywhere.

Hygrostat – SK 3118.000

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygrostat – SK 3118.000

created: 12.07.2021 on www.rittal.com/com-en



Product description

Description:	Activates the heater and/or fan when a preset relative humidity in the enclosure is exceeded. This reduces the relative humidity and prevents condensation on assemblies and electronic components.
Benefits:	Time-saving connection technique using a terminal strip with a screw connection from the outside. Flexible mounting on a vertical or horizontal 35 mm support rail to EN 50 022, and snap fastening in the enclosure section or on the mounting plate using the supplied adaptor
Technical specifications:	Contact population: Single-pole change-over contact as a quick-break contact Permissible contact load: AC ~ 5 (0.2) A (inductive load at $\cos \varphi = 0.6$)/DC = max. 20 W Setting range: 50 – 100% relative humidity Switching difference: approx. 4%
Colour:	RAL 7035

Product description

Rated operating voltage:	24 V - 250 V, 1~ 24 V - 75 V (DC)
Dimensions:	Width: 71 mm Height: 71 mm Depth: 33.5 mm
eCl@ss 8.0/8.1:	27210708
Packs of:	1 pc(s).
Weight/pack:	0.1 kg

EAN:	4028177036734
Customs tariff number:	90321080
ETIM 7.0:	EC002008
ETIM 6.0:	EC002008
eCl@ss 8.0/8.1:	27210708
eCl@ss 6.0/6.1:	27210708
Product description:	SK Hygrostat, 24-230 V, 1~, 12-75 V (DC), Colour RAL 7035, WHD: 71 x 71 x 33.5 mm
Approvals	
Approvals:	CCC exception letter UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity