



8 Port Multi AV to HDMI & VGA Presentation Switch

No.: 38273

Description

- Converts and Scales 8 AV Inputs to resolutions up to Full HD 1080p
- Accepts HDMI, VGA, Component & Composite video signals
- Simultaneous video output via VGA and 2 x HDMI
- Controlled by IR, OSD, RS-232, Telnet and Web GUI (IP/Ethernet)
- 2 Year Warranty

Featuring 8 AV inputs which can be converted and scaled to resolutions up to Full HD 1080p this AV Conversion Switch is an ideal addition to any meeting or conference room, lecture hall or auditorium. Any of the available inputs (3 x HDMI, 3 x VGA & Audio, Component Video & Audio and Composite Video & Audio) can be simultaneously shown across display equipment connected to each of the outputs (2 x HDMI and VGA). These three outputs provide compatibility with both current and legacy AV displays and can be combined with [LINDY HDMI or VGA extenders](#) to reach remotely located displays.

In addition to its video capabilities the AV Conversion Switch also features Digital to Analogue and Analogue to Digital conversion and can also embed analogue audio to HDMI video signals. With simultaneous audio output via 3.5mm stereo socket and Coaxial SPDIF the Switch can be directly connected to almost any AV Receiver in the market, whilst for further flexibility one of the HDMI outputs can also be used for audio.

The Switch features remote configuration and control via RS-232, Telnet and Web GUI as well as locally by OSD and IR making it simple to integrate within automated installations.

Package Contents:

AV Conversion Switch
IR Remote Control with 2 x AAA Alkaline batteries
IR Extender Cable
VGA to 3 x RCA (RGB) Adapter cable
Mounting Brackets
Multi Country Power Supply with UK, EU, US & AUS adapters +5V DC 3A with 5.5/2.1mm DC Connector
LINDY Quick Install Guide

Technical details

Specifications

- AV Interface: HDMI, VGA
- Interface Standard: HDMI 1.3a
- Supports Bandwidth: 6.75 Gbps
- Maximum Resolution: 1920x1080@60Hz 4:4:4 12bit
- HDCP Support: 1.2
- Supported Audio: Audio Pass-through, Stereo Audio
- Separate Audio Ports: 3.5mm Audio, RCA Audio
- IR Support: -
- CEC Support: -
- Serial Interface: RS232
- Special Features: Digital/Analogue Conversion, Scaling

Connectors

- Input: 3 x HDMI (Female) + 3.5mm (Female), 3 x VGA (Female) + 3.5mm (Female), Component Video (Female) + 2 x RCA (Female), Composite Video (Female) + 2 x RCA (Female)
- Output: 2 x HDMI (Female), VGA (Female) + 3.5mm (Female), Coaxial Digital Audio (Female)
- Control: RS232, RJ45 (IP)
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions WxDxH: 432x183x47mm (17.01x7.2x1.85in)
- Housing Material: Metal
- Net Weight: 2.59kg (5.71lb)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 60°C (-4°F - 140°F)
- Humidity: 20 – 90% RH (non-condensing)
- Power Requirements: 5VDC 3A
- Colour: Black

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 520x290x95mm (20.47x11.42x3.74in)
- Gross Weight: 3.05kg (6.72lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package content

- AV Conversion Switch
- IR Remote Control with 2 x AAA Alkaline batteries
- IR Extender Cable
- VGA to 3 x RCA (RGB) Adapter cable
- Mounting Brackets
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

Purchasing Information

- No.: 38273
- EAN: 4002888382731