

Product datasheet

Specifications



Rack Air Removal Unit SX 100-240V 50/60HZ for NetShelter 600mm enclosures.

ACF400

Overview

Presentation	High-density equipment creates an environment where traditional air distribution methods are often not effective. Densely packed enclosures can cause IT equipment to overheat, resulting in downtime. The Rack Air Removal Unit SX captures exhaust heat, returns the warm air to the plenum and eliminates hot spots from the data center. Through automatic fan speed control based upon temperature, the fans will self-adjust for optimal performance. With a unit-mounted LCD display, users can view temperatures at the rack, monitor alarm conditions and adjust unit set points. The integrated network management card allows for remote monitoring and control. This space-saving solution mounts to the back of either the NetShelter SX or VX enclosure, requiring zero U space.
--------------	--

Lead time

Main

Main Input Voltage	100 V 120 V 200 V 208 V 230 V
Plug standard	IEC 60320 C14 NEMA 5-15P
Number of cables	2
Provided equipment	Documentation CD Installation guide Operations and maintenance manual

General

Air discharge option	Upflow Ducted
Air flow	755.12 l/s

Physical

Colour	Black
Height	191.8 cm
Width	59.7 cm
Depth	25.4 cm
Net weight	67.26 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Input power	1200 W
Network frequency	50/60 Hz

Conformance

Product certifications	cUL listed CE UL listed VDE
Standards	EN 55022 class A EN 55024 FCC part 15 class A ICES-003 IEC 61000-3-2 IEC 61000-3-3

Environmental

Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	0...50 °C
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Storage altitude	0.00...4572.00 m
Acoustic level	79 dBA

Communications & Management

Control panel	Multifunction LCD status and control console
---------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	90 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Lead free	Yes

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Recommended replacement(s)