

## 19" Server Cabinet 25 U with top air A/C unit 1200 W, 800x1000x1200 +415



<b>Artikelnummer/SKU</b>	20656-DK-1.2
<b>Produkt</b>	delivery time 1-2 weeks
<b>Verfügbarkeit</b>	
<b>HE/U</b>	25
<b>Breite/width</b>	800
<b>Tiefe/depth</b>	1000
<b>Höhe/height</b>	1200+415
<b>kW</b>	1.2
<b>Segmentation</b>	No

### 19" Server Climate Cabinet with air conditioning unit with 1200W

- Glazed front door
- Full rear door
- Rotary lever handles lockable
- Removable side panels
- Stable depth-adjustable 19" mounting angles 4 x 25 U
- Max. 19" mounting depth 710 mm
- Cable entry in base module
- Earthing kit
- Levelling feet
- Air Ducts for increased airflow control
- Roof air conditioner 1200 W
- Operating voltage Volt 230 Hz, 50-60
- Pluggable terminal strip for power connection
- Powder coating RAL7035 light gray

#### Note to the site :

- The location and thus the arrangement of the heat must be selected so that good ventilation is ensured.
- Depending on the location of the system of distance on several directly mounted adjacently to the wall should be at least 200 mm.
- The refrigerator must be installed and operated in horizontal position (max. deviation: 2 °).
- The site must be free from excessive dirt and moisture.
- The ambient temperature must not be higher than 55 ° C.
- A condensate drain must be enabled.
- The network connection specifications on the nameplate of the unit must be ensured.