

Professional LCD Laser Projector

Sharp E501U



High Brightness, Low Cost

For outstanding projection performance at an impressively low total cost of ownership, the Sharp E501U appeals to cost-conscious users who demand professional reliability. Delivering 5,000 lumens of brightness and the vivid colour reproduction of 3LCD technology, this compact WUXGA laser projector packs a powerful punch while weighing just 5kg.

Designed for versatility, the E501U offers flexible installation options and a long operational life, making it a natural fit for classrooms, training facilities, and meeting rooms. Combining high performance, low maintenance, and exceptional value, it's the smart choice for any budget-aware installation.

Benefits

Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.

Enjoy a Lower TCO – highest reliability, maintenance free operation, low power consumption and up to 20000 hours life; the Laser light source results in a significantly lower total cost of ownership.

Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Cost Saving Device Management – save effort whilst administrating all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Specifications

Product Information

Product Name

Sharp E501U

Product Group

Professional LCD Laser Projector

Order Code

60006200

Image

Projection Technology

3LCD Technology

Native Resolution

1920 x 1200
(WUXGA)

Aspect Ratio

16:10

Contrast Ratio

5000000:1

Brightness

5000 Lumen (approx. 60% in Eco Mode); compliant with ISO21118-2020

Lamp

Laser Light Source

Light Source Life [hrs]

20000¹

Lens

F= 1.6–1.76, f= 19.16–23.02 mm

Keystone correction

+/- 30° manual horizontal / +/- 30° manual vertical

Projection Factor

1.37 – 1.65 : 1

Projection Distance [m]

0.85 – 11

Screen Size (diagonal) [cm] / [inch]

Maximum: 762 / 300"; Minimum: 76.2 / 30"

Zoom

Manual; x1.2

Focus Adjustment

Manual

Supported Resolutions

1920x1200 (Maximum resolution of analog input);	3840 x 2160 (Maximum resolution of digital input);	3840x2160 @ 30hz digital
--	---	-----------------------------

Connectivity

Digital

Input: 2 x HDMI™ supporting HDCP

Audio

Output: 1 x 3.5 mm Stereo Mini Jack (variable)

Control

Input: 1 x D-Sub 9 pin (RS-232) (male)

LAN

1 x RJ45

USB

1 x Type B (for Service); 1x Type A (USB 2.0 high speed) with 1.5A Power Supply

Video Signals

NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Remote Control

Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Eco Mode Control; Freeze; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Select (up, down, left, right); Source Select; Test Picture

Electrical

Power Supply

100-240 V AC; 50 - 60 Hz

Power Consumption [W]

310 (Normal) / 155 (Eco) / 2 (Network Stand-by) / 0.5 (Stand-by)

Mechanical

Dimensions (W x H x D) [mm]

390 x 128 x 294 (without lens and feet)

Weight [kg]

5

Fan Noise [dB (A)]

39 / 29 (Eco / Normal)

Colour Versions

White

Environmental Conditions**Operating Temperature [°C]**

5 to 45

Operating Humidity [%]

20 to 80

Storage Temperature [°C]

-10 to 50

Storage Humidity [%]

20 to 80

Ergonomics**Safety and Ergonomics**

CE; ErP; RoHS; TUEV Type Approved

Speakers [W]

1 x 16 (mono)

Additional Features**Special Characteristics**

Carbon Savings Meter; Control ID Function; Crestron RoomView; DICOM simulation; Free Tilt; Geometric Correction; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Light Source Adjustment; Magnify; NaViSet Administrator 2; Optional User Logo; OSD with 30 languages; Password Security System; Portrait Setting; Quick Start; Source Select with Beep Function; Test Pattern; Unique Power Saving Functions; USB Viewer

Green Features**Ecological Materials**

Downloadable manuals; ECO packaging

Ecological Standards

ErP compliant; RoHS compliant

Warranty**Projectors**

3 years pan-European service

Light Source

3 years or 10000h (whatever comes first)

Shipping Content**Shipping Contents**

2x AAA Batteries; IR Remote Control (477E); Power Cord (3 m); Projector; Quick Setup Guide; Security Sticker; Users Manual

Optional Accessories**Optional Accessories**

Universal Ceiling Mounts (PJ01UCM, PJ02UCMPF)

¹ 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.



CE



RoHS



TUEV Type Approved



ErP

This document is © 2025 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 24.11.2025